

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

JUL 10 2009

Sundry Notices and Reports on Wells

Bureau of Land Management
Farmington Field Office1. Type of Well
GAS

2. Name of Operator

ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit D (NWNW), 690' FNL & 665' FWL, Section 29, T30N, R5W, NMPM

5. Lease Number
SF-0787406. If Indian, All. or
Tribe Name7. Unit Agreement Name
San Juan 30-5 Unit8. Well Name & Number
San Juan 30-5 Unit 97M9. API Well No.
30-039-3070810. Field and Pool
Basin DK/Blanco MV11. County and State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction☐ Plugging☐ Non-Routine Fracturing☐ Final Abandonment☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection

RCVD JUL 14 '09

OIL CONS. DIV.
DIST. 3

13. Describe Proposed or Completed Operations

07/01/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3417' - Inter TD reached 7/3/09. Circ. hole. TIH w/ 80jts, 7", 20#, J-55 ST&C set @ 3408'. 07/05/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 19sx (56cfr-10bbls) premium lite cmt. Lead w/ 395sx (841cf-150bbls) premium lite cmt w/ 8% bentonite, 3% CACL, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. Tail w/ 81sx (112cf-20bbls) Type III cmt w/ 1% CACL, .25pps celloflake, .2% FL-52. Drop plug & displaced w/ 135bbls FW. Bump plug. Circ. 60bbls cmt to surface. Plug Down @ 11:56hrs on 7/5/09. RD cmt. WOC

07/05/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min. Test - OK. Drilled ahead w/ 6 1/4" bit to 7711' (TD) TD reached 7/7/09. Circ. hole & RIH w/ 194jts, 4 1/2", 11.6#, L-80 LT&C set @ 7710'. 07/08/09 RU to cmt. Pre-flush w/ 10bbls GW, 2 bbls FW. Pumped scavenger 9sx (28cf-5bbls) premium lite cmt w/ .25pps celloflake, .3% CD-32, 6.25pps LCM-1, 1% FL-52. Tail w/ 304sx (602-107bbls) premium lite cmt w/ .3% CD-32, .25pps celloflake, 1% FL-52, 6.25 LCM-1. Flushed lines w/ 15bbls FW. Drop plug & displaced w/ 120bbls FW. Bump plug. Plug down @ 16:30hrs on 7/8/09. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 02:30hrs on 7/9/09.

PT will be conducted by Completion Rig. Results & TOC will appear on next report.

APD/ROW

14. I hereby certify that the foregoing is true and correct.

Signed Crystal Tafoya Crystal TafoyaTitle: Regulatory Technician Date 7/11/2009

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOCD

JUL 13 2009

FARMINGTON FIELD OFFICE
BY shy