UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

ILIL 20 2009

Sundry Notices and Reports on Wells		Bureau of Land Management Farmington Field Offices
	5.	Lease Number
	_	SF-079351
Type of Well	6.	If Indian, All. or
GAS		Tribe Name
	7.	Unit Agreement Name
Name of Operator	ι.	San Juan 32-8 Unit
Name of Operator		San Juan 32-6 One
ConocoPhillips		
CONCOCHINIPS		•
	- 8.	Well Name & Number
Address & Phone No. of Operator		San Juan 32-8 Unit 10A
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
	-	20.045.24605
Location of Well, Footage, Sec., T, R, M		30-045-34605
	10.	Field and Pool
Surface: Unit O (SWSE), 770' FSL & 1465' FEL, Section 24, T31N, R8W, NMPM	10.	Basin DK/Blanco MV
Bottomhole: Unit P (SESE), 660' FSL & 660' FEL, Section 24, T31N, R8W, NMPM		
	11.	County and State
		San Juan, NM
Recompletion New Construction X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection		Other – Casing Report RCVD JUL 23 '09
X Subsequent Report Plugging Water Shut off Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test - OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls im Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 17sx (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5p 10bls FW. Bump plug. Circ. 20bbls cmt to surface. Plug down @ 03:30hrs on 7/15/09. RD cmt. WOC 15/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test - OK. Drilled ahea 16/09. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-flux	tole. TIH s) 75:25 c topps Gilson C. ead w/ 6 1 ush w/ 10	PCVD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations 08/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test - OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls imm Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 1/7sx (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5p 1/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test - OK. Drilled ahea 1/09. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-fluenger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps Kolite, 3.5% bentonite, .25% FL-5	tole. TIH s) 75:25 of pps cello pps Gilsor C. ad w/ 6 1 ush w/ 10 52, .15% l	PCVD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations 08/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test - OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls im Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 1/7sx (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5p 1/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test - OK. Drilled ahea 1/209. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-fluenger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, .25% FL-52, .15% Fr 1/2004 w/ 420sx (605cf-108bbls) 50:50 POZ cmt w/ .3.5% bentonite, .25pps celloflake, .25% FL-52, .15% Fr	tole. TIH s) 75:25 c pps Gilsor C. ad w/ 6 1 ush w/ 10 52, .15% l	PCVD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test - OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls im Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 1/7sx (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5p 1/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test - OK. Drilled ahea 1/209. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-flux enger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, .25pps celloflake, .25% FL-52 1/2008 W Sump plug & displaced w/ 125bbls FW. Bump plug. Plug down @ 20:15hrs on 7/17/09. RD cmt. WOC.	tole. TIH s) 75:25 c pps Gilsor C. ad w/ 6 1 ush w/ 10 52, .15% l	PCVD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations 08/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test - OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. hr 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls im Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, 25r/05x (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5pbls FW. Bump plug. Circ. 20bbls cmt to surface. Plug down @ 03:30hrs on 7/15/09. RD cmt. WOC 5/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test - OK. Drilled ahe 1/09. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-fluenger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps Kolite, 3.5% bentonite, .25% FL-5w/420sx (605cf-108bbls) 50:50 POZ cmt w/ 3.5% bentonite, .25pps celloflake, .25% FL-52, .15% From 1/18/09. 1/18/09.	tole. TIH s) 75:25 c pps Gilsor C. ad w/ 6 1 ush w/ 10 52, .15% l	PCVD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test - OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls im Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 1/7sx (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5p 1/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test - OK. Drilled ahea 1/209. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-flux enger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, .25pps celloflake, .25% FL-52 1/2008 W Sump plug & displaced w/ 125bbls FW. Bump plug. Plug down @ 20:15hrs on 7/17/09. RD cmt. WOC.	tole. TIH s) 75:25 c pps Gilsor C. ad w/ 6 1 ush w/ 10 52, .15% l	PCVD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations 08/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test - OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. hr 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls im Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, 25r/05x (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5pbls FW. Bump plug. Circ. 20bbls cmt to surface. Plug down @ 03:30hrs on 7/15/09. RD cmt. WOC 5/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test - OK. Drilled ahe 1/09. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-fluenger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps Kolite, 3.5% bentonite, .25% FL-5w/420sx (605cf-108bbls) 50:50 POZ cmt w/ 3.5% bentonite, .25pps celloflake, .25% FL-52, .15% From 1/18/09. 1/18/09.	tole. TIH s) 75:25 c pps Gilsor C. ad w/ 6 1 ush w/ 10 52, .15% l	PCVD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder.
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection Describe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test_OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 1721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls imm Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 h 175x (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5pbls FW. Bump plug. Circ. 20bbls cmt to surface. Plug down @ 03:30hrs on 7/15/09. RD cmt. WOC 5/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test_OK. Drilled ahead (90). Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-flux renger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps Kolite, 3.5% bentonite, .25% FL-5 w/ 420sx (605cf-108bbls) 50:50 POZ cmt w/ .5/9ps celloflake, 5pps Kolite, 3.5% bentonite, .25% FL-52, .15% From plug & displaced w/ 125bbls FW. Bump plug. Plug down @ 20:15hrs on 7/17/09. RD cmt. WOC. 1/18/09. 1/18/09. 2/18/09. 2/18/09. 2/18/09.	tole. TIH s) 75:25 c pps Gilsor C. ad w/ 6 1 ush w/ 10 52, .15% l	PCVD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder.
X Subsequent Report Plugging Casing Repair Water Shut off Conversion to Injection Describe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test_OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 1721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls) 10	tole. TIH s) 75:25 of pps Gilson C. ad w/ 6 1 ush w/ 10 62, .15% l riction rec ND BOP	PCUD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder. E. NU WH. RD RR @ 06:00hrs
X Subsequent Report Plugging Water Shut off Conversion to Injection Describe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test_OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. hr 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls ium Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 r/sx (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5p bils FW. Bump plug. Circ. 20bbls cmt to surface. Plug down @ 03:30hrs on 7/15/09. RD cmt. WOC 5/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test_OK. Drilled ahe 1/09. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-flux enger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, .5pps Kolite, 3.5% bentonite, .25% FL-5 w/ 420sx (605cf-108bbls) 50:50 POZ cmt w/ 3.5% bentonite, .25pps celloflake, .25% FL-52, .15% Fr p plug & displaced w/ 125bbls FW. Bump plug. Plug down @ 20:15hrs on 7/17/09. RD cmt. WOC. 1/18/09. will be conducted by Completion Rig. Results & TOC will appear on next report.	tole. TIH s) 75:25 of pps Gilson C. ad w/ 6 1 ush w/ 10 62, .15% l riction rec ND BOP	PCUD JUL 23 '09 OIL CONS. DIV. DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder, E. NU WH. RD RR @ 06:00hrs
X Subsequent Report Plugging Casing Repair Water Shut off Conversion to Injection Describe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test_OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 1721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls) 10	tole. TIH s) 75:25 of pps Gilson C. ad w/ 6 1 ush w/ 10 62, .15% l riction rec ND BOP	PCUD JUL 23 '09 DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped PR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder. E. NU WH. RD RR @ 06:00hrs
X Subsequent Report Plugging Casing Repair Water Shut off Conversion to Injection Pescribe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test_OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls im Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 75sx (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5pbls FW. Bump plug. Circ. 20bbls cmt to surface. Plug down @ 03:30hrs on 7/15/09. RD cmt. WOC 15/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test_OK. Drilled ahe 16/09. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-fluenger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps Kolite, 3.5% bentonite, .25% FL-5 18/09. w/ 420sx (605cf-108bbls) 50:50 POZ cmt w/ 3.5% bentonite, .25pps celloflake, .25% FL-52, .15% Fr 18/09. plug & displaced w/ 125bbls FW. Bump plug. Plug down @ 20:15hrs on 7/17/09. RD cmt. WOC. 1/18/09. 18/2004 I hereby certify that the foregoing is true and correct. 18/2005 Crystal Tafoya Title Regulatory of the Regulat	tole. TIH s) 75:25 of pps Gilson C. ad w/ 6 1 ush w/ 10 62, .15% l riction rec ND BOP	PCUD JUL 23 '09 DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ (4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped PR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder. E. NU WH. RD RR @ 06:00hrs
X Subsequent Report Plugging Casing Repair Water Shut off Conversion to Injection Describe Proposed or Completed Operations 8/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test_OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. hr 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls ium Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, 25 robs FW. Bump plug. Circ. 20bbls cmt to surface. Plug down @ 03:30hrs on 7/15/09. RD cmt. WOC 5/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test_OK. Drilled ahea/09. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-fluenger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps Kolite, 3.5% bentonite, .25% FL-52, .15% FL-5 plug & displaced w/ 125bbls FW. Bump plug. Plug down @ 20:15hrs on 7/17/09. RD cmt. WOC. 1/18/09. 1/18/09. 2/18/09. 2/18/09. 2/18/09. 3/18/09	tole. TIH s) 75:25 of pps Gilson C. ad w/ 6 1 ush w/ 10 62, .15% l riction rec ND BOP	PCUD JUL 23 '09 DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set and w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ .4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped FR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder. E. NU WH. RD RR @ 06:00hrs an Date 07/20/2009
X Subsequent Report Plugging Casing Repair Water Shut off Conversion to Injection Pescribe Proposed or Completed Operations 18/2009 MIRU HP 282. NU BOPE. PT csg to 600#/30 min @ 10:30hrs on 7/9/09. Test_OK 19/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3730' - Inter TD reached 7/12/09. Circ. h 721'. 7/14/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (56cf-10bbls im Medasillicate, 20% anti-foam. Lead w/ 441sx (926cf-165bbls) Class G cmt w/ .2% anti-foam, .25 75sx (122cf-22bbls) Class G cmt w/ .1% anti-foam, 2% bentonite, .25pps celloflake, .2% dispersant, 5pbls FW. Bump plug. Circ. 20bbls cmt to surface. Plug down @ 03:30hrs on 7/15/09. RD cmt. WOC 15/2009 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 12:00hrs on 7/15/09. Test_OK. Drilled ahe 16/09. Circ. hole & RIH w/ 196jrs, 4 1/2", 11.6#, L-80 LT&C set @ 8047'. 07/17/09 RU to cmt. Pre-fluenger 15sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps Kolite, 3.5% bentonite, .25% FL-5 18/09. w/ 420sx (605cf-108bbls) 50:50 POZ cmt w/ 3.5% bentonite, .25pps celloflake, .25% FL-52, .15% Fr 18/09. plug & displaced w/ 125bbls FW. Bump plug. Plug down @ 20:15hrs on 7/17/09. RD cmt. WOC. 1/18/09. 18/2004 I hereby certify that the foregoing is true and correct. 18/2005 Crystal Tafoya Title Regulatory of the Regulat	tole. TIH s) 75:25 of pps Gilson C. ad w/ 6 1 ush w/ 10 62, .15% l riction rec ND BOP	PCUD JUL 23 '09 DIST. 3 w/ 90jts, 7", 23#, J-55 ST&C set mt w/ .25pps celloflake, 3% flake, 2% Sodium Silicate. Tail nite. Drop plug & displaced w/ 4" bit to 8048' (TD) TD reached bbls GW, 2 bbls FW. Pumped PR, .15% retarder, .1% anti-foam lucer, 5pps Kolite, .15% retarder. E. NU WH. RD RR @ 06:00hrs