This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## Oil Conservation Division

## **Northwest New Mexico Packer-Leakage Test**

Page 1 Revised June 10, 2003

Operator COP				Lease	e Name	SAN	JUAN 28	-7 UN	IT N	JP.	Well No10
Location of Well	l: Unit Let	ter N	Sec	18	Twp	027N	Rg	е	007W	_ API	# 30-039-07036
Name of Reservoir or Pool			or Pool	Type of Prod				Method of Prod			Prod Medium
Upper Completion	MV			Gas	Gas			Artificial Lift			Tubing
Lower Completion	DK			Gas	Gas			Artificial Lift			Tubing
			F	Pre-Flow S	Shut-In I	Pressu	ıre Data				
Upper Hour, Date, Shut-In			Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	
Completion	7/1/2009			201	201 hours			230			Yes
Lower	Hour, Date, Shut-In				Length of Time Shut-In				s. PSIG		Stabilized?(Yes or No)
Completion	7/1/20	009		201 hours					Yes		
Commenced a	t: 7/6/200						oducing (		or Lowe	er): Up	eer
Time		Lapsed Time		PRESSURE P			Prod Z	Prod Zone			
(date/time)	Since*		U	Upper zone Lowe		zone	Temperature		Remarks		
7/7/2009 9:53:00 AM 23			230 397				both zones shut in, turned on the DK				
7/9/2009 9:00:00 AM 71			237	237 146				lower zone flowing, upper zone shut in			
Production rate	during test	Ī									
Oil:	l:BPOD Based on:		B	Bbls. InHrs				GravGC			GOR
Gas		_MCFPD; T	est thru (C	Orifice or M	leter)						
				did Took C	Should be F	<b>.</b>	D.1.				
Upper	Hour Date	Shut-In	<u>N</u>	/lid-Test S				SI Proc	e BSIG		Stabilized?(Yes or No)
Completion	Upper Hour, Date, Shut-In Completion			Length of Time Shut-In				SI Press. PSIG . Stabilized?(Yes or No)  RCUD JUL 14'09			
Lower Completion	Hour, Date, Shut-In			Length of Time Shut-In							Stabilized?(Yes or No)
				(Continu	ue on re	verse s	side)			1	DIST. 3

## Flow Test No. 2

Commenced	at:		Zone Pro	oducing (Uppe	r or Lower)
Time	Lapsed Time	ļ	SURE	Prod Zone	
(date/tim	e) Since*	Upper zone	Lower zone	Temperature	Remarks
					·
Oil:	BPOD Based on:	Bbls. In	Hrs.		GravGOR
ias	MCFPD; Test	thru (Orifice or M	leter)		
Remarks:			<u> </u>		
hereby certify	that the information hereir	n contained is true	and complete	to the best of	my knowledge.
Approved:	JUL 2 3 2009	20	Opera	tor: COP	
			<del></del>		200
New Iviexic	o Oil Conservation Division G. Tall		By:	Vernon Hugh	
By:	Trees of the	ootor	Title:	Multi-Skilled	Operator
itle:	Deputy Oil & Gas Insported #3	Jecioi,	Date:	Monday, July	, 13. 2009

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual
  completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.
  Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or
  chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or
  the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when
  requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests, immediately prior to the beginning of each flow period, at fifteen-inmute intervals during the first hour thereot, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests, immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Dissision on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).