This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR			Lease	Name SAN	JUAN 29-7 U	NIT	Well No8
ocation of Well	: Unit L	_etter <u>B</u> Se	ec <u>04</u>	Twp029N	Rge _	007W AP	I# 30-039-07671
	N	ame of Reservoir or Pool		Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC		Gas	Gas		icial Lift	Tubing
Lower Completion	MV			Gas		icial Lift	Tubing
			Pre-Flow S	hut-In Pressu	ıre Data		
Completion	6/2	te, Shut-In 3/2009	178	Length of Time Shut-In 178 hours		ess. PSIG 343	Stabilized?(Yes or No) Yes
Lower Completion		te, Shut-In 3/2009	_	Length of Time Shut-In 178 hours		ess. PSIG 175	Stabilized?(Yes or No) Yes
			Flo	w Test No. 1			
Commenced at	: /23/2	2009 10:30:00 AM		Zone Pro	oducing (Upp	er or Lower): U	oeer
Time Lapsed Time (date/time) Since*			PRES Upper zone	SURE Lower zone	Prod Zone Temperatur	l .	Remarks
6/28/2009 10:00:00 AM 120		120	343 175			TURNED ON UP	PPER ZONE
6/29/2009 10.00:0	6/29/2009 10.00:00 AM 144		285	176			
6/30/2009 10:44:0	6/30/2009 10:44:00 AM 168		135	173			
Production rate of	during t	est		•			'
oil:BPOD Based on:B			Bbls. In	Bbls. InHrs		Grav.	GOR
as		MCFPD; Test thr	ru (Orifice or M	leter)			
			Mid Toot S	hut In Proces	uro Dota		•
Upper Completion	Hour, Date, Shut-In			Mid-Test Shut-In Pressure Length of Time Shut-In		ess. PSIG	Stabilized?(Yes or No)
Lower Completion	Hour, Da	te, Shut-In	Length o	Length of Time Shut-In		ess. PSIG	Stabilized?(Yes or No) OIL CONS. DIV.
	,		(Continu	ue on reverse s	side)		DIST. 3

Flow Test No. 2

Commenced at:			Zone Producing (Upper or Lower)						
Time	Lapsed Time		SURE	Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature	}	Remarks			
							-		
			4	,					
L									
Production rate duri	ing test								
Oil:BP	BPOD Based on:		Hrs.	Grav.		GOR			
Gas	MCFPD; Test the	nru (Orifice or M	leter)		,				
		(01							
Remarks:									
· ·									

I hereby certify that	the information herein of	contained is true	and complete	to the best of	my knowledg	ge.			
Approved:	JUL 2 2 2009	20	Opera	tor: BR					
New Mexico Oil	Conservation Division			By: Rhonda Rogers					
Valle G.	Roa		-	Title: Multi-Skilled Operator					
By:			Title: _						
Title:	.puty Oil & Gas Ins	spector,	Date:	Monday, Jul	y 06, 2009				
	District #3	,	_						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for piessure stabilization Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4. For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note it, on an initial packer leakage test, a gas well is being flowed to the
- atmosphere due to lack of a pipeline connection the flow period shall be three hours

- Flow Test No 2 shall be conducted even though no leak was indicated during Flow Test No 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded

with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone

8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3