This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR					Lease	e Name	CANY	ON LA	N LARGO UNIT COM			Well No. 136	
Location of Well: Unit Letter N Se			ec (04 Twp 025N Rge 00				ge	006W	API	# 30-039-82259		
	Name of Reservoir or Pool			l	Type of Prod			Method of Prod			Prod Medium		
Upper Completion	PC		Gas				Flow			Tubing			
Lower Completion	СН				Gas			Flow				Tubing	
Sensitive and the sense of the				Pre-	Flow S	Shut-In	Pressu	re Data	a				
Upper	Hour, Date,	Hour, Date, Shut-In				Length of Time Shut-In				ss. PSIG		Stabilized?(Yes or No)	
Completion	5/31/2009				130 hours				0			Yes	
Lower	Hour, Date,		Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)				
Completion	5/31/2009				81 hours						244	Yes	
Commenced a	at: 6/3/20		50:00 AM							r or Lowe	er): Lov	wer	
Time Lapsed Time			ed Time			SURE	JRE Prod		rod Zone			Remarks	
(date/time	*)) Since		Upper	Upper zone		er zone Tem		Temperature				
6/4/2009 10:05:00 AM			25	0		1:	28	60					
6/5/2009 10:03:00 AM 49			(0		23	60		1				
Production rate	during test	t											
Oil:	Oil:BPOD Based on:				Bbls. In			Grav.			GOR		
										•		** . «,	
Mid-Test Shut-In Pressure Data													
Upper Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)	
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG		Stabilized?(Yes or No)		

(Continue on reverse side)

Flow Test No. 2

Commenced at:			Zone Pro	oducing (Upper or L	ower)				
Time	Lapsed Time	PRES	SURE	Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks				
				-					
	,								
Production rate durin Oil:BPO	g test D Based on:	Bbls. In	Hrs.	Grav.	GOR				
Gas	MCFPD; Test thru (Orifice or Meter)								
Remarks:									
	ne did build pressure, r	received verbal p	permission from	n Kelly Roberts not	to witness				
				•					
I hereby certify that the	ne information herein o	contained is true	and complete	to the best of my ki	nowledge.				
Approved: 111 2	2 2009	20	Operat	or: BR					
New Mexico Oil C	onservation Division		Ву:	By: Tom Stahle					
Dv.		enactor_	Title:	: Multi-Skilled Operator					
Dep Title:	outy Oil & Gas Ins District #3	specioi,	Date:	te: Tuesday, June 16, 2009					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of a noil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests, immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests, all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Dission on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

⁵ Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.