This form is <u>not</u> to be used for reporting packer leakage tests

Completion

NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

in Southeast Ne	ew Mexico	MONITIVESI	NEW WIENICC					ŕ
bp	America Prod	uction Compan	y	1.27		> · ;	Well	۸
Operator 20	10 Energy Cour	t, Farmington	<u>, NM 87401</u>	Lease Na	ame <u>\</u>	ANDEWART	H No. 1	H
Location Of V	Well: Unit Letter.	Sec	II Twp 2	9 N Rge_	8 1	API # 30-0 <u>* 4</u> 5	5-22361	12' 1 ' 10'
		- 10						
	Name of Res	servoir or Pool		f Prod.	1	Iethod of Prod.	Prod. Me	
	11 22	20 (2	(Oil or	Gas),	(F	low or Art. Lift)	(Tbg. Or	Csg.)
Upper Completion	BLANCO	70 M	GA:	S		FLOW	TBG	· (***)
Lower Completion	BLANCO		GA:	S		FLOW ·	TRG	
	••		e-Flow Shut-In	Pressure Da	ıta	* * * *		
Upper	Hour, Date, Shut		Length of Tin			Press. Psig	Stabilized? (Y	es or No)
Completion	06/10/09		72 HOU			155	YES	
Lower	Hour, Date, Shut-In		Length of Time Shut-In		SI	Press. Psig	Stabilized? (Yes or No)	
Completion	06/10/	09	72 HOU	RS		11a	YES	
	·		Flow Test	No. 1			ą	
Commenced	at (hour, date)*				g (Up	per or Lower):		
Time	Lapsed Time PC Pres		ssure mv	Prod. Z		Remarks		
(Hour, Date)	Since*	Upper Compl.	Lower Compl.	Temp	э.			
6/10	DAY 1	154	104			BOTH ZONES	SHUT IN	
6/11	DAY 2	155	109			BOTH ZONES	SHUTIN	
6/12	DAY 3	155	ιιa			BOTH ZONES		
64713	DAY 4	ON 145 4		·13.		FLOW LOWIE	- ZONE	f ~
64 71 14	DAY 5	Marie 1	120	, ,		∹FĽOW "	ZONE	, ,
6 / 15	DAY 6	15%	122			FLOW "	ZONE	
Production rat	e during test 🖈	VERY HIGH LIN	JE PRESSURE -	WELL People	DUCED	Some GAS		
)il:	BOPD based of	nBbl	ss Over-Cor s. In	Hrs.		Grav.	GOR	
Gas:	MCFP.	D; Test thru (Orifi	ice or Meter):					····
		Mi	d-Test Shut-In	Pressure Da	ta		RCVD JUN 24	4m2
Upper						ess. Psig	Stabilized? (Yo	es or No)
Completion			_				nti cons. DIV.	
Lower			Length of Time Shut-In		SI Pr	ess. Psig	Stabilized? (Yes or No)	

(Continue on reverse side)

Flow Test No. 2

Commenced at (hour, date)**				Zone producing (Upper or Lower):			
Time	Lapsed Time	Pc Pre	essure mv	Prod. Zone	Remarks		
(Hour, Date),	Since**	.Upper Compl.	Lower Compl	. Temp.			
6/16		158	્ ૧૱૱	<u>, </u>	Both Zones Shut In		
9/17		159	124		te te te to		
6/18		160	193		ge ge ee e		
6/19		161	120		Start Compressor		
6/20		161	95		115 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
6/21		162	96		v v u		
Production rate	during test						

Oil:	BOPD based on	Bbls. In	-41	Hrs	Grav. 🗓	GOR		
Gas:	MCFPD; Test	thru (Orifice or Meter	r):					
Remarks:		$E_{i}(t)$						
I hereby certify th	nat the information here	ein contained is true ar	nd comp	lete to the b	est of my knowledge.			
	JUL 2 2 2009	20		Operator	bp Ameri ^c a Producti	on Company		
	Conservation Division			_				
Fall G. Rost				Ву	<u>Sheri Bradshaw</u>	S		
· · ·				• .				
Ву				Title	<u>Field Tech</u>			
Title	uty Oil & Gas Insp	ector.	·	E-mail Ac	ddress			
District #3						* (
	14437	Northwest New Mexico Pa		Date	06/22/09	. 27		

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: 1f, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).