

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

| |
|---|
| WELL API NO. 30-045-34524 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. V-2364 |
| 7. Lease Name or Unit Agreement Name Road Runner |
| 8. Well Number 92 |
| 9. OGRID Number 006515 |
| 10. Pool name or Wildcat Basin Fruitland Coal |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Dugan Production Corp.

3. Address of Operator
P. O. Box 420, Farmington, NM 87499-0420

4. Well Location

Unit Letter B : 1200 feet from the North line and 1850 feet from the East line

Section 26 Township 24N Range 11W NMPM San Juan County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
6511' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Production ☒
Spud, surface casing

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Drill to TD @ 1160' on 7/31/09. Run 5-1/2" 15.5# J-55 csg. Land @ 1150', float collar @ 1110'. Cement w/80 sx Premium Lite FM 3% CaCl2 & 1/4# celloflake, 8% Bentonite & .4% Sodium Metasilicate. Tail w/50 sx Type III cement w/1#/sx CaCl2 & 1/4# celloflake/sx (239 cu ft total slurry). Displace w/26.5 bbls water. Circulate 5 bbls cement. Pressure test will be reported on completion sundry. Released Wayne Smith Drilling @ 1500 hrs on 8/1/09.

RCVD AUG 4 '09

OIL CONS. DIV.

DIST. 3

Spud Date:

7/27/09

Rig Release Date:

8/1/09

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

John C. Alexander

TITLE Vice-President

DATE August 3, 2009

Type or print name John C. Alexander

E-mail address: johncalexander@duganproduction.com

PHONE: 505-325-1821

For State Use Only

Deputy Oil & Gas Inspector,
District #3

APPROVED BY: Kelly G. Powell

TITLE

DATE

AUG 05 2009

Conditions of Approval (if any):

Report hole size for production strings