This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator COF				L	ease N	lame SAN	JUAN 28	8-7 UN	IT	Well No. 106X
Location of We	ell: Unit	Letter	M S	ec <u>10</u>	Tv	wp <u>027N</u>	Rg	ge	007W API	# 30-039-07103
	Name of Reservoir or Pool			1	Type of Prod			Method of Prod		Prod Medium
Upper Completion	PC				Gas			Flow		Tubing
Lower Completion	MV				Gas			Flow		Tubing
				Pre-Flo	ow Shu	ıt-In Pressu	ıre Data			
Upper Completion	Hour, Date, Shut-In 8/20/2009			Lei	Length of Time Shut-In 180 hours			SI Press. PSIG		Stabilized?(Yes or No) Yes
Lower Completion	Hour, Da	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)
	8/20/2009				180 hours			210		Yes
Commenced	at: /24/	2009 12			Flow	Test No. 1 Zone Pro	oducina	(Uppei	or Lower): Up	neer .
				В				d Zone		
(date/time)		Lapsed Time Since*			Upper zone Lower :		Temperature		Remarks	
8/25/2009 12:18:00 PM			24	238		210	·		Both Zones Shut in.	
8/26/2009 12:00:00 PM			48	238		210			Both zones shut in, turned on PC	
8/27/2009 12:46:00 PM 72		72	133		210			Turned on MV		
Production rate	e during	test								
Oil:BPOD Based on:Bb			Bbls. In	ls. InHrs		····	Grav.		GOR	
Gas		МС	FPD; Test th	nru (Orifice	or Mete	er)				
				Mid. To	act Chi	ıt-İn Broccu	ıra Data	•		
Upper Completion	Hour, Date, Shut-In				d-Test Shut-In Pressure Data Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In			Le	Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No) IL CUMS. DIV.
				(00	ntinue	on reverse	side)			NIST 3

Flow Test No. 2

Commenced at:			Zone Producing (Upper or Lower)							
Time	Lapsed Time	PRES	SURE	Prod Zone						
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks					
	;									
	,									
	;									
				-						
										
Production rate d	uring test									
Oil: F	BPOD Based on:	Bbls. In	Hrs	G	Grav. GOR					
Gas	MCFPD; Test	thru (Orifice or M	leter)							
Remarks:										
Tomarko.	· · · · · · · · · · · · · · · · · · ·									
										
I hereby certify the	at the information herein	contained is true	and complete	to the best of n	ny knowledge.					
Approved: \$	EP 1 8 2009	20	Opera	tor: COP						
New Mexico C	il Conservation Division		By:	By: Danny Roberts						
talse	i, Resident		-							
By:			rile:	Title: Multi-Skilled Operator						
Title:	Deputy Oil & Gas In District #3	spector,	Date:	Date: Friday, August 28, 2009						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production
- while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone

The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packet Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

5 Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3