submitted in lieu of Form 3160-5

RECEIVED

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SEP 0 9 2009

Buleau of Land Marshamont Farmington Field Office Sundry Notices and Reports on Wells 5. Lease Number SF-078604 Type of Well If Indian, All. or 6. **GAS** Tribe Name 7. **Unit Agreement Name** 2. Name of Operator BURLINGTON RESOURCES OIL & GAS COMPANY LP 8. Well Name & Number Address & Phone No. of Operator Scott 7B PO Box 4289, Farmington, NM 87499 (505) 326-9700 9. API Well No. 30-045-34952 Location of Well, Footage, Sec., T, R, M 10. Field and Pool Unit C (NENW), 660' FNL & 1595' FWL, Section 3, T31N, R10W, NMPM Blanco MV / Basin DK 11. **County and State** San Juan, NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission **Type of Action** Abandonment Casing Report Notice of Intent Change of Plans X Other -Recompletion New Construction ROWD SEP 17'09 Subsequent Report Plugging Non-Routine Fracturing OIL CONS. DIV. Casing Repair Water Shut off Final Abandonment Altering Casing DIST. 3 Conversion to Injection 13. Describe Proposed or Completed Operations 08/27/2009 MIRU AWS 711. NU BOPE, PT csg to 600#/30min 8/28/09. Test - OK. 08/28/2009 TIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3000' - Inter TD reached 8/30/09. Circ. hole. RIH w/ 72jts, 7", 20#, J-55 ST&C set @ 2990'. 08/30/2009 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scavenger 15sx (55cf-10bbls) 75:25 Class G cmt w/ .25pps celloflake, 3% sodium medasilicate, .20% anit-foam. Lead w/ 346sx (727cf-129bbls) 75:25 Class G cmt w/ .25pps celloflake, 3% sodium medasilicate, .20% anit-foam. Tail w/ 79sx (100cf-18bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps gilson, 2% bentonite, 2% CACL, .15% friction reducer, .1% anitfoam. Drop plug & displaced w/ 120bbls FW. Bump plug. Circ. 47bbls cmt to surface. Plug down @ 6:00hrs on 08/31/09. RD cmt. WOC. 08/31/2009 PT 7" csg to 1500#/30min @ 17:30hrs on 08/31/2009. Test - OK. RIH w/ 6 1/4" bit. Drilled ahead to 7350' (TD) TD reached 09/03/2009. Circ. hole & RIH w/ 179jts, 4 1/2", 11.6#, L-80 LT&C set @ 7350. 09/03/2009 RU to cmt. Pre-flush w/ 10bbls GW, 2bbls FW. Pumped scavenger 16sx (28cf-5bbls) 50:50 POZ cmt w/ .25pps celloflake, 5pps kolite, 3.5% bentonite, .25% FL, .15% friction reducer, .15% retarder, .1% antifoam. Tail w/ 420sx (605cf-108bbls) 50:50 POZ cmt w/ .1% antifoam, 3.5% bentonite, .25pps celloflake, .25% FL, .15% friction reducer, 5pps kolite, .15% retarder. Drop plug & displaced w/ 114bbls FW. Bump plug. Plug down @ 03:45hrs on 09/03/2009. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 10:00hrs on 9/4/09. ✔ PT will be conducted by Completion Rig. Results & TOC will appear on next report. 14. I hereby certify that the foregoing is true and correct. Crystal Tafoya Title Regulatory Technician ACCEPTED FOR RECORD (This space for Federal or State Office use) APPROVED BY Title CONDITION OF APPROVAL, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or traudulent statements or representations as to any matter within its jurisdict