

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. <b>30-045-35008</b>
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name <b>Boardwalk 11</b>
8. Well Number <b>1</b>
9. OGRID Number <b>215009</b>
10. Pool name or Wildcat <b>Entrada Oil</b>

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	
2. Name of Operator <b>Cimarex Energy Co</b>	
3. Address of Operator <b>15 E 5<sup>th</sup> St., Suite 1000, Tulsa, OK 74103</b>	
4. Well Location Unit Letter <b>P</b> : <b>1663</b> feet from the <b>North</b> line and <b>357</b> feet from the <b>East</b> line Section <b>11</b> Township <b>21N</b> Range <b>9W</b> NMPM <b>San Juan</b> County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>GL-6514'</b>	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

*IN 12 1/4" HOLE*  
Cement surface casing @ 356' Ran 9 5/8" J-55 36# LTC&, pump 20 bbls of fresh water spacer followed with 171 sacks Type III + .25 Cello Flake + 3% Calcium Chloride @ 15.2 ppg, Yield 1.28 displaced with 20.5 bbls of fresh water plug bumped and float held.

Time cement in place on September 10, 2009 @ 11:00 pm Mountain Time.

REVISED SEP 28 '09

OIL CONS. DIV.  
DIST. 3

Spud Date: **9/09/2009**

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sharon LaValley TITLE Engineer Tech DATE 9/25/09

Type or print name Sharon LaValley E-mail address: slavalley@cimarex.com PHONE: 918-295-1673

For State Use Only

APPROVED BY: Toby G. Bolte TITLE Deputy Oil & Gas Inspector, District #3 DATE OCT 14 2009  
Conditions of Approval (if any):

8