

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED  
OMB No. 1004-0137  
Expires July 31, 2010

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. I-22-IND-2772
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name Ute Mountain Ute
2. Name of Operator Burlington Resources Oil and Gas Co., LP		7. If Unit or CA Agreement, Name and No.
3a. Address c/o Huntington Energy, L.L.C. 908 N.W. 71st St., Oklahoma City, OK 73116	3b. Phone No. (include area code) (405) 840-9876	8. Lease Name and Well No. Ute Mountain Ute #90
4. Location of Well (Report location clearly and in accordance with any State requirements *) At surface Lot E, 1970' FNL & 980' FWL At proposed prod. zone same as above		9. API Well No. 30-045-35046
10. Field and Pool, or Exploratory Barker Creek-Dakota Pool		11. Sec., T. R. M. or Blk. and Survey or Area Sec 21-T32N-R14W
14. Distance in miles and direction from nearest town or post office* 5 miles to La Plata	12. County or Parish San Juan	13. State NM
15. Distance from proposed* location to nearest property or lease line, ft (Also to nearest drig. unit line, if any) 980'	16. No. of acres in lease 160	17. Spacing Unit dedicated to this well 160
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft	19. Proposed Depth 2740'	20. BLM/BIA Bond No. on file BOK04SDF02064
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 6222'	22. Approximate date work will start*	23. Estimated duration

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, must be attached to this form:

- |   |  |
|---|--|
| 1. Well plat certified by a registered surveyor   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above) |
| 2. A Drilling Plan  | 5. Operator certification  |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office) | 6. Such other site specific information and/or plans as may be required by the BLM.            |

25. Signature <i>Catherine Smith</i>	Name (Printed/Typed) Catherine Smith	Date 10/27/2008
Title Huntington Energy, L.L.C., agent for Burlington Resources Oil and Gas Company, LP		
APPROVED FOR A PERIOD NOT TO EXCEED 2 YEARS		
Approved by (Signature) <i>/s/ Richard A. Rymerson</i>	Name (Printed/Typed)	Date NOV 30 2009
Title MINERALS STAFF CHIEF	Office	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

Venting / Flaring approved for 90 days  
per NTL-4A

\*(Instructions on page 2)

Approval of this agreement does not warrant or certify that the operator thereof and other holders of operating rights hold legal or equitable title to those rights in the subject lease which are committed hereto...

DEC 08 2009 - *AL*

SEE ATTACHED  
CONDITIONS OF APPROVAL

NOTIFY AZTEC OCD 24 HRS  
PRIOR TO CASING & CEMENT  
RECEIVED  
NOV 10 2008

Bureau of Land Management  
Durango, Colorado

DISTRICT I  
P.O. Box 1980, Hobbs, N.M. 88241-1980

DISTRICT II  
1301 W. Grand Avenue, Artesia, N.M. 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, N.M. 87410

DISTRICT IV  
1220 South St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION

1220 South St. Francis Dr  
Santa Fe, NM 87504-2088

Form C-1  
Revised October 12, 2000  
Instructions on back  
Submit to Appropriate District Office  
State Lease - 4 Copies  
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number 30.045.35046	<sup>2</sup> Pool Code 71520	<sup>3</sup> Pool Name Barker Creek - Dakota
<sup>4</sup> Property Code 18725	<sup>5</sup> Property Name UTE MOUNTAIN UTE	<sup>6</sup> Well Number 90
<sup>7</sup> GRID No 14538	<sup>8</sup> Operator Name Burlington Resources Oil and Gas Company, LP	<sup>9</sup> Elevation 6222'

<sup>10</sup> Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
E	21	32-N	14-W		1970	NORTH	980	WEST	SAN JUAN

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County

<sup>12</sup> Dedicated Acres W - 160	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No.
--	-------------------------------	----------------------------------	-------------------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16

FD. 3 1/4" AC. 1986 B.L.M.	S 89-59-36 E 2641.63' (M)	FD. 3 1/4" AC. 1986 B.L.M.
S 00-02-21 E 2636 30' (M)	1970' 1910'	
1010'	C.O.P.	CENTER OF PIT LAT: 36.97544° N. (NAD 83) LONG: 108.32010° W. (NAD 83) LAT: 36°58'31.62" N. (NAD 27) LAT: 108°19'10.07" W. (NAD 27)
980'	21	
FD. 3 1/4" AC. 1986 B.L.M.	SURFACE LOCATION LAT: 36.97528° N. (NAD 83) LONG: 108.32020° W. (NAD 83) LAT: 36°58'31.02" N. (NAD 27) LONG: 108°19'10.45" W. (NAD 27)	

17

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a well interest or undivided mineral interest in the land including the proposed bottom hole location or has right to drill this well at this location pursuant to contract with an owner of such a mineral or work interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

*Catherine Smith* 8/18/08  
Signature Date


Catherine Smith  
Printed Name

18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

MAY 21, 2008

Date of Survey  
Signature and Seal of Professional Surveyor:



Certificate Number

## OPERATIONS PLAN

**Well Name:** Ute Mountain Ute #90  
**Location:** 1970' FNL, 980' FWL, SWNW Sec 21, T-32-N, R-14-W NMPM  
San Juan Co., New Mexico  
**Formation:** Basin Dakota  
**Elevation:** 6222' GR 6237' KB

<u>Formation Tops:</u>	<u>Top</u>	<u>Bottom</u>	<u>RMSL</u>	<u>Contents</u>
Menefee	Surf	105'		
Point Lookout	105'	425'	6110'	
Mancos	425'	1455'	5790'	
Gallup (Niobrara)	1455'	2165'	4760'	oil or water
Greenhorn	2165'	2235'	4050'	
Graneros	2235'	2290'	3980'	
Dakota	2290'	2515'	3925'	gas or water
Burro Canyon	2515'	2535'	3700'	gas
Morrison	2535'	2740'	3680'	gas
TD	2740'			

### Logging Program:

Mud log – 300' to TD  
Open hole logs – AIT/GR/SP/CNL/LDT Surface Casing to TD  
Cased hole logs – CBL/GR – TD to surface  
Cores & DST's – none

### Mud Program:

<u>Interval</u>	<u>Type</u>	<u>Weight</u>	<u>Vis.</u>	<u>Fluid Loss</u>
0 – 300'	Spud	8.4-9.0	40-50	no control
300' - 2740'	Clean Faze	8.4-9.0	32-40	≤10 cc

Pit levels will be visually monitored to detect gain or loss of fluid control.

### Casing Program (as listed, the equivalent, or better):

<u>Hole Size</u>	<u>Depth Interval</u>	<u>Csg. Size</u>	<u>Wt.</u>	<u>Grade</u>
12 1/4"	0 – 300'	8 5/8"	23#	LS-J55
6 1/4"	0 – 2740'	4 1/2"	10.5#	J-55

### Tubing Program:

0 – 2740'                      2 3/8"                      4.7#                      J-55

### BOP Specifications, Wellhead and Tests:

#### Surface to TD –

11" 3000 psi minimum double gate BOP stack (Reference Figure #1). After nipple-up prior to drilling out surface casing, rams and casing will be tested to 600 psi for 30 minutes.

2" nominal, 3000 psi minimum choke manifold (Reference Figure #2).

### Completion Operations:

7 1/16" 3000 psi double gate BOP stack (Reference Figure #1). After nipple-up prior to completion, pipe rams, casing and liner top will be tested to 2000 psi for 15 minutes.

### Float Equipment:

8 5/8" surface casing – saw tooth guide shoe.

Centralizers will be run in accordance with Onshore Order #2.

4 1/2" production casing – guide shoe and self-fill float collar. Standard centralizers run every other joint above shoe. Standard centralizers thereafter every fourth joint up to the base of the surface pipe.

**Wellhead:**

8 5/8" x 4 1/2" x 2 3/8" x 5000 psi tree assembly.

**General:**

- Pipe rams will be actuated once each day and blind rams will be actuated once each trip to test proper functioning.
- An upper kelly cock valve with handle available and drill string valves to fit each drill string will be available on the rig floors at all times.
- BOP pit level drill will be conducted weekly for each drilling crew.
- All BOP tests and drills will be recorded in the daily drilling reports.
- Blind and pipe rams will be equipped with extension hand wheels.

**Cementing:**

8 5/8" surface casing –

Cement to surface w/230 sx Premium cement 2% Calcium Chloride and 1/4# Flocele (274 cu. ft. of slurry). WOC 8 hours before pressure testing or drilling out from under surface casing.

4 1/2" production Casing -

Lead with 185 sx San Juan PRB-2, 5# Gil/sk + .25#/sk Superflake (415 cu ft of slurry – est top of cement: surface). Tail w/100 sx San Juan PRB-2, 5# Gil/sk + .25#/sk Superflake (200 cu ft of slurry – est top of tail cement: 2200').

Note: 50% excess cement will be used unless open hole logs are run, then 25% excess cement over caliper will be pumped. Cement will be circulated to surface.

Float guide shoe/float collar ran on bottom jt. Bowspring centralizers will be run in accordance with Onshore Order #2.

- If hole conditions permit, an adequate water space will be pumped ahead of each cement job to prevent cement/mud contamination or cement hydration.

**Additional Information:**

- The Dakota formation will be completed. If non-commercial, the Mancos will be secondary objectives.
- No abnormal temperatures or hazards are anticipated. H2S is not anticipated.
- Anticipated pore pressure for the Dakota is 750 psi. Maximum bottom hole pressure at TD is 800 psi.
- Sufficient LCM will be added to the mud system to maintain well control, if lost circulation is encountered.
- The northwest quarter of Section 21 is dedicated to this well. This gas is dedicated.

# HALLIBURTON

## Cement Test Report

Farmington District Laboratory  
4109 E. Main  
Farmington, NM 87499

---

To: Randy Snyder  
Halliburton Energy Services

Report: FLMM65810A  
Date:

Company: Slurry Book

Total Vertical Depth: 330 ft  
BHST: 80 °F  
BHCT: 80 °F

Slurry: 15.6 Surface mixed with fresh Water

**All Test performed according to modified API RP Spec 10, 1997**

### Thickening Time to 70 Bc:

2hr 09min

### Design

Mountain G Cement  
3% CaCl<sub>2</sub>  
1/4 #/sk Flocele

### Production Cement

Density:	15.6	lb/gal
Yield:	1.2	ft <sup>3</sup> /sk
Water	5.27	gal/sk

### Compressive Str @ 80F

Hr:Min	psi
2:10	50
3:41	500
6:25	1500
12:00	2415

Deidra Benally  
Lab Technician

**Note:** This report is for information and the content is limited to the sample described. Halliburton Energy Services makes no warranties, express or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage, regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

# HALLIBURTON

## Cement Test Report

Farmington District Laboratory  
4109 E. Main  
Farmington, NM 87499

Halliburton Energy Services

Report: FLMM5000

Total Vertical Depth: 3000 ft

BHST: 115 °F

BHCT: 80 °F


Slurry: San Juan PRB II, 2/10 % D-Air 3000, 5#/sk Gilsonite, 1/8 #/sk Poly-E-Flake

**All Test performed according to modified API RP Spec 10,1997**

<u>Density</u>	<u>Yield</u>	<u>Water</u>	<u>Thickening Time</u>	<u>Free Water</u>	<u>Settling</u>	<u>Rheology</u>	<u>Compressive Strength</u>
lb/gal	ft <sup>3</sup> /sk	gal/sk	to 70 Bc			at 100°F	psi Time
12.5	2.24	12.10	2 hr: 53 min	0%	0%	300 67	500 3 hr 46 min
						200 60	1085 12 hr
						100 51	1268 24 hr
						60 47	36 hr
						PV 26	48 hr
						YP 45	

<u>Density</u>	<u>Yield</u>	<u>Water</u>	<u>Thickening Time</u>	<u>Free Water</u>	<u>Settling</u>	<u>Rheology</u>	<u>Compressive Strength</u>
lb/gal	ft <sup>3</sup> /sk	gal/sk	to 70 Bc:			at 100 °F	psi Time
13.0	2.00	10.29	2 hr: 02 min	0%	0%	300 99	500 3 hr
						200 92	1477 12 hr
						100 84	1722 24 hr
						60 81	1837 36 hr
						PV 28	48 hr
						YP 77	

**Note:** This report is for information and the content is limited to the sample described. Halliburton Energy Services makes no warranties, express or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage, regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.



PLAT #1

ANTICIPATED  
PRODUCTION FACILITIES  
FOR A  
DAKOTA WELL

HUNTINGTON ENERGY, L.L.C.

BOP STACK 3000 PSI




Figure #1

CHOKER MANIFOLD




Figure #2