UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RCVD JAN 12'10 OIL CONS. DIV. DIST. 3

	Sundry Notices and Reports on Wells		
1.	Type of Well GAS RECEIVED	5.6.	Lease Number SF-078500-A If Indian, All. or Tribe Name
	JAN 0 6 2010	7.	Unit Agreement Name
2.	Name of Operator Bureau of Land Menagers Famington Field Office		San Juan 28-7 Unit
	ConocoPhillips		
3.	Address & Phone No. of Operator	8.	Well Name & Number San Juan 28-7 Unit 251
	PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
- 4.	Location of Well, Footage, Sec., T, R, M		30-039-30671
	Surface: Unit D (NWNW), 729' FNL & 395' FWL, Section 31, T28N, R7W, NMPM Bottomhole: Unit D (NWNW), 670' FNL & 825' FWL, Section 31, T28N, R7W, NMPM	10.	Field and Pool Blanco MV / Basin DK
		11.	County and State Rio Arriba, NM
	Final Abandonment Casing Repair Water Shut off Altering Casing Conversion to Injection		
12// 12// 12// 12// 12// 12// 12// 12//	Describe Proposed or Completed Operations 28/2009 MIRU HP 282. NU BOPE. PT csg. to 600#/30min @ 5:30hrs on 12/29/09. Test - OK 29/2009 RIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 2756' - Inter TD reached 12/30/09 0 LT&C set @ 2749'. 12/31/09 RU to cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumped scass G cmt w/ .25pps celloflake, 3% sodium medasillicate, .20% anti-foam. Lead w/ 310sx (657 anti-foam, .25pps celloflake, 3% sodium medasillicate. Tail w/ 72sx (91cf-512bbls) 50:50 PC tonite, .25pps celloflake, .15% friction reducer, 5% gilsonite. Drop plug & displaced w/ 106bl ohrs on 1/1/10. Circ. 48hbls cmt to surface. RD cmt. WOC. 20/2010 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 15:30hrs on 1/1/10. Test - OK. Dril reached 1/4/10. Circ. hole & RIH w/ 164jts total. 65jts, 4 1/2", 11.6#, L-80 LT&C and 99jts, 7'. 1/4/10 RU to cmt. Pre-flush w/ 10bbls GW, 2bbls FW. Pumped scavenger 15sx (27cf-5bb oflake, 5pps kolite, 3.5% bentonite, .25% FL, .15% FR, .15% retarder, .1% anti-foam. Tail w/ .25 w/ .1% anti-foam, 3.5% bentonite, .25pps celloflake, .25% fluid loss, .15% friction reducer, 5 sw/ 15bbls FW. Drop plug & displaced w/ 108bbls FW. Bump plug. Plug down @ 07:30hrs PE. NU WH. RD RR @ 13:30hrs on 1/5/10 ✓	venge cf-11 OZ cn ols FV led al 4 1/2 ls) 50 420s pps k	er 15sx (40cf-7bbls) 75:25 7bbls) 75:25 Class G cmt w nt w/ .1% anti-foam, 2% V. Bump plug. Plug down nead w/ 6 1/4" bit to 6928' (2", 11.6#, 1-55 LT&C set @ ::50 POZ cmt w/ .25pps x (605cf-108bbls) 50:50 PC olite, .15% retarder. Flushe
PT	will be conducted by Completion Rig. Results & TOC will appear on next report. ✓		
	I hereby certify that the foregoing is true and correct. ned	chnic	ian Date 1/10/2010
	is space for Federal or State Office use)	ŕ	ACCOMINATION IN
CO	PROVED BYTitleTOUR STANDITION OF APPROVAL, if any:	Project Co.	Date PIED FOR RECORD
Title he U	18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of nited States any false, fictitious or fraudulent statements or representations as to any matter within list us distinct the statements.	2	JAN 07 2010