RCVD JAN 12'10 OIL CONS. DIV. DIST. 3

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells		
1. Type of Well GAS JAN 0 6 2010	-, •	Lease Number SF- 07638 7 0 後33子 If Indian, All. or Tribe Name
2. Name of Operator Famington Field O	7.	Unit Agreement Name
RESOURCES OIL & GAS COMPANY LP		
3. Address & Phone No. of Operator	- 8.	Well Name & Number Pierce 2B
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
4. Location of Well, Footage, Sec., T, R, M Surface: Unit P (SESE), 1180' FSL & 780' FEL, Section 8, T30N, R9W, NMPM	10.	30-045-34999 Field and Poot
		Blanco MV / Basin DK
	11.	County and State San Juan, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, O	THER I	DATA
Type of Submission Type of Action Notice of Intent Abandonment Change of Plans Recompletion New Construction	<u> </u>	Other - Casing Report
X Subsequent Report Plugging Non-Routine Fracturing Casing Repair Water Shut off		
Final Abandonment Altering Casing Conversion to Injection		
13. Describe Proposed or Completed Operations		
12/26/2009 MIRU AWS 711. PT csg to 600#/30min @ 18:00hrs on 12/28/09. Test - OK. 12/28/2009 RIH w/ 8 3/4" bit. Tag & DO cmt. Drilled ahead to 3236' - Inter TD reached 12/30. 20#, J-55 LT&C set @ 3226'. 12/31/09 RU cmt. Pre-flush w/ 10bbls GW, 10bbls FW. Pumper w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite, .4% SMS. Lead w/ 4 w/ 3% CACL, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. Tail w/ 77sx (164cf-29bl celloflake, .2% FL-52. Drop plug & displaced w/ 129bbls FW. Plug down @ 5:30hrs on 1/1/2 cmt. WOC. 11/01/2010 RIH w/ 6 1/4" bit. PT 7" csg to 1500#/30min @ 21:30hrs on 1/1/2010. Test - OK. (TD) TD reached 1/4/2010. Circ. hole & RIH w/ 182jts, 4 1/2", 11.6#, L-80 LT&C set @ 7534 CW, 2bbls FW. Pumped scavenger 9sx (27cf-5bbls) Premium lite cmt w/ .25pps celloflake, .3% CD-32, 6.25pps LCM displaced w/ 117bbls FW. Bump plug. Plug down @ 12:45hrs on 1/5/10. RD cmt. WOC. ND on 1/5/10	1 19sx (5 16sx (88 ols) Type 010. Cir Drilled a 1. 1/5/10 6 CD-32 M-1, 1%	67cf-10bbls) Premium lite cmt 66cf-158bbls) Premium lite cmt 66cf-158bbls) Premium lite cmt e III cmt w/ 1% CACL, .25pps ec. 60bbls cmt to surface. RD ahead w/ 6 1/4" bit to 7536' 0 RU cmt. Pre-flush w/ 10bbls e, 6.25pps LCM-1, 1% FL-52. FL-52. Drop plug &
PT will be conducted by Completion Rig. Results & TOC will appear on next report.		
14. I hereby certify that the foregoing is true and correct.		ı 1
Signed Jafoya Crystal Tafoya Title Regulatory	<u> Fechnici</u>	an Date <u>[6 2</u> 010
(This space for Federal or State Office use) APPROVED BY	7. 15 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	-Date ACCEPTED FOR RECORD JAN 0 7 2010