

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

1. RECEIVED

FEB 08 2010

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Surface: Unit J (NWSE), 1410' FSL & 1785' FEL, Section 25, T30N, R7W, NMPM

Bottomhole: Unit I (NESE), 2360' FSL & 910' FEL, Section 25, T30N, R7W, NMPM

Bureau of Land Management
Farmington Field Office
Lease Number SF-079382

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name
San Juan 30-6 Unit

8. Well Name & Number
San Juan 30-6 Unit 129M

9. API Well No.
30-039-30809

10. Field and Pool
Blanco MV / Basin DK

11. County and State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

☒ Other - Change Int Csg Depth

RCVD FEB 12 '10
OIL CONS. DIV.
DIST. 3

13. Describe Proposed or Completed Operations

Burlington Resources requests permission to change the Intermediate casing depth from 3849' TVD to 3410' TVD due to possible circulation losses in the Lewis formation. The BLM (Jim Lovato) & OCD (Steve Hayden) were contacted and received verbal approval to proceed. The new project proposal and directional drill plan are attached.

2/8/2010

14. I hereby certify that the foregoing is true and correct.

Signed Crystal Tafoya Crystal Tafoya

Title Regulatory Technician

Date 2/8/2010

(This space for Federal or State Office use)

APPROVED BY Troy L. Salvors

Title Petroleum Engineer

Date 2/9/2010

CONDITION OF APPROVAL, if any:

Title 18 U S C Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Hold C104
for Directional Survey
and "As Drilled" plat

CONDITIONS OF APPROVAL
Adhere to previously issued stipulations.

NMOCD

PROJECT PROPOSAL - New Drill / Sidetrack

San Juan Business Unit

SAN JUAN 30-6 UNIT 129M

DEVELOPMENT

Lease:		AFE #: WAN.CDR.8526		AFE \$: 1,888,078.28	
Field Name: SAN JUAN		Rig: Aztec Rig 730		State: NM	County: RIO ARRIBA
Geologist:		Phone:		Geophysicist:	
Geoscientist:		Phone:		Prod. Engineer:	
Res. Engineer:		Phone:		Proj. Field Lead:	
Primary Objective (Zones):					
Zone	Zone Name				
FRR	BASIN DAKOTA (PRORATED GAS)				
RON	BLANCO MESAVERDE (PRORATED GAS)				
Location: Surface					
Datum Code: NAD 27		Directional:			
Latitude: 36.780234	Longitude: -107.518784	X:	Y:	Section: 25	Range: 007W
Footage X: 1785 FEL	Footage Y: 1410 FSL	Elevation: 6257 (FT)	Township: 030N		
Tolerance:					
Location: Bottom Hole					
Datum Code: NAD 27		Directional:			
Latitude: 36.782844	Longitude: -107.515804	X:	Y:	Section: 25	Range: 007W
Footage X: 910 FEL	Footage Y: 2360 FSL	Elevation:	(FT)	Township: 030N	
Tolerance:					
Location Type: Year Round		Start Date (Est.): 1/1/2010		Completion Date:	
				Date In Operation:	
Formation Data: Assume KB = 6272 Units = FT					
Formation Call & Casing Points	Depth (TVD in Ft)	SS (Ft)	Depletion (Yes/No)	BHP (PSIG)	BHT
Surface Casing	199	6073	☐		
NACIMIENTO	904	5368	☐		
OJO ALAMO	2223	4049	☐		
KIRTLAND	2334	3938	☐		
FRUITLAND	2752	3520	☐		Possible Gas
PICTURED CLIFFS	3186	3086	☐		
LEWIS	3310	2962	☐		
Intermediate Casing	3410	2862	☐		
HUERFANITO BENTONITE	3888	2384	☐		
CHACRA	4218	2054	☐		Est. Top Perf - 4219 (2052)
UPPER CLIFF HOUSE	4822	1450	☐		Gas
MASSIVE CLIFF HOUSE	5040	1232	☐	358	Gas
MENEFEE	5096	1176	☐		
POINT LOOKOUT	5406	866	☐		
MANCOS	5745	527	☐		
UPPER GALLUP	6665	-393	☐		
GREENHORN	7376	-1104	☐		
GRANEROS	7432	-1160	☐		
TWO WELLS	7518	-1246	☐	3365	Gas
PAGUATE	7560	-1288	☐		
UPPER CUBERO	7576	-1304	☐		
LOWER CUBERO	7612	-1340	☐		Est. Btm Perf - 7672 (-1401) based on offset wells

PROJECT PROPOSAL - New Drill / Sidetrack

SAN JUAN 30-6 UNIT 129M

DEVELOPMENT

ENCINAL	7658	-1386	☐	TD - 80' below T/ENCN
Total Depth	7738	-1466	☐	6-1/4" hole, 4-1/2" 11.6 ppf, J-55/L-80, LTC casing. Cement w/ 589 cuft. Circulate cement a minimum of 100' inside the previous casing string.

Reference Wells:		
Reference Type	Well Name	Comments
Production	SJ 30-6 129	30N 7W 25 NW SE SE
Production	SJ 30-6 96B	30N 7W 26 SE SE NE
Production	SJ 30-6 78-A	30N 7W 25 SE NW SE
Production	SJ 30-6 417	30N 7W 25 NW SE NE

Logging Program:	
Intermediate Logs:	☐ Log only if show ☐ GR/ILD ☐ Triple Combo

TD Logs:	☐ Triple Combo ☐ Dipmeter ☐ RFT ☐ Sonic ☐ VSP ☐ TDT ☒ Other
----------	---

Cased Hole GR / CBL

Mudlog from 100' above top of GRHN to TD - mudlogger will call TD.

Additional Information:					
Log Type	Stage	From (Ft)	To (Ft)	Tool Type/Name	Remarks

ConocoPhillips SJBU

San Juan Basin - New Mexico Wells

San Juan 30 Wells

SJ 30-6 #129M

Principal Wellbore

Plan: Plan #2 ✓

Standard Planning Report

08 February, 2010

ConocoPhillips or its affiliates

Planning Report

Database:	EDM Central Planning	Local Co-ordinate Reference:	Well SJ 30-6 #129M
Company:	ConocoPhillips SJBU	TVD Reference:	RKB @ 6273.0ft (Original Well Elev)
Project:	San Juan Basin - New Mexico Wells	MD Reference:	RKB @ 6273.0ft (Original Well Elev)
Site:	San Juan 30 Wells	North Reference:	True
Well:	SJ 30-6 #129M	Survey Calculation Method:	Minimum Curvature
Wellbore:	Principal Wellbore		
Design:	Plan #2		

Project:	San Juan Basin - New Mexico Wells, New Mexico, Directional "S"		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico West 3003		Using geodetic scale factor

Site:	San Juan 30 Wells		
Site Position:		Northing:	2,100,610.50 ft
From:	Lat/Long	Easting:	654,846.83 ft
Position Uncertainty:	3.5 ft	Slot Radius:	"
		Latitude:	36° 46' 18.382 N
		Longitude:	107° 18' 16.710 W
		Grid Convergence:	0.32 °

Well:	SJ 30-6 #129M		
Well Position	+N-S	0.0 ft	Northing:
	+E-W	0.0 ft	Easting:
Position Uncertainty	3.5 ft	Wellhead Elevation:	ft
		Latitude:	36° 46' 48.840 N
		Longitude:	107° 31' 7.638 W
		Ground Level:	6,257.0 ft

Wellbore:	Principal Wellbore		
Magnetics	Model Name	Sample Date	Declination
	BGGM2009	7/28/2009	10.02
			Dip Angle
			63.62
			Field Strength
			50,996 nT

Design:	Plan #2		
Audit Notes:			
Version:	Phase:	PLAN	Tie On Depth:
			0.0
Vertical Section:	Depth From (TVD)	+N-S	+E-W
	(ft)	(ft)	(ft)
	0.0	0.0	0.0
			Direction
			42.58

Plan Sections										
Measured	Inclination	Azimuth	Vertical	+N-S	+E-W	Dogleg	Build	Turn	TFO	Target
Depth	(°)	(°)	Depth	(ft)	(ft)	Rate	Rate	Rate	(°)	
(ft)			(ft)			(°/100ft)	(°/100ft)	(°/100ft)		
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
320.0	0.00	0.00	320.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,447.3	33.82	42.58	1,382.9	237.9	218.6	3.00	3.00	0.00	42.58	
2,607.7	33.82	42.58	2,347.1	713.5	655.6	0.00	0.00	0.00	0.00	
3,735.0	0.00	0.00	3,410.0	951.5	874.2	3.00	-3.00	0.00	180.00	SJ 30-6 #129M - ICP
8,063.0	0.00	0.00	7,738.0	951.5	874.2	0.00	0.00	0.00	0.00	SJ 30-6 #129M - PCP

ConocoPhillips or its affiliates

Planning Report

Database:	EDM Central Planning	Local Co-ordinate Reference:	Well SJ 30-6 #129M
Company:	ConocoPhillips SJBU	TVD Reference:	RKB @ 6273.0ft (Original Well Elev)
Project:	San Juan Basin - New Mexico Wells	MD Reference:	RKB @ 6273.0ft (Original Well Elev)
Site:	San Juan 30 Wells	North Reference:	True
Well:	SJ 30-6 #129M	Survey Calculation Method:	Minimum Curvature
Wellbore:	Principal Wellbore		
Design:	Plan #2		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N-S (ft)	+E-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
215.0	0.00	0.00	215.0	0.0	0.0	0.0	0.00	0.00	0.00
Surface									
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
320.0	0.00	0.00	320.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	2.40	42.58	400.0	1.2	1.1	1.7	3.00	3.00	0.00
500.0	5.40	42.58	499.7	6.2	5.7	8.5	3.00	3.00	0.00
600.0	8.40	42.58	599.0	15.1	13.9	20.5	3.00	3.00	0.00
700.0	11.40	42.58	697.5	27.7	25.5	37.7	3.00	3.00	0.00
800.0	14.40	42.58	795.0	44.2	40.6	60.0	3.00	3.00	0.00
900.0	17.40	42.58	891.1	64.4	59.1	87.4	3.00	3.00	0.00
913.5	17.81	42.58	904.0	67.4	61.9	91.5	3.00	3.00	0.00
Nacimiento									
1,000.0	20.40	42.58	985.7	88.2	81.0	119.8	3.00	3.00	0.00
1,100.0	23.40	42.58	1,078.5	115.7	106.3	157.1	3.00	3.00	0.00
1,200.0	26.40	42.58	1,169.2	146.7	134.8	199.2	3.00	3.00	0.00
1,300.0	29.40	42.58	1,257.6	181.1	166.4	246.0	3.00	3.00	0.00
1,400.0	32.40	42.58	1,343.4	218.9	201.2	297.3	3.00	3.00	0.00
1,447.3	33.82	42.58	1,382.9	237.9	218.6	323.1	3.00	3.00	0.00
1,500.0	33.82	42.58	1,426.8	259.6	238.5	352.5	0.00	0.00	0.00
1,600.0	33.82	42.58	1,509.8	300.5	276.1	408.1	0.00	0.00	0.00
1,700.0	33.82	42.58	1,592.9	341.5	313.8	463.8	0.00	0.00	0.00
1,800.0	33.82	42.58	1,676.0	382.5	351.4	519.4	0.00	0.00	0.00
1,900.0	33.82	42.58	1,759.1	423.5	389.1	575.1	0.00	0.00	0.00
2,000.0	33.82	42.58	1,842.2	464.5	426.8	630.8	0.00	0.00	0.00
2,100.0	33.82	42.58	1,925.2	505.5	464.4	686.4	0.00	0.00	0.00
2,200.0	33.82	42.58	2,008.3	546.4	502.1	742.1	0.00	0.00	0.00
2,300.0	33.82	42.58	2,091.4	587.4	539.7	797.7	0.00	0.00	0.00
2,400.0	33.82	42.58	2,174.5	628.4	577.4	853.4	0.00	0.00	0.00
2,458.4	33.82	42.58	2,223.0	652.3	599.4	885.9	0.00	0.00	0.00
Ojo									
2,500.0	33.82	42.58	2,257.6	669.4	615.0	909.0	0.00	0.00	0.00
2,592.0	33.82	42.58	2,334.0	707.1	649.7	960.2	0.00	0.00	0.00
Kirtland									
2,600.0	33.82	42.58	2,340.7	710.4	652.7	964.7	0.00	0.00	0.00
2,607.7	33.82	42.58	2,347.1	713.5	655.6	969.0	0.00	0.00	0.00
2,700.0	31.05	42.58	2,424.9	750.0	689.1	1,018.5	3.00	-3.00	0.00
2,800.0	28.05	42.58	2,511.9	786.3	722.4	1,067.8	3.00	-3.00	0.00
2,900.0	25.05	42.58	2,601.4	819.2	752.7	1,112.5	3.00	-3.00	0.00
3,000.0	22.05	42.58	2,693.0	848.6	779.7	1,152.4	3.00	-3.00	0.00
3,063.2	20.15	42.58	2,752.0	865.4	795.1	1,175.2	3.00	-3.00	0.00
Fruitland									
3,100.0	19.05	42.58	2,786.7	874.5	803.4	1,187.5	3.00	-3.00	0.00
3,200.0	16.05	42.58	2,882.0	896.7	823.8	1,217.7	3.00	-3.00	0.00
3,300.0	13.05	42.58	2,978.8	915.2	840.8	1,242.8	3.00	-3.00	0.00
3,400.0	10.05	42.58	3,076.7	929.9	854.4	1,262.8	3.00	-3.00	0.00
3,500.0	7.05	42.58	3,175.6	940.8	864.4	1,277.7	3.00	-3.00	0.00
3,510.5	6.74	42.58	3,186.0	941.8	865.3	1,278.9	3.00	-3.00	0.00
Pictured Cliffs									
3,600.0	4.05	42.58	3,275.1	948.0	871.0	1,287.3	3.00	-3.00	0.00
3,634.9	3.00	42.58	3,310.0	949.5	872.4	1,289.5	3.00	-3.00	0.00

ConocoPhillips or its affiliates

Planning Report

Database:	EDM Central Planning	Local Co-ordinate Reference:	Well SJ 30-6 #129M
Company:	ConocoPhillips SJB	TVD Reference:	RKB @ 6273 0ft (Original Well Elev)
Project:	San Juan Basin - New Mexico Wells	MD Reference:	RKB @ 6273 0ft (Original Well Elev)
Site:	San Juan 30 Wells	North Reference:	True
Well:	SJ 30-6 #129M	Survey Calculation Method:	Minimum Curvature
Wellbore:	Principal Wellbore		
Design:	Plan #2		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
Lewis										
3,700.0	1.05	42.58	3,375.0	951.2	874.0	1,291.8	3.00	-3.00	0.00	
3,735.0	0.00	0.00	3,410.0	951.5	874.2	1,292.1	3.00	-3.00	-121.73	
Intermediate - SJ 30-6 #129M - ICP										
3,800.0	0.00	0.00	3,475.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
3,900.0	0.00	0.00	3,575.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,000.0	0.00	0.00	3,675.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,100.0	0.00	0.00	3,775.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,200.0	0.00	0.00	3,875.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,213.0	0.00	0.00	3,888.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Huerfano Bentonite										
4,300.0	0.00	0.00	3,975.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,400.0	0.00	0.00	4,075.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,500.0	0.00	0.00	4,175.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,543.0	0.00	0.00	4,218.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Chacra										
4,600.0	0.00	0.00	4,275.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,700.0	0.00	0.00	4,375.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,800.0	0.00	0.00	4,475.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
4,900.0	0.00	0.00	4,575.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,000.0	0.00	0.00	4,675.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,100.0	0.00	0.00	4,775.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,147.0	0.00	0.00	4,822.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Upper Cliffhouse										
5,200.0	0.00	0.00	4,875.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,300.0	0.00	0.00	4,975.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,365.0	0.00	0.00	5,040.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Mass. Cliffhouse										
5,400.0	0.00	0.00	5,075.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,421.0	0.00	0.00	5,096.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Menefee										
5,500.0	0.00	0.00	5,175.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,600.0	0.00	0.00	5,275.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,700.0	0.00	0.00	5,375.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,731.0	0.00	0.00	5,406.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Point Lookout										
5,800.0	0.00	0.00	5,475.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
5,900.0	0.00	0.00	5,575.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,000.0	0.00	0.00	5,675.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,070.0	0.00	0.00	5,745.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Mancos										
6,100.0	0.00	0.00	5,775.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,200.0	0.00	0.00	5,875.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,300.0	0.00	0.00	5,975.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,400.0	0.00	0.00	6,075.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,500.0	0.00	0.00	6,175.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,600.0	0.00	0.00	6,275.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,700.0	0.00	0.00	6,375.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,800.0	0.00	0.00	6,475.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,900.0	0.00	0.00	6,575.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
6,990.0	0.00	0.00	6,665.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Upper Gallup										

ConocoPhillips or its affiliates

Planning Report

Database:	EDM Central Planning	Local Co-ordinate Reference:	Well SJ 30-6 #129M
Company:	ConocoPhillips SJB	TVD Reference:	RKB @ 6273.0ft (Original Well Elev)
Project:	San Juan Basin - New Mexico Wells	MD Reference:	RKB @ 6273.0ft (Original Well Elev)
Site:	San Juan 30 Wells	North Reference:	True
Well:	SJ 30-6 #129M	Survey Calculation Method:	Minimum Curvature
Wellbore:	Principal Wellbore		
Design:	Plan #2		

Planned Survey										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
7,000.0	0.00	0.00	6,675.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,100.0	0.00	0.00	6,775.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,200.0	0.00	0.00	6,875.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,300.0	0.00	0.00	6,975.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,400.0	0.00	0.00	7,075.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,500.0	0.00	0.00	7,175.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,600.0	0.00	0.00	7,275.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,700.0	0.00	0.00	7,375.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,701.0	0.00	0.00	7,376.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Greenhorn										
7,757.0	0.00	0.00	7,432.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Graneros										
7,800.0	0.00	0.00	7,475.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,843.0	0.00	0.00	7,518.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Two Wells										
7,885.0	0.00	0.00	7,560.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Paguate										
7,900.0	0.00	0.00	7,575.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
7,901.0	0.00	0.00	7,576.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Upper cubero										
7,937.0	0.00	0.00	7,612.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Lower Cubero										
7,983.0	0.00	0.00	7,658.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Encinal										
8,000.0	0.00	0.00	7,675.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
8,063.0	0.00	0.00	7,738.0	951.5	874.2	1,292.1	0.00	0.00	0.00	
Production - SJ 30-6 #129M - PCP										

Targets										
Target Name	hit/miss target	Dip Angle (°)	Dip Dir (°)	TVD (ft)	+N/-S (ft)	+E/-W (ft)	Northing (ft)	Easting (ft)	Latitude	Longitude
SJ 30-6 #129M - ICP	- plan hits target center	0.00	0.00	3,410.0	951.5	874.2	2,104,368.52	592,986.74	36° 46' 58.248 N	107° 30' 56.892 W
- Point										
SJ 30-6 #129M - PCP	- plan hits target center	0.00	0.00	7,738.0	951.5	874.2	2,104,368.55	592,986.73	36° 46' 58.248 N	107° 30' 56.892 W
- Point										

Casing Points					
Measured Depth (ft)	Vertical Depth (ft)	Name	Casing Diameter (")	Hole Diameter (")	
215.0	215.0	Surface	9-5/8	12-1/4	
3,735.0	3,410.0	Intermediate	7	8-3/4	
8,063.0	7,738.0	Production	4-1/2	6-1/4	

ConocoPhillips or its affiliates

Planning Report

Database:	EDM Central Planning	Local Co-ordinate Reference:	Well SJ 30-6 #129M
Company:	ConocoPhillips SJB	TVD Reference:	RKB @ 6273 0ft (Original Well Elev)
Project:	San Juan Basin - New Mexico Wells	MD Reference:	RKB @ 6273 0ft (Original Well Elev)
Site:	San Juan 30 Wells	North Reference:	True
Well:	SJ 30-6 #129M	Survey Calculation Method:	Minimum Curvature
Wellbore:	Principal Wellbore		
Design:	Plan #2		

Formations:						
Measured Depth (ft)	Vertical Depth (ft)	Name	Lithology	Dip (°)	Dip Direction (°)	
6,990.0	6,665.0	Upper Gallup		0.00		
7,885.0	7,560.0	Paguate		0.00		
5,731.0	5,406.0	Point Lookout		0.00		
2,458.4	2,223.0	Ojo		0.00		
7,843.0	7,518.0	Two Wells		0.00		
7,757.0	7,432.0	Graneros		0.00		
7,937.0	7,612.0	Lower Cubero		0.00		
4,213.0	3,888.0	Huerfano Bentonite		0.00		
5,365.0	5,040.0	Mass. Cliffhouse		0.00		
6,070.0	5,745.0	Mancos		0.00		
5,147.0	4,822.0	Upper Cliffhouse		0.00		
7,701.0	7,376.0	Greenhorn		0.00		
5,421.0	5,096.0	Menefee		0.00		
7,983.0	7,658.0	Encinal		0.00		
4,543.0	4,218.0	Chacra		0.00		
7,901.0	7,576.0	Upper cubero		0.00		
3,510.5	3,186.0	Pictured Cliffs		0.00		
3,063.2	2,752.0	Fruitland		0.00		
3,634.9	3,310.0	Lewis		0.00		
2,592.0	2,334.0	Kirtland		0.00		
913.5	904.0	Nacimiento		0.00		