Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR

EWE	D	OMB No 1004-013 Expires July 31, 199

BUREAU	OF	LAND	MANAGEMENT	

5 Lease Serial No.

SUNDRY	NOTICES AND REPORTS	DI WELLS I ED TT (010	[NIVINIVI-23050
Do not use this	6 If Indian, Allottee or Tribe Name		
abandoned well.	ment		
VIS. COMPRESSION OF THE RESIDENCE OF THE STATE OF THE STA	a verse seminare e le company e	Fammuion Fran O	1 109
SUBMIT IN TRIPLI	CATE – Other instruct	ions on reverse side	7." If Unit or CA/Agreement, Name and/or No
1. Type of Well		基本。在	
	Other		8 Well Name and No
			South Blanco Federal 6-3
•			
Elm Ridge Exploration Compan	y, LLC		9. API Well No.
3a Address	3t	Phone No (include area code)	30-039-22599
PO BOX 156, Bloomfield, NM &	87413 5	05-632-3476	10 Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T, R.	., M, or Survey Description)		Lybrook Gallup Ext.
Sec. 6-T23N-R7W			11 County or Parish, State
1740' FNL X 330' FEL, Unit H			
			Rio Arriba, NM
12. CHECK APPROPRIATE BOX(ES	S) TO INDICATE NATURE OF	F NOTICE, REPORT, OR OTHER D.	ATA
TYPE OF SUBMISSION	TYPE OF ACTION		
Notice of Intent	Acıdize	Deepen . Production ((Start/Resume) Water Shut-Off
	Alter Casing	Fracture Treat Reclamation	
Subsequent Report	Casing Repair	New Construction Recomplete	Other
	Change Plans	Plug and Abandon Temporarily	Abandon
Final Abandonment Notice	Convert to Injection	Plug Back Water Dispo	osal
Attach the Bond under which the work w Following completion of the involved opera	or recomplete horizontally, give substantial be performed or provide the Bondations If the operation results in a adonment Notices shall be filed only ion.) tion. Elm Ridge Exploration	urface locations and measured and true verticd No. on file with BLM/BIA Required submultiple completion or recompletion in a new after all requirements, including reclamation,	al depths of all pertinent markers and zones sequent reports shall be filed within 30 days or interval, a Form 3160-4 shall be filed once have been completed, and the operator has
		Notify NMOCD 24 hrs prior to beginning operations	RCVD FEB 17'10 OIL CONS. DIV. DIST. 3
14 I hereby certify that the foregoing is the	ie and correct		
Name (Printed/Typed)		Title	
Amy Mia	ackey	Administ	rative Manager
Signature		Date Febru	ary 10, 2010
	THIS SPACE FO	R FEDERAL OR STATE USE	
Approved by Original Signed	d: Stephen Mason	Title	FEB 1 6 2010
Conditions of approval, If any, are attached a certify that the applicant holds legal or equital which would entitle the applicant to conduct of	ble title to those rights in the subject		

(Instructions on reverse)

fraudulent statements or representations as to any matter within its jurisdiction.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or

Plugging Program for South Blanco Federal 6-3

Plug 1: MOL & RU. NU BOP. PU 2-3/8" workstring. With end of tubing at 5448', spot 15 sx balanced plug from 5448-5310' to cover 50' across perfs and Gallup top. PU and reverse circulate with 2 tubing volumes of water. TOOH.

944 2848

- Plug 2: With end of tubing at 3-553, spot 12 sx balanced plug from 3-553-3-453 to cover 50 across Cliff House top. PU and reverse circulate with 2 tubing volumes of water.
- Plug 3: With end of tubing at 2468', spot 12 sx balanced plug from 2468-2368' to cover 50' across Chacra top per NMOCD. PU and reverse circulate with 2 tubing volumes of water.

1220

- Plug 4: With end of tubing at 2049', spot 64' sx balanced plug from 2049-1254' to cover 50' across Pictured Cliffs, Fruitland, and Ojo Alamo tops. PU and reverse circulate with 2 tubing volumes of water.
- Plug 5: With end of tubing at 317', mix and pump 28 sx or sufficient volume to bring cement to surface, inside 4-1/2" casing.

NOTE: All cement volumes include excess.

Elm Ridge Resources

Pertinent Data Sheet

Well Name: South Blanco Federal 6-3 Footage: 1740' FNL and 330' FEL

Footage: 1740' FNL and 330' FEL Location: Section 6, T23N, R7W Rio Arriba County, NM

API#: 30-039-22599

Field: Lybrook Gallup Ext. Elevation: 7008' GR TD: 5740' KB

PBTD: 5688' KB

Completed: 3/16/81

Casing Record:

Hole Size	Casing Size	Wt.	Grade	Depth Set	Cement
12-1/4"	8-5/8"	24#	J-55	267'	200 sx (Circ. To Surface)
7-7/8"	4-1/2"	10.5#	K-55	5735'	Stg 1: 1008 ft ³ ; Stg 2: 846 ft ³ (DV@3151')

(1) 1st Stage: TOC: 3345' (CBL). 2nd Stage: TOC: Circulated cement to surface.

Tubing Record: None

Formation Tops:

Nacimiento	Surface
Ojo Alamo	1304'
Kirtland	1443'
Fruitland	1850'
Pictured Cliffs	1999'
Lewis	2095'
Chacra	2418'
Cliff House	3503'
Menefee	3538'
Point Lookout	4316'
Mancos	4504'
Gallup	4531'

Perforations: Gallup: 5398-5669'

Wellbore Diagram

South Blanco Federal 6-3 NE/4 Sec. 6, T23N, R7W Rio Arriba County Co., NM

API #30-039-22599

Before


Nacimiento-Surface 12-1/4" OH 8-5/8" 24# J-55 set @ 267' Circulated cmt to surface TOC: Circulated to surface Ojo Alamo 1304' Kirtland 1443' Fruitland 1850' Pictured Cliffs 1999' Lewis 2095' Chacra 2418' 4-1/2" DV Tool @ 3151' 1st Stage: TOC 3345' (CBL) Cliff House 3503' Menefee 3538' Point Lookout 4316' Mancos 4504' Gallup 5360' Gallup Perfs: 5398-5669' PBTD: 5703' 4-1/2" 10.5# K-55 Set @ 5735' 7-7/8" OHTD @ 5740'

Wellbore Diagram

South Blanco Federal 6-3

NE/4 Sec. 6, T23N, R7W Rio Arriba County Co., NM API #30-039-22599

After



S. Blanco Federal 6-3 WBD 2/10/2010

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT FARMINGTON DISTRICT OFFICE

1235 LA PLATA HIGHWAY FARMINGTON, NEW MEXICO 87401

Attachment	to notice of
Intention to	Ahandon:

Re: Permanent Abandonment Well: 3 South Blanco Federal 6

CONDITIONS OF APPROVAL

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
- 2. Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907.
- 3. The following modifications to your plugging program are to be made:
- a) Place the Mesaverde plug from 2948' 2848'.
- b) Bring the top of the Pictured Cliffs/Fruitland/Kirtland/Ojo Alamo plug to 1220'.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.