RECEIVED

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

MAR 1 6 2010

			au of Land Management
	Sundry Notices and Reports on Wells	- X-6	armington Field Office
		5.	Lease Number
			SF-079383
1.	Type of Well	6.	If Indian, All. or
	GAS		Tribe Name
		7.	Unit Agreement Name
2.	Name of Operator		San Juan 30-6 Unit
	BURLINGTON		
	RESOURCES OIL & GAS COMPANY LP		
		8.	Well Name & Number
3.	Address & Phone No. of Operator		San Juan 30-6 Unit 96N
	DO D 4000 D' NIM 07400 (E0E) 207 0700		A DV SSZ. D SY.
	PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
_			30-039-30836
4.	Location of Well, Footage, Sec., T, R, M		
	O C EL LA LOCATION ACCESTANTE O SEGUIDADE COMO ACCESANT DELLA ACCESANTANTA	10.	Field and Pool
	Surface: Unit H (SENE), 2565' FNL & 153' FEL, Section 26, T30N, R7W, NMPM		Blanco MV / Basin DK
	Bottomhole: Unit G (SWNE), 2430' FNL & 1390' FEL, Section 26, T30N, R7W, NMPM	11.	County and State
	1928, EST 1800,		Rio Arriba, NM
	CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTITY of Submission Type of Submission Notice of Intent Abandonment Recompletion Y Subsequent Report Plugging Casing Repair Final Abandonment Altering Casing Conversion to Injection		Other – Casing Report RCVD MAR 23'10 OIL CONS. DIV.
Ke	Final Abandonment Altering Casing Conversion to Injection		DIST. 3
13.	Describe Proposed or Completed Operations		
Pre cmm ST Pre Pre FW 03/800 Tai 124	05/2010 MIRU AWS 730. NU BOPE. PT csg to 600#/30min @ 5:30hrs on 3/6/10. Test_OK. 06/2010 RIH w/8 3/4" bit. Tag & DO cmt. Drilled ahead to 4785' - Inter TD reached 3/9/10. Circ. 1 &C set @ 4765' w/ ST@2904'. 3/11/10 RU to cmt. 1 Stage - Pre-flush w/ 10bbls GW, 2bbls FW. Imium lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, .4% SMS, 8% bentonite. mium lite cmt w/ 8% bentonite, 3% CACL2, .25pps celloflake, .4% FL-52, 5pps LCM-1, .4% SMS. w/ 1% CACLS, .25pps celloflake, .2% FL-52. Drop plug & displaced w/ 80bbls FW & 105bbls M & Circ. 8bbls cmt to surface. WOC. 2 nd Stage - Pre-flush w/ 10bbls FW, 10bbls GW, 2bbls FW. Pmium lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, .4% SMS, 8% bentonite. mium lite cmt w/ 3% CACL, .25pps celloflake, 5pps LCM-1, .4% FL-52, .5pps LCM-1, .4% SMS. Bump plug & closed ST. Circ. 25bbls cmt to surface. Plug down @ 07:09hrs on 3/12/10. RD crt. 12/2010 R1H w/ 6 1/4" bit. Drill out ST@2904'. PT 7" csg to 1500#/30min @ 1:30hrs on 3/12/10. T7' (TD) TD reached 3/14/10. Circ. hole & RIH w/ 195jts, 4 1/2", 11.6#, L-80 LT&C set @ 8006'. 1 bls CW, 2bbls FW. Pumped scavenger 9sx (28cf-5bbls) Premium lite cmt w/ .25pps celloflake, .3% lw/ 240sx (475cf-84bbls) Premium lite cmt w/ .3% CD-32, .25pps celloflakes, 1% FL-52, 6.25pps bbls FW. Bump plug. Plug down @ 16:19hrs on 3/15/10. RD cmt. WQC. ND BOPE. NU WH. R will be conducted by Completion Rig. Results & TQC will appear on next report. ✓ I hereby certify that the foregoing is true and correct.	Pump Lead Tail W. E W. E Lead Dro ont. W Fest - 6 CD LCM D RR	ed scavenger 19sx (57cf-10bbls) w/ 187sx (398cf-71bbls) w/ 110sx (152cf-27bbls) Type III bump plug. Plug down. Open d scavenger 19sx (57cf-10bbls) w/ 380sx (809cf-144bbls) p plug & displaced w/ 114 bbls OC. OK. Drilled ahead w/ 6 1/4" bit 0 RU to cmt. Pre-flush w/ 32, 6.25pps LCM-1, 1% FL-52. 1. Drop plug & displaced w/ @ 23:00hrs on 3/15/10 **Transpired State of the scale of
	is space for Federal or State Office use) PROVED BY Title Title		ACCEPTED FOR RECORD
CO	NDITION OF APPROVAL, if any: 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of		MAR 2 2 2010
46-11	noted States any false firstlying or fraudulant statements or representations as to any matter within its invisid atom.	•	THE PROPERTY OF STREET