Form 3160-3 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED OMB No. 1004-0136 Expires November 30, 2000

5. Lease Seria SF-07815

			and the second s		SF-0/0150	
	APPLICAT	ION FOR PERM	AIT TO DRILL OR REENTE	₹117 PM 3	45.71f Indian, Allottee or Tri	be Name
la. Typc of Work:	☑ DRILL	REENTER	0 70 f	Farmington, N	If Unit or CA Agreemen	nt, Name and No.
1b. Type of Weil:	Oil Well	☐ Gas Well	Other: CBM Single Zone	☐ Multiple Zone	Lease Name and Well N SALGE FEDERAL A	lo.
2. Name of Opera DUGAN PRO	tor ODUCTION C	Con ORP.	tact: KURT FAGRELIUS E-Mail: kfagrelius@duganproductio	n.com	9. API Well No. 30045	31349
3a. Address 709 EAST MU FARMINGTON	IRRAY DRIVE N, NM 87401		3b. Phone No. (include area coor Ph: 505.325.1821 Fx: 505.327.4613	ic)	10. Field and Pool, or Expl BASIN FRUITLAND	
4. Location of We	ll (Report local	tion clearly and in acc	cordance with any State requirements.*)	11. Sec., T., R., M., or Blk.	and Survey or Are
At surface At proposed p		E 1450FSL 1850F	FEL 36.26290 N Lat, 108.12110	W Lon	Sec 34 T26N R13W	Mer NMP
14. Distance in mi	les and direction	from nearest town or DF CARSON TRA	post office* DING POST		12. County or Parish SAN JUAN	13. State
		n to nearest property orig. unit line, if any)	or 16. No. of Acres in Lease 1599.00		17. Spacing Unit dedicated 320.00	to this well
18 Distance from	proposed location	n to nearest well, drill	ing, 19. Proposed Depth		20. BLM/BIA Bond No. on	
completed, ap	plied for, on this	lease, ft.	1395 MD		20. BENEBIA Bolid No. 01.	ine
21. Elevations (She 6265 GL	ow whether DF, I	KB, RT, GL, etc.	22. Approximate date work will 06/01/2003	start	23. Estimated duration 5-DAYS	
			24. Attachment	S		
he following, comp	leted in accordance	ce with the requireme	nts of Onshore Oil and Gas Order No. 1	, shall be attached to t	this form:	<u> </u>
	an (if the location	urveyor. is on National Forest ropriate Forest Service	System Lands, the 5. Open 6. Such	20 above).	ons unless covered by an existing formation and/or plans as may	
25. Signature	+ fear	clivs	Name (Printed/Typed) KURT FAGRELIUS			Date 01/13/2003
Title GEOLOGIST						
Approve Sign	Man Man		Name (Printed/Typed)			JAN 14
Title			Office			<u> </u>
pplication approval ocrations thereon. onditions of approva			t holds legal or equitable title to those r	ights in the subject lea	ase which would entitle the app	olicant to conduct

Additional Operator Remarks:

A water based gel-mud will be used to drill surface and production casing hole. Standard 2,000 psi BOP will be used to drill production hole. The Fruitland Coal will be completed from approximately 1225'-1267'. The interval will be fractured.

This action is subject to technical and procedural review pursuant to 43 CFR 3165 3 and appeal pursuant to 43 CFR 3165.4

DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHED "GENERAL REQUIREMENTS".





District I PC Box 1980, Hobbs, NM 88241-1980

District II PO Drawer DD, Artesia, NM 88211-0719

District III 1000 Rio Brazos Rd., Aztec, NM 87410

District IV PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION PO Box 2088 Santa Fe, NM 87504-2088

Form C-Revised February 21, 1991 Instructions on best Submit to Appropriate District Office State Lease - 4 Copies

Fee Lease - 3 Copies

AMENDED REPORT

SALGE FEDERAL A 'OGRID No. 'Operator Name 'Ele 'OGS 15 DUGAN PRODUCTION CORPORATION 10 Surface Location U. or lot no. Section Township Range Lot Ion Feet from the North/South line Feet from the East/Nest line				
SALGE FEDERAL A 9 OGRID No. ODGAN PRODUCTION CORPORATION 10 Surface Location U. or lot no. Section Township Range Lot ion Feet from the North/South line Feet from the East/Nest line J 34 26N 13W 1450 SOUTH 1850 EAST 11 Bottom Hole Location If Different From Surface				
O06515 DUGAN PRODUCTION CORPORATION 10 Surface Location U. or lot no. Section Township Range Lot ion Feet from the North/South line Feet from the East/Nest line J 34 26N 13W 1450 SOUTH 1850 EAST S 11 Bottom Hole Location If Different From Surface	11 Number 94S			
U. or lot no. Section Township Range Lot Ion Feet from the North/South line Feet from the East/Nest line J 34 26N 13W 1450 SOUTH 1850 EAST S 11 Bottom Hole Location If Different From Surface	*Elevation 6255 '			
J 34 26N 13W 1450 SOUTH 1850 EAST S				
	County SAN JUAN			
	County			
320.0 ACRES - (E/2) ¹³ Joint or Infill ¹⁴ Consolidation Code ¹⁵ Order No.				
NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSC OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION	SOLIDATED			
5280.00 Dugan 100% SF-078156 SF-078156 Dugan 100% SF-078156 SF-078156 Dugan 100% SF-078156 SF-078156 SF-078156 SF-078156 SI hereby certify that the info contained herein is true and central to the best of my knowledge and the best of my				

01/15/2003 0 Date *SURVEYOR CERTIFICATION 5280.00 00 I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 5280. Survey Date: DECEMBER 27, 2002 Signature and Seal of Professional Surveyor SON C. EDWARDS EN MEXICO 945 MM_,notgramme 1 070 AND ESSIONAL MIN B 3: 20 450 5280.00 Certificate Number

EXHIBIT B OPERATIONS PLAN

Salge Federal A #94-S

APPROXIMATE FORMATION TOPS:

Ojo Alamo	55 ′	Pictured Cliffs	1271 ′
Kirtland	125 ′		
Fruitland	935 ′	Total Depth	1395′

Catch samples every 10 feet from 1200 feet to total depth.

LOGGING PROGRAM:

Run cased hole GR-CCL-CNL from total depth to surface.

CASING PROGRAM:

Hole	Casing		Setting	Grade and
<u>Size</u>	<u>Size</u>	Wt./ft.	Depth	<u>Condition</u>
9-7/8''	711	20#	120	J-55
6-1/4''	4-1/2''	10.5#	1,395	J-55

Plan to drill a 9-7/8" hole and set 120' of 7" OD, 20#, J-55 surface casing. Then plan to drill a 6-1/4" hole to total depth with gel-water mud program to test the Fruitland Coal. 4-1/2", 10.5#, J-55 production casing will be run and cemented. Cased hole GR-CCL-CNL log will be run. Productive zone will be perforated and fractured. After frac, the well will be cleaned out and production equipment will be installed.

CEMENTING PROGRAM:

<u>Surface</u>: Cement to surface with 70 cf Class B + 2% CaCl₂.

Circulate to surface.

Production Stage-Cement with 150 cf 2%Lodense with

the celloflake/sx followed by 90 cf Class "B" with

the celloflake/sx.

Total cement slurry for production stage is 240 cf.

Circulate cement to surface.

An adequate spacer will be pumped ahead of the cement slurry to help prevent mud contamination of the cement. An adequate number of casing centralizers will be run through usable water zones to ensure that casing is centralized through these zones. The adequate number of centralizers will be determined based on API standards. Centralizers to impart a swirling action around the casing will be used just below and into the base of the lowest usable water zone. These devices will assist mud

displacement, increase cement bonding potential and create an effective hydraulic seal. A chronological log will be kept which records the pump rate, pump pressure, slurry density, and slurry volume for the cement job. The log will be sent to the BLM after completion of the job.

WELLHEAD EQUIPMENT:

Huber 7"x4-1/2" casing head, 1000# WP, tested to 2000#. Huber 4-1/2"x2-7/8" tubing head, 1000# WP, tested to 2000#.

BOP and Related Equipment will include for a 2000 psi system: (Exhibit D)

Annular preventer, double ram, or 2 rams with one being blind and one being a pipe ram.

Kill line (2" minimum)

1 kill line valve (2" minimum)

1 choke line valve

2 chokes

Upper kelly cock valve with handle available Safety valve and subs to fit all drill string connections in use.

Pressure gauge on choke manifold.

2" minimum choke line.

Fill-up line.

Contacts:

Dugan Prod.Corp. Office & Radio Dispatch: 325-1821

Mark	Brown	327-3632 320-8247	
Kurt	Fagrelius	325-4327 320-8248	
John	Alexander	325-6927 320-1935	• •