

Submit 1 Copy To Appropriate District  
Office  
District I  
1625 N French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
October 13, 2009

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-045-29227

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Burnham Gas Com B

8. Well Number 1

9. OGRID Number 778

10. Pool name or Wildcat

Kutz PC

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
BP America Production Company

3. Address of Operator  
P.O. Box 3092 Houston, TX 77253-3092

4. Well Location

Unit Letter M : 850 feet from the South line and 1190 feet from the West line  
Section 12 Township 29N Range 13W NMPM San Juan County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Acid Job ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/31/10 RU Schlumberger and acid transport. Pressure tested pump and lines to 500 psi. held for 3 minutes. good test. released pressure and opened tubing valve. used centrifugal pump and pumped 690 gallons of 15% hcl with 2 gallons of inhibitor, and 2 gallons of ezefflo surfactant. maximum pressure seen was 100 psi. pumped acid, then switched to water. pumped 10 barrels of water with 1 gallon of lo-64 clay stabilizer. Finished pumping water and shut down. RD Schlumber

Landed 2 3/8"; 4.7# J-55 Tbg @ 1459'.

Spud Date:

12/08/1995

Rig Release Date:

04/01/2010

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Cherry Hlava TITLE Regulatory Analyst DATE 04-08-2010

Type or print name Cherry Hlava E-mail address: hlavacl@bp.com PHONE: 281-366-4081

For State Use Only

APPROVED BY: [Signature] TITLE Deputy Oil & Gas Inspector, DATE APR 20 2010  
Conditions of Approval (if any): District #3

4/20