District I	nit I Copy To Appropriate District State of New Mexico		Form C-103		
	Energy, Minerals and Natural Resources		d Natural Resources	October 13, 2009	
1625 N. Fre District II	N. French Dr., Hobbs, NM 88240			WELL API NO.	
	W. Grand Ave , Artesia, NM 88210 OIL CONSERVATION DIVISION			30-045-33218	
<u>District III</u>	1220 South St. Francis Dr.		t. Francis Dr.	5. Indicate Type of Lease STATE ☐ FEE ☐	1
1000 R10 B District IV	razos Rd, Aztec, NM 87410	Santa Fe. J	NM 87505	6. State Oil & Gas Lease No.	<u> </u>
1220 S. St.	Francis Dr., Santa Fe, NM			o. State on & Gas Ecase No.	
87505	OLDIDDA NOT	TICES AND REPORTS ON V	WELLO	7 1 11 11 11 11	
(DO NOT I		7. Lease Name or Unit Agreement Name Valentine Gas Com			
	(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH				
PROPOSAL	LS.)	8. Well Number 1M			
	of Well: Oil Well	Gas Well 🛛 Other		O OCRID V I	
	of Operator erica Production Con			9. OGRID Number 000778	
	ess of Operator	грану		10., Pool name or Wildcat	•
	3092 Houston, TX 77	253	in the state of th	Basin Dakota	
4. Well I	Location	,	, , t t .		
1	Unit LetterC :	350 feet from the No	rth line and 2420	feet from the West	line
l .	Section 32	Township 32			ounty
			her DR, RKB, RT, GR, etc.,		4) 43 5 5
			5984'		
	12. Check	Appropriate Box to Indie	cate Nature of Notice,	Report or Other Data	
	NOTIOE OF I	NTENTION TO	OLID		
DEDEOD		NTENTION TO:		SEQUENT REPORT OF:	
	M REMEDIAL WORK	-	REMEDIAL WOR	 -	
	ARILY ABANDON	-	COMMENCE DRI		
	RALTER CASING	•	☐ CASING/CEMEN	T JOB L	
DOWNHO	OLE COMMINGLE	l			
OTHER	Change Cementing pro	ocedure	OTHER:		
		·- 	nt details, and give pertinent date	s, including estimated date of starting any prop	osed work).
		For Multiple Completions: Attach w	vellbore diagram of proposed com	pletion or recompletion.	
Ket: KRDI	WS KGR0930630621				
The origin	al procedure called for	circulating cement to surfa	as Interes see below sh	ange per conversation between Kel	
Roberts (0	DCD) & Jesse Gracia (B		ce – piease see below cit	ange per conversation between Ke	lly
	JCD) & Jesse Glacia (E	(P)	ce – piease see below cit	-	•
Assuming	,	BP)	ce – piease see below Cit	-	•
Assuming	perf holes @ 2950'	SP)	ce – piease see below cit	-	•
Assuming 1.	perf holes @ 2950'	BP) h circulation through 5 ½" x 7		-	•
1.	perf holes @ 2950' Pump water to establis	h circulation through 5 ½" x 7	5/8" annulus. Contact engi	Nouty NMOCD 24 h	•
	perf holes @ 2950' Pump water to establis	BP)	5/8" annulus. Contact engi	-	•
1.	perf holes @ 2950' Pump water to establis If circulation is establish Pump cement into 5-1/	h circulation through 5 ½" x 7 ned, RIH and set cement retai 2" by 7-5/8" annulus to 2000' -	5/8" annulus. Contact engi	-	nrs 3
1. 2.	perf holes @ 2950' Pump water to establis	h circulation through 5 ½" x 7 ned, RIH and set cement retai 2" by 7-5/8" annulus to 2000' -	5/8" annulus. Contact engi	$N_{O_{cl}(y)}N_{cl}MOCD$ 24 h $prior$ to beginning $operations$	nrs 3
1. 2.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1/2 engineer before pump	h circulation through 5 ½" x 7 ned, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement.	5/8" annulus. Contact engi iner at 2900'. -[950'] - class G cement.	$N_{O_{cl}(y)}N_{cl}MOCD$ 24 h $prior$ to beginning $operations$	nrs 3
1. 2.	perf holes @ 2950' Pump water to establis If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap	th circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus to 5 ½" x 7 5/8" annulus	5/8" annulus. Contact enginer at 2900'. -[950'] - class G cement. ulus: 0.0835 ft3/ft : 0.0999 ft3/ft	Nouty NMOCD 24 h Prior to beginning neer. If no circulation is establish, conta	ore ct
1. 2.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Cap	th circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus to 5 ½" x 7 5/8" annulus bacity of 5 ½" casing	5/8" annulus. Contact enginer at 2900 ". -[950'] - class G cement. ulus: 0.0835 ft3/ft : 0.0999 ft3/ft : 0.1305 ft3/ft	Nouty NMOCD 24 h Prior to beginning neer. If no circulation is establish, conta	ore ct
1. 2.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Cap Plu	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus to 5 ½" x 7 5/8" annulus to 2000' acity of 5 ½" casing goutside casing 2950' to 2449	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. ulus: 0.0835 ft3/ft : 0.0999 ft3/ft : 0.1305 ft3/ft 9' → 501' → 41.83 ft3	No _U ty NMOCD 24 h Prior to beginning operations If no circulation is establish, conta	urs ct
1. 2.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Cap Plue	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus to 5 ½" x 7 5/8" annulus to 2000' acity of 5 ½" casing goutside casing 2950' to 2449 goutside casing 2449' to 2000	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. ulus: 0.0835 ft3/ft : 0.0999 ft3/ft : 0.1305 ft3/ft 9' → 501' → 41.83 ft3 0' → 450' → 45 ft3	Nouty NMOCD 24 h Prior to beginning neer. If no circulation is establish, conta	urs ct
1. 2.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Cap Plu Plu Plu	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus to 5 ½" x 7 5/8" annulus to 2000' acity of 5 ½" casing goutside casing 2950' to 2449	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. ulus: 0.0835 ft3/ft : 0.0999 ft3/ft : 0.1305 ft3/ft 9' → 501' → 41.83 ft3 0' → 450' → 45 ft3	No _U ty NMOCD 24 h Prior to beginning operations If no circulation is establish, conta	urs ct
1. 2. 3.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1/2 engineer before pump Cap Cap Cap Plue Plue Plue Total	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus to 5 ½" x 7 5/8" annulus to 2000' acity of 5 ½" casing goutside casing 2950' to 2448 goutside casing 2449' to 2000 goutside casing 2449' to 2000 goutside casing 2450' to 2900 al + 15% excess = 107 ft3	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. -	Nouty NMOCD 24 h prior to beginning operations If no circulation is establish, conta RCUD MAY 20 '1' OIL CONS. DIV DIST. 3	ors ct
1. 2.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Cap Plu Plu Plu Tota Monitor 5 ½" x 7 5/8" cap	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus of 5 ½" x 7 5/8" annulus bacity of 5 ½" casing goutside casing 2950' to 2449 goutside casing 2449' to 2000 goutside casing 2449' to	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. ulus: 0.0835 ft3/ft : 0.1305 ft3/ft : 0.1305 ft3/ft 9' → 501' → 41.83 ft3 0' → 450' → 45 ft3 0' → 50' → 6.5 ft3 up pressure after WOC. Ble	Nouty NMOCD 24 h prior to beginning operations If no circulation is establish, conta RCVD MAY 20 '1' OIL CONS. DIV	ors ct
1. 2. 3.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Cap Plu Plu Plu Tota Monitor 5 ½" x 7 5/8" cap	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus to 5 ½" x 7 5/8" annulus to 2000' acity of 5 ½" casing goutside casing 2950' to 2448 goutside casing 2449' to 2000 goutside casing 2449' to 2000 goutside casing 2450' to 2900 al + 15% excess = 107 ft3	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. ulus: 0.0835 ft3/ft : 0.1305 ft3/ft : 0.1305 ft3/ft 9' → 501' → 41.83 ft3 0' → 450' → 45 ft3 0' → 50' → 6.5 ft3 up pressure after WOC. Ble	Nouty NMOCD 24 h prior to beginning operations If no circulation is establish, conta RCUD MAY 20 '1' OIL CONS. DIV DIST. 3	ors ct
1. 2. 3.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Plup Plup Plup Tota Monitor 5 ½" x 7 5/8" ca 5, 10, 15 and 30mins.	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. Deacity of 5 ½" x 6 3/4" OH annulus of 5 ½" x 7 5/8" annulus bacity of 5 ½" casing goutside casing 2950' to 2449 goutside casing 2449' to 2000 goutside casing 2449' to	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. ulus: 0.0835 ft3/ft : 0.1305 ft3/ft : 0.1305 ft3/ft 9' → 501' → 41.83 ft3 0' → 450' → 45 ft3 0' → 50' → 6.5 ft3 up pressure after WOC. Bleddata in OpenWells.	Nouty NMOCD 24 h operations If no circulation is establish, conta RCVD MAY 20 '1' OIL CONS. DIV DIST. 3 eed off pressure and record pressure	ors ct
1. 2. 3.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Plup Plup Plup Tota Monitor 5 ½" x 7 5/8" ca 5, 10, 15 and 30mins.	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. cacity of 5 ½" x 6 3/4" OH annulus of 5 ½" x 7 5/8" annulus of 5 ½" x 7 5/8" annulus of 5 ½" casing goutside casing 2950' to 2448 goutside casing 2449' to 2000 go below retainer' 2950' to 2900 al + 15% excess = 107 ft3 asing pressure. Record builduction contact engineer and record of s, perform MIT that meets required.	5/8" annulus. Contact enginer at 2900' . -[950'] - class G cement. -	Nouty NMOCD 24 h operations If no circulation is establish, conta RCVD MAY 20 '1' OIL CONS. DIV DIST. 3 eed off pressure and record pressure	ors ct
1. 2. 3.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Plup Plup Plup Tota Monitor 5 ½" x 7 5/8" ca 5, 10, 15 and 30mins. After cement operations	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. cacity of 5 ½" x 6 3/4" OH annulus of 5 ½" x 7 5/8" annulus of 5 ½" x 7 5/8" annulus of 5 ½" casing goutside casing 2950' to 2448 goutside casing 2449' to 2000 go below retainer' 2950' to 2900 al + 15% excess = 107 ft3 asing pressure. Record buildue Contact engineer and record of s, perform MIT that meets requater	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. -	Nouty NMOCD 24 h operations If no circulation is establish, conta RCVD MAY 20 '1' OIL CONS. DIV DIST. 3 eed off pressure and record pressure	ors ct
1. 2. 3.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Plup Plup Plup Tota Monitor 5 ½" x 7 5/8" ca 5, 10, 15 and 30mins. After cement operations i. Fill hole with w ii. Pressure test to	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. cacity of 5 ½" x 6 3/4" OH annulus of 5 ½" x 7 5/8" annulus of 5 ½" x 7 5/8" annulus of 5 ½" casing goutside casing 2950' to 2449 outside casing 2449' to 2000 go below retainer' 2950' to 2900 al + 15% excess = 107 ft3 asing pressure. Record buildue Contact engineer and record of s, perform MIT that meets requater to 500psi for 30 minutes. Must	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. -	Nouty NMOCD 24 h operations If no circulation is establish, conta RCVD MAY 20 '1' OIL CONS. DIV DIST. 3 eed off pressure and record pressure 19.15.25.14: ting that time.	ct O buildup a
1. 2. 3.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Plup Plup Plup Tota Monitor 5 ½" x 7 5/8" ca 5, 10, 15 and 30mins. After cement operations i. Fill hole with waii. Pressure test to	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. bacity of 5 ½" x 6 3/4" OH annulus of 5 ½" x 7 5/8" annulus bacity of 5 ½" x 7 5/8" annulus bacity of 5 ½" casing goutside casing 2950' to 2448 goutside casing 2449' to 2000 gobelow retainer' 2950' to 2900 al + 15% excess = 107 ft3 asing pressure. Record buildue Contact engineer and record of s, perform MIT that meets requater to 500psi for 30 minutes. Mustachart recorder with maximum	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. -	Nouty NMOCD 24 h operations If no circulation is establish, conta RCVD MAY 20 '1' OIL CONS. DIV DIST. 3 eed off pressure and record pressure	ct O buildup at
1. 2. 3.	perf holes @ 2950' Pump water to establish If circulation is establish Pump cement into 5-1// engineer before pump Cap Cap Plu Plu Plu Plu Tota Monitor 5 ½" x 7 5/8" ca 5, 10, 15 and 30mins. After cement operations i. Fill hole with waii. Pressure test to *Record test on a calibrated within it.	h circulation through 5 ½" x 7 hed, RIH and set cement retain 2" by 7-5/8" annulus to 2000' - bing cement. cacity of 5 ½" x 6 3/4" OH annulus of 5 ½" x 7 5/8" annulus of 5 ½" x 7 5/8" annulus of 5 ½" casing goutside casing 2950' to 2449 outside casing 2449' to 2000 go below retainer' 2950' to 2900 al + 15% excess = 107 ft3 asing pressure. Record buildue Contact engineer and record of s, perform MIT that meets requater to 500psi for 30 minutes. Must	5/8" annulus. Contact enginer at 2900 '. -[950'] - class G cement. -	Nouty NMOCD 24 h operations If no circulation is establish, conta RCVD MAY 20 '1' OIL CONS. DIV DIST. 3 eed off pressure and record pressure 19.15.25.14: ting that time.	ct O buildup at

Spud Date:	07/31/2006	Rig Release Date:	
I hereby certi	fy that the information above is true	and complete to the best of my knowledge and b	elief.
SIGNATURE	E. Cherry Hlava	TITLE <u>Regulatory Analyst</u>	DATE05/17/2010
Type or print For State Us		E-mail address: hlavacl@bp.com	PHONE: <u>281-366-4081</u>
APPROVED	BY: COC & ROS f Approval (if any):	District #3	ector, DATE MAY 2 1 2010

Notify NMOCD 24 hrs prior to beginning operations

site.