<u>District I</u>

1625 N. French Dr., Hobbs, NM 88240

District II

and Aure Artesia NM 98710

State of New Mexico

Energy Minerals and Natural Resources

Department

Form C-144

July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

Dietrot III	1220 South St. France		
District III 1000 Rio Brazos Rd., Azzec, NM 87410	Santa Fe, NM 873		s subunit to the Santa Fe
District IV	SMILLOW E WY I TITLE OF	Environmental Bureau office and pr	ovide a copy to the
1220 S. St. Francis Dr., Santa Fe, NM. 8750		appropriate NMOCD District Office	·
5506 Pro	Pit, Closed-Loop System, Be		
Pro	posed Alternative Method Pern	nit or Closure Plan Application	
l'ype of action:	X Permit of a pit. closed-loop system, I	below-grade tank, or proposed alternative me	thod
1	Closure of a pit, closed-loop system,	below-grade tank, or proposed alternative m	ethod
	Modification to an existing permit		
•	Closure plan only submitted for an e below-grade tank, or proposed altern	existing permitted or non-permitted pit, closed native method	l-loop system,
Instructions: Please submit one	application (Form C-144) per individual j	olt, closed-loop system, below-grade tank or	alternative request
		ould operations result in pollution of surface water, ground	
environment. Nor does approval r	refieve the operator of its responsibility to comply with any	other applicable governmental authority's rules, regulations	or ordinances.
Operator: Burlington Resources	Oil & Gas Company, LP	OGRID#: 14538	
Address: PO Box 4289, Farming	gton, NM 87499		
Facility or well name: ATLANTI	C A 8B		
API Number:	30-045- OCD	Permit Number.	
U/L or Qtr/Qtr: E(SW/NW) Sec	ction: 29 Township: 31N	Range: 10W County: San Juan	
Center of Proposed Design: Latitu	· · · · · · · · · · · · · · · · · · ·	ngitude: 107.91064 °W NAI	D: 1927 X 1983
Surface Owner: X Federal		Frust or Indian Allotment	
Permanent	ection H of 19 15.17.11 NMAC X Drilling a new well Workover or Drill	LLDPE HDPE PVC Other tume: bbl Dimensions L x V	
		ther LLDPE HDPE PVD Other	123456
Below-grade tank: Subsection Volume: Fank Construction material: Secondary containment with leak Visible sidewalls and liner Liner Type: Thickness	bbl Type of fluid:	ach lift and automatic overflow shut-off	RECENTED MAR 2010 OIL CONS. DIV. DIS
Alternative Method:	Samuel Same Same Street Street	e we have a proposed as the constraint for order a few	priora na sa nomena.
toubatice of an exemption reduced in	reguned. Icasephors and besubanded to be St 	elik by Elysourgelik Bikel Chred for Coreder 	

Festig (144

- Oil Cerementan Dicasón

Bago Lot 5

Fencing: Subsection D of 19 15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wite at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify				
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)				
Signs: Subsection C of 19,15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC				
9 Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.				
Please check a bax if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval. (Fencing/BGT Liner) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.				
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Bariconmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.				
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	□No -		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□Yes	No		
Within 300 feet from a permanent residence, school, bospital, institution, or church in existence at the time of initial application.	Yes	□No		
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	□NA			
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image				
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits)	∏Yes ∏NA	No		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		_		
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No		
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.				
Within incorporated manicipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adapted pursuant to NMSA 1978, Section 3-27-3, so amounded - Written confirmation or verification from the municipality; Written approval obtained from the municipality	∏Yes	∏No •		
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	□No		
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division		∐No		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic men	Yes	∏Nc		
Within a 106-year modplain Plinin and		This		

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment CheckligtSubsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached					
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC					
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9					
Sixing Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC					
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC					
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC					
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of					
19.15.17.9 NMAC and 19.15.17.13 NMAC					
Previously Approved Design (attach copy of design) API or Permit					
tree! • • • • • • • • • • • • • • • • • •					
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9 Siting Criteria Comphance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Society Plan - based upon the appropriate requirements of 19.15.17.11 NMAC					
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC					
X Closure Plan (Picase complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Previously Approved Design (attach copy of design) API					
Previously Approved Operating and Maintenance Plan API					
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freehoard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazurdous Odors, including H2S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC					
Proposed Closure: 19.15.17.13 NMAC					
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.					
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-toop System					
Alternative					
Proposed Closure Method: Waste Excavation and Removal					
X Waste Removal (Closed-loop systems only)					
On-site Closure Method (only for temporary pits and closed-loop systems)					
In-place Buriai On-site Trench					
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)					
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, thus the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Samoling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Fermit Number (for liquids, drilling fluids and sail entitings)					
Sel Fackfil and Cover Tradge Epocifications - Evanduate the adjunctions may increase of Follocations High 19-15-17-13 PMAC					
Re-regeration (inc.) beside much the expressible requirements of Subsection (in 1913). (1) 5 PMAC					
Site Restance of 4) - hand yet the warrante example on the sample of the same					

Hara South

16 Note Description for Cloud to Septem 78 of Miles About County of Cont. Tools on Don Africa Only (SO 16 17 12 D.) 164-67.				
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Hant-off Bins Onlys 19.15.17.13.D NMAC) Instructions: Please identify the facilities for the disposal of liquids, dralling fluids and drall cuttings. Use attachment if more than two facilities are required.				
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI Disposal Facility Permit #: NM-01-0011 / NM-01-0	010B			
Disposal Facility Name: Basin Disposal Facility Disposal Facility Permit #: NM-01-005				
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will nibe used for future Yes (If yes, please provide the information No	service and			
Regulared for Impacted areas which will not be used for future service and operations. Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection II of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC				
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				
17 Siting Criteria (Regarding on-site rloyure methods only; 19.15.17.10 NMAC Instructions, Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain string criteria may require administrative approval from the appropriate district office or may be considered in exception which must be submitted to the Santa Fe Environmental Bureau office for cansideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.				
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS: Data obtained from nearby wells	Yes No			
Ground water is between 50 and 100 feet below the bettom of the buried waste	Yes No			
- NM Office of the State Engineer - IWATERS database search; USGS, Data obtained from nearby wells	□N/A			
Ground water is more than 100 feet below the bottom of the buried waste.	Yes No			
- NM Office of the State Engineer - iWATERS database search; USGS, Data obtained from nearby wells	□n/A			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or plays lake (measured from the ordinary high-water mark).	☐Yes ☐No			
- Topographic map, Visual inspection (certification) of the proposed site				
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; satellite image	Yes No			
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application.				
 NM Office of the State Engineer - (WATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978. Section 3-27-3, as amended. 	Yes No			
 Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map: Visual inspection (certification) of the proposed site 	Yes No			
Within the area overlying a Subsurface mine.	Yes No			
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division				
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society;	Yes No			
Topographic map Within a 100-year floodplain FEMA map	Yes No			
18 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	•			
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15 17.11 NMAC				
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17 11 NMAC				
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Waste Materia: Sampling Flan - based upon the appropriate requirements of Subsection F of 195.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)				
Disposal Facility Name and Permit Number (for liquids, drilling funds and drift culturgs or in case on-sale closure standar Solit Cover Design - based upon the appropriate resourcements of Subsection in of 15.45 #1.45 NIMAC	or coming no source.			
Ro-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19 15.17.13 NWAC				
2.1 Site the classical Plans - Investigates the expression to require project of Subsection O of 19.15.17.17 NMAC				

Parts Collide CE Compression Projects Projects Projects

19 Character A and Marking Condition Research				
Operator Application Certification: I hereby certify that the information submitted with shis application is true, accurate and complete to the best of my knowledge and belief.				
Name (Print): 1/1 A // Marie E Jaramillo / Title: Staff Regulatory Technician				
e-mail address: marie e jaramillo@conocophillips.com Telephone: 505-326-9865				
20 OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)				
OCD Representative Signature: 5/3/10				
Title: Euglis Sper OCD Permit Number:				
The Partition of the Pa				
Closure Report (required within 60 days of closure completion): Subsection 8, of 1915 17,13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:				
Closure Wethpd: Waste Excavation and Removal On-site Closure Méthod Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain.				
23				
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Fanks or Haul-off Bins Only:				
Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.				
Disposal Facility Name: Disposal Facility Pennit Number				
Disposal Facility Name. Disposal Facility Pennit Number.				
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?				
Yes (If yes, please demonstrate compiliane to the items below)				
Required for impacted areas which will not be used for finure service and operations:				
Site Reclamation (Photo Documentation)				
Soil Backfüling and Cover installation				
Re-vegetation Application Rates and Seeding Techniqua				
24 <u>Closure Report Attachment Checklist:</u> Instructions: Each of the following items must be attached to the closure report. Please Indicate, by a check mark in				
the box, that the documents are attached.				
Proof of Closure Notice (surface owner and division)				
Proof of Deed Notice (required for on-site closure)				
Plot Plan (for on-site closures and temporary pits)				
Confirmation Sampling Analytical Results (if applicable)				
Waste Material Sampling Analytical Results (if applicable)				
Disposal Facility Name and Permit Number				
Soit Backfilling and Cover Installation				
Re-vegetation Application Rates and Seeding Technique				
Site Reclamation (Photo Documentation)				
On-site Closure Location: Latitude: Longitude: NAD 1927 1983				
25				
Operator Closure Certification:				
Thereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that the closure complex with all applicable closure requirements and conditions specified in the approved closure plan.				
те скоми в выпусков тип от аррисамия визмо в годинетств ини выштым эросурго т те пругочен скозто риш.				
Name (Priut): Title:				
Signature: Date.				
DEPTH OF THE PARTY				
e-mail address;				

Burlington Resources Oil & Gas Company, LP

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burlal of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Jadustrial Ecosystem Inc. (Permit #NM-01-0010E) within 6 months from the date that the draining has released.

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion, Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100

Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality) Source No. two (better quality) Purity 50 percent Purity 80 percent 40 percent Germination 83 percent Garmination . 50 percent Percent PLS 20 percent Percent PLS 2 lb. bulk seed required to make

5 lb. bulk seed required to make 1 lb. PLS 1 lb. PLS