District 1
1625 N French Dr., Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Azice NM 87410
District IV
1220 S. St. Francis Dr., Sania Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.
For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application
Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
Operator: ENEROYNE LLC OGRID#: 185239
Operator: ∠NGROYNE LL OGRID#: 185239 Address.
Facility or well name 200 100 100 100 100 100 100 100 100 100
API Number: 50-031-31103 OCD Permit Number: MCVINASA
Contact of Proposed Design: Latitude 25 91357) Longitude -127 8/199 NAD: 1993
Surface Owner: Federal State Private Tribal Frust or Indian Allotment
Surface of which is reaching state in the arms of mean whomen
Pit: Subsection F or G of 19 15.17.11 NMAC
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A
☐ Lined ☐ Unfined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other
String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
Clased-toop System: Subsection H of 19.15,17.11 NMAC Type of Operation. P&A
Below-grade tank: Subsection 1 of 19.15.17.11 NMAC
Volume:bbt_Type of fluid:
Tank Construction material:
Secondary containment with leak detection [Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other
Liner type: Thickness mit HDPF PVC Other
Alternative Method:

Submitted of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.


String Other	Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, twn strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate Please specify			
Signed in compliance with 19.15.3 103 NMAC	Screen Netting Other			
Puteste check a box if one or more of the following is requested, If not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Instructions: The applicant must demonstrate compliance for each string criteria below in the application. Recommendations of approval. Applicant must demonstrate to empliance for each stanking criteria approval are provided below. Requests regarding changes to certain string criteria below in the appropriate district office or most provided and exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attack passification for request. Please refer to 19.15.17.10 NMAC for guidance. String criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system. Yes No Molfice of the State Engineer - iWATERS database search: USGS, Data obtained from nearby wells Within 300 feet of a contininously flowing watercourse, or 200 feet of any other significant watercourse or takehed, sinkhole, or playa lake (measured from the ordinary high-water must,) Yes No No Yes No Yes No Yes No Yes No No Yes No No No No No No No N	2 12"v 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers			
Siting Criteria Ircearding permitting: 19 15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source muteral are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered on exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system. Ground water is less than 50 feet helow the bottom of the temporary pit, permanent pit, or below-grade tank. Yes No NM Office of the State Engineer - WA TERS database search: USGS. Data obtained from mearby wells Within 100 feet of a continuously, flowing watercourse, or 200 feet of any other significant watercourse or takehed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map, Visual inspection (certification) of the proposed site Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Yes No No No No No No No N	Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blunk: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau of consideration of approval.	office for		
NM Office of the State Engineer - iWA TERS database search; USGS. Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or takehed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map. Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to remporary; emergency; or cavitation pits and below-grade tanks) Visual inspection (certification) of the proposed site: Aerial photo: Satellite image Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application (Applies to permanent pits) Visual inspection (certification) of the proposed site: Aerial photo: Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of uny other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978. Section 3-27-3, as amended. Within 500 feet of a wetland. 11S Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. Figureering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological	Siting Criteria tregarding permitting): 19 15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siling criteria may require administrative approval from the appropriate district office or may be considered on exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or			
lake (measured from the ordinary high-water mark). Topographic map. Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary; emergency, or cavitation pits and below-grade tanks) Visual inspection (certification) of the proposed site; Aerial photo: Satellite image Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application (Applies to permanent pits) Visual inspection (certification) of the proposed site: Aerial photo: Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer—iWATERS database search; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978. Section 3-27-3, as amended. Within 500 feet of a wetland. 1 IS Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine. Written confirmation or verification or mup from the NM EMNRD-Mining and Mineral Division Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological	Chound water is less than 50 feet helow the tottom of the temperature pre- of below gride tank.	☐ Yes ☐ No		
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo: Satellite image Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application (Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo: Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as unended. - Written confirmation or verification from the municipality: Written approval obtained from the municipality Within 500 feet of a wetland. - 11S Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological	lake (measured from the ordinary high-water mark).	Yes No		
Within 1000 feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site. Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality: Written approval obtained from the municipality. Within 500 feet of a wetland. 11S Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division. Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological.	(Applies to temporary, emergency, or cavitation pits and below-grade tanks)			
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978. Section 3-27-3, as amended. Written confirmation or verification from the municipality: Written approval obtained from the municipality Within 500 feet of a wetland. INS Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological	(Applies to permanent pits)	= - 1		
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. Written confirmation or verification from the municipality: Written approval obtained from the municipality Within 500 feet of a wetland. 11S Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological	watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes No		
- IIS Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological	adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	☐ Yes ☐ No		
- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological □ Yes □ No		☐ Yes ☐ No		
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources, USGS: NM Geological	,	☐ Yes☐ No		
Society. Topographic map		☐ Yes☐ No		
Within a 100-year floodplain - FEMA map	· ·	☐ Yes ☐ No		

Temporary Pits. Emergency Pits. and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18. if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15 17.13 NMAC Previously Approved Design (attach copy of design) API Number:
Previously Approved Operating and Maintenance Plan API Number:
above ground steel tunks or haul-off bias and propose to implement waste removal for closure)
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are oftached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S. Prevention Plan Einergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site French Burial Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excayation and Removal Closure Plan Checklist: {19.15.17.13 NMAC} Instructions: Each of the following items must be attached to the closure plan. Please inducate, by a check mark in the box, that the documents are official. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.) Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if	D NMAC) more than two
facilities are required. Discovered Facility Name: ENVIROTE N. TET LANDON Discovered Facility Name: Number NM = 0/20	DULAMI-DI
Disposal Facility Name: BASIM OBSPISH Disposal Facility Permit Number: MM-01-0 Disposal Facility Name: BASIM OBSPISH Disposal Facility Permit Number: MM1-0	01-005 DO 10E
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future ser Yes (If yes, please provide the information below) \(\bigcap \) No	
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specifications based upon the appropriate requirements of Subsection II of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	С
v. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sou provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate disconsidered an exception which must be submitted to the Sunta Fe Environmental Bureau office for consideration of approval. Just demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.	trict office or may be
Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water Is between 30 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search: USGS: Data obtained from nearby wells	Yes No
Ground water is more than 100 feet below the bottom of the buried waste, - NM Office of the State Engineer - iWATERS database search: USGS; Data obtained from nearby wells	Yes No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map: Visual inspection (certification) of the proposed site	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site: Aerial photo: Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application, NM Office of the State Engineer - iWATERS database: Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978. Section 3-27-3, as amended. - Written confirmation or verification from the municipality: Written approval obtained from the municipality.	Yes No
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map: Topographic map: Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM FMNRD-Mining and Mineral Division	☐ Yes ☐ No
 Within an unstable area. Engineering measures incorporated into the design: NM Bureau of Geology & Mineral Resources: USGS: NM Geological Society: Topographic map 	☐ Yes ☐ No
Within a 100-year floodplain FbMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Euch of the following items must be utuched to the closure public a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - hased upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cant Soil Cover Design - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC	.15.17.}1 NMAC

Operator Application Certification:			
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.			
Name (Print): DON DE OFFICIOSIV Title: 6M	٠		
Signature Date: 6/2/10			
e-mail address: DHANOSH 496 @ AOL, Com Jelephone: 1-505-414-854 &	3		
20. OCD Approval: Permit Application (including closuse plan) Closure Plan (only) OCD Conditions (see attachment)			
OCD Representative Signature: Sundon Squell Approval Date: 6/2/10			
Title: Fusivo /spec OCD Permit Number:	<u> </u>		
11. Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.			
Closure Completion Date:	-		
22. Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems or If different from approved plan, please explain.	ગીક)		
23. <u>Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:</u> Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if mort two facilities were utilized.	e thon		
Disposal Facility Name: Disposal Facility Permit Number:			
Disposal Facility Name: Disposal Facility Permit Number:	-		
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations? Yes (If yes, please demonstrate compliance to the items below) \(\bigcup \) No			
Required for impacted areas which will not be used for litture service and operations Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique			
23. Closure Report Attachment Checklist: Instructions: Eoch of the following items must be oftached to the closure report. Please indicate, by o chemark in the hox, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Rectamation (Photo Documentation)	heck		
On-site Closure Location: Latitude Longitude NAD: 1927 1983			
25. Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan. Name (Print)			
Signature: Date:			
e-mail address:			

ENDY 102 CLOSED-LOOP SYSTEM DESIGN AND CONSTRUCTION



ENERDYNE LLC

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Enerdyne may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquid derived from drilling cuttings, as specified per subsection H of 1-9.15.17.11 The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. A water truck will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01 -001 OB). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-010011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # W-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01 -005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # W-01 -0010B). The liner will be disposed of at the McKinley County Landfill located on US Highway 66, Milan, NM. The drying pad will be dosed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the dosed loop containment. Any required repairs will commence immediately

Closed Loop Closure Plan:

 Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01 -0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01 -0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit # NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit -4 W-01-0010B) within 6 months from The date that the drilling rig is released. 2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.1713 i.e.. Dig and haul.

Components:	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-8468015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCO when the reclaimed area is seeded.
- 5. Energyne shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety	PLA/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgass	Ely-crest	3.0
Bottlebrush Squirreltall	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100

Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality) Source No. two (better quality) Purity 50 percent 80 percent **Purity** Germination 40 percent Germination 63 percent Percent PLS Percent PLS 50 percent 20 percent 5lb. bulk seed required to make 2 lb bulk- seed required to make

1 lb. PLS 1 lb. PLS