

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S. St. Francis Dr, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-045-34986

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.
34986

7. Lease Name or Unit Agreement Name

Ruby

8. Well Number 2

9. OGRID Number 22044

10. Pool name or Wildcat
Basin Fruitland Coal

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
McElvain Oil & Gas Properties, Inc

3. Address of Operator
1050 17th Street, Suite 1800, Denver, CO 80265

4. Well Location

Unit Letter P : 370 feet from the South line and 881 feet from the East line
Section 3 Township 29 N Range 13W NMPM County San Juan

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
5434 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/18/2010 @ 9:00 Continued drilling a 12 1/4" hole to 250'.

6/19-20 2010 Drilled hole to 525'. Cleaned Pits.

6/21/2010 Ran 12 Jts new 8 5/8" 24# J-55 csg. Landed @ 520'. Cemented as follows:
330 sx Type III cmt, 2% CaCl, 14.5 ppg, 1.14 Y.
Circulated 23 bbls to surface.

6/22/2010 Test BOP,choke manifold @ 2000psi 10 min, 200 psi 5 min.. Test csg @ 600 psi 30 minutes. All held.

RCVD JUN 30 '10
OIL CONS. DIV.
DIST. 3

Spud Date:

6/10/2010

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Debby Powell TITLE Eng Tech Supervisor DATE 6/28/2110

Type or print name Deborah Powell E-mail address: DebbyP@McElvain.com PHONE: 303-893-0933

For State Use Only

APPROVED BY: Deputy Oil & Gas Inspector, TITLE District #3 DATE JUL 06 2010

Conditions of Approval (if any):