This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Completion

NEW MEXICO OIL CONSERVATION DIVISION

Page 1 Revised June 10, 2003

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Well

Operator WILLIAMS PRODUCTION Lease Name Rosa Unit No. 023C DK/MV Location Of Well: Unit Letter L Sec 29 Twp 31N Rge 05W API # 30-0 3927609 Type of Prod. Name of Reservoir or Pool Method of Prod. Prod. Medium (Oil or Gas) (Flow or Art. Lift) (Tbg. Or Csg.) Upper Completion Lower Completion **Pre-Flow Shut-In Pressure Data** Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Upper Completion 1020 4/26/10) days T100 C187 Length of Time Shut-In SI Press. Psig Stabilized? (Yes) or No) Lower Hour, Date, Shut-In Completion 191 Flow Test No. 1 Commenced at (hour, date)* Zone producing (Upper or Lower): 5/3/10 Time Lapsed Time Pressure Prod. Zone Remarks Since* Lower Compl. Upper Compl. Temp. (Hour, Date) T 104 1055 5/4 24 hr C 190 106 4840 C 192 T 108 72 hr 194 WAY 2010 T 109 C 197 T 112 198 T 114 C 200 roduction rate during test 80 MCFPD; Test thru (Orifice or Meter): Mid-Test Shut-In Pressure Data Stabilized? (Yes or No) Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Upper Completion Stabilized? (Yes or No) Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Lower

(Continue on reverse side)

Flow Test No. 2

Commenced at (hour, date)**				One producing (Upper or Lower):			
Time	Lapsed Time			Prod. Zone Remarks			
(Hour, Date)	Since**	Upper Compl.	Lower Compl.	Temp.	′		
				+	<u> </u>		
					<u> </u>		
Production rate	during test	<u></u>	<u></u>	<u> </u>			
Oil:	BOPD based	d on	Bbls. In	Hrs.	Grav.	GOR	
Gas:	MCFP	D; Test thru (Ori	fice or Meter):				
Remarks: Sh Achieved	ut well in a seperation.	Durng flow	test test C	ion. Flower	Lower (DK	GOR	
		tion herein contain	ned is true and con	plete to the best			
Approved			Operator 4	Operator Williams Production			
	il Conservation I			-	C .1	/	
Valy G. Roots				By Vasa	By Vason SM. th		
Ву				Title jasm with & Williams con			
TitleDeputy Oil & Gas Inspector,				Title jasm swith ewilliams com E-mail Address jason swith ewilliams com			
	,			Date 4			

Northwest New Mexico Packer Leakage Test Instructions
e commenced on each multiply
f actual completion of the well, and during Flow Test No.

. A packer leakage test shall be commenced on each multiply ompleted well within seven days after actual completion of the well, and naually thereafter as prescribed by the order authorizing the multiple ompletion. Such tests shall also be commenced on all multiple ompletions within seven days following recompletion and/or chemical r fracture treatment, and whenever remedial work has been done on a rell during which the packer or the tubing have been disturbed. Tests hall also be taken at any time that communication is suspected or when equested by the Division

. At least 72 hours prior to the commencement of any packer leakage st, the operator shall notify the Division in writing of the exact time the st is to be commenced. Offset operators shall also be so notified.

The packer leakage test shall commence when both zones of the dual impletion are shut-in for pressure stabilization. Both zones shall remain nut-in until the well-head pressure in each has stabilized, provided tweever, that they need not remain shut-in more than seven days.

For Flow Test No. 1, one zone of the dual completion shall be oduced at the normal rate of production while the other zone remains aut-in. Such test shall be continued for seven days in case of a gas well d 24 hours in the case of an oil well. Note: if, on an initial packer akage test, a gas well is being flowed to the atmosphere due to the lack a pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be ut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).