Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

FORM APPROVED OMB NO. 1004-0137 Expires July 31, 2010

5. Lease Serial No.

NMNM~	03523
TATATIAL-	UJJZJ

6. If Indian, Allottee or Tribe Name

abandoned well. Use For						
SUBMIT IN TRIPLICAT	TE - Other instructions	on page &	CEIVED	7. If Unit or Ca	A/Agreement, Name and/or No.	
Oil Well A das well Other			8. Well Name and No. FEDERAL 31 #21			
2. Name of Operator	•	Farmi	ngton Field Office		<u></u>	
XTO Energy Inc. Bureau of Land Manageme 3a. Address 3b. Phone No. (include area code)				9. API Well No.		
382 CR 3100 Aztec, NM 87410			505-333-3176 _		30-045-24964 10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					WEST KUIZ PICTURED CLIFFS/	
990' FNL & 1650' FWL NENW SEC.31(C)-T27N-R11W N.M.P.M.		BASIN FRUITLAND COAL				
		11. County or Parish, State				
12. CHECK APPROPRIATI	E BOY(ES) TO INDIC	TATE MATIDE	OF NOTICE REPO	SAN JUAN	NM NM	
TYPE OF SUBMISSION	BOX(ES) TO INDIC	CATE NATURE	TYPE OF ACTION		EK DATA	
THE OF SOBINISSION						
Notice of Intent	Acıdize ,	Deepen	Productio	n (Start/Resume)	Water Shut-Off	
X Subsequent Report	Alter Casing	X Fracture Treat	Reclamati	on	Well Integrity	
22 dassequent report	Casing Repair	New Construc	tion Recomple	ete	Other	
Va Final Abandonment Notice	Change Plans	Plug and Aban	don Temporar	ily Abandon		
KZ	Convert to Injection	Plug Back	Water Dis	posal		
XTO Energy Inc. has refraced the The rig moved in on 6/11/2010 and report was sent on 7/30/2010 report	l a casing leak wa	s found. Repa	airs were compl			
			RCVD AUG 24'10			
				OIL	CONS. DIV. DIST. 3	
14. I hereby certify that the foregoing is true and correct		1				
Name (Printed/Typed) TEENA M. WHITING		Title RF	GULATORY COMPLI	־ANCE: ידאריניהידי	CTAN	
Signature of some m. 41 hitima			2/2010	AOC	edten ean pro	
THIS	S SPACE FOR FEDE	RAL OR STATE	OFFICE USE		or real rooms (Constitution)	
Approved by		Title		Da	AUS 6 2010	
Conditions of approval, if any, are attached. Approval of this not the applicant holds legal or equitable title to those rights in the sul entitle the applicant to conduct operations thereon.	ice does not warrant or centry	NOC Deffice			HIGTON FIELD OFFICE	
Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212,	makes it a crime for any persor	knowingly and willful	ly to make to any departm		United States any false,	



fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Federal 31-21

6/11/2010

MIRU Rig.

6/30/2010

MIRU AFU. DO CIBP @ 1,123'. DO btm of CIBP & CO fill fr/1,566'-1,570' (hd fill, CIBP @ 1,574').

PU &TIH w/4-1/2" ArrowSet pkr, 2 jts 2-3/8" N-80 tbg, XO & 50 jts 2-7/8" DSS-AB tbg. Set pkr @ 1.543'.

7/2/2010

MIRU frac equip. A. Lwr/ FC perfs fr/1,560' - 66' w/500 gals 15% NEFE HCl ac. Frac Lwr FC perfs w/10,974 gals N2 foamed fld carrying 3,215# sd per denseometer. Frac strg started lkg in WH. RD frac equip. RU flwback FL. Rlsd pkr. Set pkr @ 1,543'. RU frac equip.

Frac Lwr FC perfs w/34,335 gals N2 foamed fld carrying 27,996# sd per denseometer.

7/3/2010

Cont'd flwg fr/Lwr FC frac on ck. RD flwback equip.

7/6/2010

MIRU SLU. RIH w/4-1/2" 10K CBP & set @ 1,535'. POH w/setting tl. RDMO WLU. TIH w/4-1/2" ArrowSet pkr & tbg. Set pkr @ 1,481'.

7/8/2010

MIRU frac equip. A. Upr/FC perfs fr/1,518' - 26' w/500 gals 15% NEFE HCl ac. Frac Upr/FC perfs w/4,393 galls 60Q N2 foamed fld carrying 2,700# sd per denseometer. Pressd out @ 6,000 psig. RU flwback FL. RU frac equip. Frac Upr/FC perfs w/12,411 gals 60Q N2 foamed fld carrying 12,300# sd per denseometer. Press to max TP. RDMO frac equip.

7/9/2010

Cont'd flwg fr/Upr FC frac on ck. Rlsd pkr @ 1,481'. TOH w/2-7/8" tbg & pkr. TIH w/bit & 2-3/8" tbg. CO fill fr/1,507' - 1,512'.

7/10/2010

CO fill fr/1,515' - 1,535' (CBP). DO CBP. DO hd fill fr/1,566' - 70' (CIBP). Drld on CIBP-.

7/12/2010

DO CIBP. CO fill fr/1,740' - 45' (PBTD). TOH w/tbg, TIH w/20' OEMA, SN & 2-3/8", 4.7#, J-55, EUE 8rd tbg. Ld tbg w/donut & seal assy as follows; SN @ 1,618'. EOT @ 1,639'. FC perfs fr/1,518' - 66'. PC perfs fr/1,580' - 1,600'. PBTD @ 1,745'. PU & loaded w/2" x 1-1/2" x 10' RWAC-Z (DV) EPS pmp. TIH w/pmp &, rods. Seated pmp. GPA. Clamped rods off. RDMO Rig. Rtn well to construction dept.