

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 17 2010

Sundry Notices and Reports on Wells

Farmington Field Office
Bureau of Land Management1. Type of Well
GAS

2. Name of Operator

ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit F (SENW), 1815' FNL & 2159' FWL, Section 1, T30N, R6W, NMPM

5. Lease Number
SF-0794016. If Indian, All. or
Tribe Name7. Unit Agreement Name
San Juan 31-6 Unit8. Well Name & Number
San Juan 31-6 Unit 40M9. API Well No.
30-039-3089610. Field and Pool
Blanco MV / Basin DK11. County and State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action


☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Completion Report☒ Subsequent Report☐ Recompletion☐ New Construction

RCVD SEP 8 '10

☐ Final Abandonment☐ Plugging☐ Non-Routine FracturingOIL CONS. DIV.
DIST. 3☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection

13. Describe Proposed or Completed Operations

Please See Attached



14. I hereby certify that the foregoing is true and correct.

Signed Crystal Tafoya Crystal TafoyaTitle Staff Regulatory Technician Date 8/17/2010

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOCD

San Juan 31-6 Unit 40M
API# 30-039-30896
Blanco Mesaverde / Basin Dakota
ConocoPhillips Company

05/12/2010 RU Basin W/L. RIH w/ 3 3/4" gauge ring. Run GR/CCL/CBL Logs. TOC @ 2760' ✓. RD W/L 5/12/10

05/21/2010 RU Basin W/L. Run GR/CCL/CBL Logs. RD W/L.

06/08/2010 Install Frac valve. PT csg to 6600#/30min @ 10:30hrs on 6/8/10. Test – OK. ✓

06/09/2010 RU Basin W/L to Perf **Dakota** w/ .34" diam. – 2SPF @ 7816', 7818', 7820', 7822', 7824', 7826', 7828', 7830', 7832', 7834', 7836', 7838', 7840', 7842', 7855', 7864', 7866', 7868', 7870', 7872', 7874', 7876', 7882', 7884', 7890', 7892', 7906', 7908', 7910' = 58 Holes. Acidize w/ 10bbbls 15% HCL. Frac w/ 106,554gals SlickWater w/ 40,040# of 20/40 TLC Sand. Set CBP @ 6050'.

Perf **Point Lookout** w/ .34" diam. – 1SPF @ 5564', 5570', 5632', 5638', 5646', 5656', 5668', 5676', 5690', 5706', 5720', 5726', 5740', 5764', 5772', 5812', 5822', 5836', 5844', 5854', 5880', 5886', 5898', 5930', 5936' = 25 Holes. Acidize w/ 10bbbls 15% HCL. Frac w/ 39,312gals 70% SlickWater w/ 102,119# of 20/40 Arizona Sand. N2:1,246,000SCF. Set CFP @ 5510'.

Perf **Upper Menefee/Cliffhouse** w/ .34" diam. – 1SPF @ 5074', 5082', 5096', 5108', 5120', 5142', 5154', 5168', 5188', 5200', 5218', 5233', 5244', 5264', 5274', 5286', 5297', 5310', 5326', 5338', 5350', 5362', 5380', 5390', 5406', 5440', 5452' = 27 Holes. Acidize w/ 10bbbls 15% HCL. Frac w/ 36,792gals 70% SlickWater w/ 100,827# of 20/40 Arizona Sand. N2:1,198,000SCF. Set CFP @ 5010'.

Perf **Lewis** w/ .34" diam. – 1SPF @ 4536', 4544', 4550', 4556', 4564', 4576', 4592', 4606', 4614', 4626', 4686', 4696', 4706', 4714', 4726', 4738', 4758', 4774', 4786', 4800', 4858', 4922', 4930', 4962', 4970' = 25 Holes. Frac w/ 36,078gals 75% AquaStar foam w/ 101,331# of 20/40 Arizona Sand. N2:1,753,000SCF. Start Flowback. ✓

07/19/2010 RIH w/ CBP set @ 4410'. RD Flowback & Frac Equip.

07/29/2010 MIRU DWS 24. ND WH. NU BOPE. PT BOPE. Test – OK

07/30/2010 Tag CBP set @ 4410' & M/O. Flowback.

07/30/2010 **Started selling MV gas thru GRS.** ✓

08/02/2010 CO & M/O CFP @ 5010'. CO & M/O CFP @ 5510'. Flow Test MV. ✓ Flowback.

08/03/2010 CO & M/O CBP @ 6050'. C/O to PBTB @ 7929'. Flowback.

08/03/2010 **Started selling DK gas with MV gas thru GRS.** ✓

08/09/2010 Run Spinner on Dakota. ✓ RIH w/ 255jts, 2 3/8", 4.7#, L-80 tbg set @ 7831' w/ F-Nipple @ 7829'. ND BOPE. NU WH. RD RR @ 20:00hrs on 8/9/10. ✓