

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*


1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐		5. LEASE DESIGNATION AND SERIAL NO. Jicarilla Contract 100																									
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP. EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache																									
2. NAME OF OPERATOR ConocoPhillips Company		7. UNIT AGREEMENT NAME Report to lease																									
3. ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700		8. FARM OR LEASE NAME, WELL NO. Jicarilla D 22Y																									
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface M (SWSW), 1225' FSL & 1095' FWL At top prod. interval reported below N (SESW), 1104' FSL & 1901' FWL At total depth N (SESW), 1104' FSL & 1901' FWL		9. API WELL NO. 30-039-30837-0002																									
10. FIELD AND POOL, OR WILDCAT Blanco Mesaverde		11. SECTION, T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 32, T26N, R3W																									
12. COUNTY OR PARISH Rio Arriba		13. STATE New Mexico																									
14. PERMIT NO. DATE ISSUED 08/18/2010		15. DATE SPUDDED 03/18/2010																									
16. DATE T.D. REACHED 04/02/2010		17. DATE COMPL. (Ready to prod.) 08/18/2010																									
18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* GL 7338' KB 7354'		19. ELEV. CASINGHEAD																									
20. TOTAL DEPTH, MD & TVD MD 6446' TVD 6325'		21. PLUG. BACK T.D., MD & TVD MD 6443' TVD 6322'																									
22. IF MULTIPLE COMPL., HOW MANY* 0		23. INTERVALS DRILLED BY yes																									
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Blanco Mesaverde 6122' - 6432'		25. WAS DIRECTIONAL SURVEY MADE YES																									
26. TYPE ELECTRIC AND OTHER LOGS RUN GR/CCL/CBL		27. WAS WELL CORED No																									
28. CASING RECORD (Report all strings set in well)																											
<table border="1"><thead><tr><th>CASING SIZE/GRADE</th><th>WEIGHT, LB./FT.</th><th>DEPTH SET (MD)</th><th>HOLE SIZE</th><th>TOP OF CEMENT, CEMENTING RECORD</th><th>AMOUNT PULLED</th></tr></thead><tbody><tr><td>9 5/8" / H-40</td><td>32.3#</td><td>230'</td><td>12 1/4"</td><td>Surface, 172sx(220cf-39bbbls)</td><td>15 bbbls</td></tr><tr><td>7" / J-55</td><td>23#</td><td>4334'</td><td>8 3/4"</td><td>Surface, ST@3569'</td><td>68 bbbls</td></tr><tr><td>4 1/2" / J-55</td><td>11.6#</td><td>6444'</td><td>6 1/4"</td><td>TOC@2816', 160sx(327cf-58bbbls)</td><td></td></tr></tbody></table>				CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED	9 5/8" / H-40	32.3#	230'	12 1/4"	Surface, 172sx(220cf-39bbbls)	15 bbbls	7" / J-55	23#	4334'	8 3/4"	Surface, ST@3569'	68 bbbls	4 1/2" / J-55	11.6#	6444'	6 1/4"	TOC@2816', 160sx(327cf-58bbbls)	
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED																						
9 5/8" / H-40	32.3#	230'	12 1/4"	Surface, 172sx(220cf-39bbbls)	15 bbbls																						
7" / J-55	23#	4334'	8 3/4"	Surface, ST@3569'	68 bbbls																						
4 1/2" / J-55	11.6#	6444'	6 1/4"	TOC@2816', 160sx(327cf-58bbbls)																							
29. LINER RECORD																											
<table border="1"><thead><tr><th>SIZE</th><th>TOP (MD)</th><th>BOTTOM (MD)</th><th>SACKS CEMENT*</th><th>SCREEN (MD)</th></tr></thead><tbody><tr><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>				SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)																			
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)																							
30. TUBING RECORD																											
<table border="1"><thead><tr><th>SIZE</th><th>DEPTH SET (MD)</th><th>PACKER SET (MD)</th></tr></thead><tbody><tr><td>2 3/8", 4.7#, L-80</td><td>6347'</td><td></td></tr></tbody></table>				SIZE	DEPTH SET (MD)	PACKER SET (MD)	2 3/8", 4.7#, L-80	6347'																			
SIZE	DEPTH SET (MD)	PACKER SET (MD)																									
2 3/8", 4.7#, L-80	6347'																										
31. PERFORATION RECORD (Interval, size and number) Point Lookout/Lower Menefee w/ .34" diam. 1SPF @ 6122' - 6432' = 25 Holes Mesaverde Total Holes = 25																											
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. 6122' - 6432' Acidize w/ 10bbbls 15% HCL. Frac w/ 29,686gals 75% SlickWater w/ 100,180# of 20/40 Arizona Sand.																											
33. PRODUCTION DATE FIRST PRODUCTION N/A PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) FLOWING WELL STATUS (Producing or shut-in) SI																											
DATE OF TEST 08/16/2010 HOURS TESTED 1 hr. CHOKE SIZE 1/2" PROD'N FOR TEST PERIOD 0 OIL-BBL 138 mcf/h GAS-MCF trace WATER-BBL trace GAS-OIL RATIO																											
FLOW. TUBING PRESS. SI - 645psi CASING PRESSURE SI - 855psi CALCULATED 24-HOUR RATE 0 OIL-BBL 3300 mcf/d GAS-MCF 6 bwpd WATER-BBL OIL GRAVITY-API (CORR.)																											
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold																											
35. LIST OF ATTACHMENTS																											
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records																											

SIGNED *Crystal Medina*

TITLE **Staff Regulatory Technician**

DATE **8/20/2010**

*(See Instructions and Spaces for Additional Data on Reverse Side)
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



API # 30-039-30837	Jicarilla D 22Y	
Ojo Alamo	3702'	3782' White, cr-gr ss.
Kirtland	3782'	3855' Gry sh interbedded w/tight, gry, fine-gr ss.
Fruitland	3855'	4024' Dk gry-gr carb sh, coal, grn silts, light-med gry, tight, fine gr ss.
Pictured Cliffs	4024'	4145' Bn-Gry, fine grn, tight ss.
Lewis	4145'	4480' Shale w/siltstone stringers
Huerfano Bentonite	4480'	4976' White, waxy chalky bentonite
Chacra	4976'	5545' Gry fn grn silty, glauconitic sd stone w/drak gry shale
Mesa Verde	5545'	5804' Light gry, med-fine gr ss, carb sh & coal
Menefee	5804'	6202' Med-dark gry, fine gr ss, carb sh & coal
Point Lookout	6202'	6446' Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation
Mancos		' Dark gry carb sh.
Gallup		' Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. interbed sh
Greenhorn		' Highly calc gry sh w/thin lmst.
Graneros		' Dk gry shale, fossil & carb w/pyrite incl.
Dakota		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay Y shale breaks
Morrison		' Interbed grn, brn & red waxy sh & fine to coarse grn ss