

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Jun 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-045-35074
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Atlantic Com B
8. Well Number 8M
9. OGRID Number 14538
10. Pool name or Wildcat Blanco Mesaverde / Basin Dakota
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6376' GR

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☐ Gas Well ☒ Other	
2. Name of Operator Burlington Resources Oil Gas Company LP	
3. Address of Operator P.O. Box 4289, Farmington, NM 87499-4289	
4. Well Location Unit Letter L : 1290 feet from the South line and 820 feet from the West line Section 23 Township 31N Range 10W NMPM San Juan County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6376' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
OTHER: ☐		OTHER: ☒ COMPLETION REPORT	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Please See Attached

RCVD OCT 6 '10
OIL CONS. DIV.
DIST. 3

Spud Date: **05/20/2010**

Rig Released Date: **06/04/2010**

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Crystal Tafoya* TITLE Staff Regulatory Technician DATE 10/5/2010

Type or print name Crystal Tafoya E-mail address: crystal.tafoya@conocophillips.com PHONE: 505-326-9837

For State Use Only

APPROVED BY: *Kelly G. Rosta* TITLE Deputy Oil & Gas Inspector, District #3 DATE OCT 15 2010
Conditions of Approval (if any):

K

Atlantic Com B 8M
API# 30-045-35074
Blanco Mesaverde / Basin Dakota
Burlington Resources Oil & Gas Company, LP

06/22/2010 RU WESC W/L. RIH w/ 3 3/4" gauge ring. Run GR/CCL/CBL Logs. TOC @ 2410'. RD W/L 6/22/10

07/20/2010 RU W/L. Run GR/CCL/CBL Logs. RD W/L 7/20/10.

08/11/2010 Install Frac valve. PT csg to 6600#/30min @ 08:00hrs on 8/11/10. Test – OK.

08/18/2010 RU W/L to Perf **Dakota** w/ .34" diam. – 2SPF @ 7936', 7946', 7950', 7954', 7958', 7962', 7970', 7978', 7982', 7990', 7999', 8006', 8010', 8014', 8018' = 30 Holes. 1SPF @ 7812', 7818', 7824', 7830', 7836', 7842', 7848', 7854', 7864', 7870', 7876', 7882', 7888', 7894', 7906', 7912', 7918', 7924' = 18 Holes. Dakota Total Holes = 48. Acidize w/ 10bbls 15% HCL. Frac w/ 31,080gals 85% SlickWater w/ 25,150# of 20/40 Arizona Sand. N2:5,106,000SCF. Set CFP @ 6110'.
Perf **Point Lookout** w/ .34" diam. – 1SPF @ 5430', 5454', 5527', 5538', 5564', 5588', 5656', 5664', 5676', 5686', 5702', 5720', 5732', 5744', 5758', 5770', 5784', 5844', 5896', 5910', 5924', 5938', 5954', 5982', 5994' = 25 Holes. Acidize w/ 10bbls 15% HCL. Frac w/ 35,490gals 70% SlickWater w/ 99,939# of 20/40 Arizona Sand. N2:1,287,000SCF. Set CFP @ 5410'.
Perf **Upper Menefee/Cliffhouse** w/ .34" diam. – 1SPF @ 4964', 4978', 4998', 5010', 5020', 5034', 5050', 5070', 5090', 5106', 5136', 5160', 5180', 5200', 5210', 5223', 5238', 5250', 5278', 5296', 5308', 5320', 5346', 5362', 5390' = 25 Holes. Acidize w/ 10bbls 15% HCL. Frac w/ 37,842gals 70% SlickWater w/ 100,375# of 20/40 Arizona Sand. N2:1,126,000SCF. Set CFP @ 4910'.
Perf **Lewis** w/ .34" diam. – 1SPF @ 4516', 4530', 4544', 4554', 4570', 4578', 4590', 4630', 4640', 4652', 4668', 4696', 4710', 4720', 4734', 4746', 4762', 4780', 4788', 4798', 4818', 4832', 4846', 4858', 4870' = 25 Holes. Frac w/ 33,390gals 75% Visco Elastic Foam w/ 115,063# of 20/40 Arizona Sand. N2:1,825,000SCF. Start Flowback.

08/23/2010 RIH w/ CBP set @ 4420'. RD Flowback & Frac Equip.

09/13/2010 MIRU AWS 448. ND WH. NU BOPE. PT BOPE. Test – OK. Tag CBP @ 4420' & M/O.

09/14/2010 CO & M/O CFP @ 4910'. CO & M/O CFP @ 5410'.

09/15/2010 Started selling MV gas thru GRS.

09/16/2010 CO & M/O CFP @ 6110'. Flowback.

09/16/2010 Started selling DK gas with MV gas thru GRS.

09/17/2010 RIH w/ CBP set @ 6135'.

09/18/2010 Flow Test MV. CO & M/O CBP set @ 6135'. C/O to PBTD @ 8026'. Flowback.

09/21/2010 Run Spinner on Dakota. RIH w/ 258jts, 2 3/8", 4.7#, L-80 tbg set @ 7925' w/ F-Nipple @ 7923'. ND BOPE. NU WH. RD RR @ 17:30hrs on 9/21/10.