UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED	
OM B No. 1004-0137	
Expires: March 31, 200)


	Lease Serial No.
i	272 5272 5 4054

CLINDO	V NOTICES AND DE		T110	5. Lease Seria		1
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					, Allottee or Tribe Name	
abandoned v	well. Use Form 3160-3 (
SUBMIT IN TH	RIPLICATE- Other inst	tructions on reve	erse side.	7. If Unit or	CA/Agreement, Name and/or No.	
1. Type of Well ☐ Oil Well ☐ ☐	✓ Gas Well □ □ Other	OCT	01 2010	8. Well Nar	me and No.	
2. Name of Operator NM&O Op	erating Company	Farmingto	on Field Office	Guardi 9. API We	an Federal #1	
3a Address		3b. Phone No. (include area code)		30-039-	-24023	
15 East 5th Street Suite 3000, Tulsa, OK.74103 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			918 584 3802		d Pool, or Exploratory Area n Pictured Cliffs	
790' FSL & 790' FEL (P) Section 5, T25N, R2W				11. County	or Parish, State	
170 TOD SO 170 TELLI (E) OPERIOR OF REALITY RIM IT				Rio Arı	riba Co. , NM	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA						
TYPE OF SUBMISSION		T	YPE OF ACTION			
Notice of Intent	Acidize	Deepen	Production (Sta			
Subsequent Report	Alter Casing Casing Repair	Fracture Treat Reclamation New Construction Recomplete		Well Integrity Other		
	Change Plans	Plug and Abandon	,	oandon		
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal			
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea Guardian Federal #1 SE/4 SE/4 Sec 5-T25N-F		ally, give subsurface locate wide the Bond No. on file on results in a multiple con	tions and measured and true with BLM/BIA. Requirempletion or recompletion	ie vertical depthed subsequent r in a new interva	ns of all pertinent markers and zone reports shall be filed within 30 days al, a Form 3160-4 shall be filed once	5.
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea Guardian Federal #1 SE/4 SE/4 Sec 5-T25N-R Rio Arriba Co., NM Plugging and Abandonn July 23 through July 27, valve. Load tbg to 1000 land @ 3461'. Load tbg displaced. Sting into rete cement and displace w/ 4 holes @ 2200'. RIH w/ RIH and perf 4 holes @	irectionally or recomplete horizonta in the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be ddy for final inspection.)	ally, give subsurface locate wide the Bond No. on file on results in a multiple corpe filed only after all requires. Install weight indicate OOH w/ 2 3/8" tbg. R st retainer. Set retaine 2 BPM at 560 psig thruer w/ 179 psig in tbg. tbg and cement dn tbg 73'. Mix and pump 17	tions and measured and the with BLM/BIA. Require a pletion or recompletion irements, including reclar and the w/4 1/2" squeeze rerand shear off. Pumpough perfs @ 3805'-38 t. Left 5 sx cmt to fall or sw/50 sx cement @ 1 1	de vertical depthed subsequent rin a new intervaluation, have been declared downhole petainer. Assection of the mixed top of retait top of retait /2 BPM @ 50	ns of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once on completed, and the operator has rump. Lay down. Drop standing mbly on 113 jts 2 3/8" tbg and circulate up csg w/3 bbls as and squeeze perfs w/37 sx aer. POOH w/ tbg. RIH and po 10 psig. POOH w/tbg. Fill hole.	s.
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea Guardian Federal #1 SE/4 SE/4 Sec 5-T25N-R Rio Arriba Co., NM Plugging and Abandonn July 23 through July 27, valve. Load tbg to 1000 land @ 3461'. Load tbg displaced. Sting into rete cement and displace w/ 4 holes @ 2200'. RIH w/ RIH and perf 4 holes @	irectionally or recomplete horizonta in the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be day for final inspection.) R2W ment Operations: , 2010: MIRU well service unit. psig - OK. NDWH. NUBOP. Per and circulate 15 bbls water passainer and establish inj rate of 2 3 bbls water. Sting out of retain the gand set @ 2250'. Pack off the 325. RIH w/tbg and land @ 37 DBOP. Rig down and move out.	ally, give subsurface locate wide the Bond No. on file on results in a multiple corpe filed only after all requires. Install weight indicate OOH w/ 2 3/8" tbg. R st retainer. Set retaine 2 BPM at 560 psig thruer w/ 179 psig in tbg. tbg and cement dn tbg 73'. Mix and pump 17	tions and measured and the with BLM/BIA. Require a pletion or recompletion irements, including reclar and the w/4 1/2" squeeze rerand shear off. Pumpough perfs @ 3805'-38 t. Left 5 sx cmt to fall or sw/50 sx cement @ 1 1	de vertical depthed subsequent rin a new intervaluation, have been declared downhole petainer. Assection of the mixed top of retait top of retait /2 BPM @ 50	ns of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once on completed, and the operator has rump. Lay down. Drop standing mbly on 113 jts 2 3/8" tbg and circulate up csg w/3 bbls as and squeeze perfs w/37 sx aer. POOH w/ tbg. RIH and po 10 psig. POOH w/tbg. Fill hole.	s. g
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea Guardian Federal #1 SE/4 SE/4 Sec 5-T25N-F Rio Arriba Co., NM Plugging and Abandonn July 23 through July 27, valve. Load tbg to 1000 land @ 3461'. Load tbg displaced. Sting into ret: cement and displace w/ 4 holes @ 2200'. RIH w/ RIH and perf 4 holes @ surface. POH w/ tbg. NI	irectionally or recomplete horizonta in the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be day for final inspection.) R2W ment Operations: , 2010: MIRU well service unit. psig - OK. NDWH. NUBOP. Per and circulate 15 bbls water passainer and establish inj rate of 2 3 bbls water. Sting out of retain the gand set @ 2250'. Pack off the 325. RIH w/tbg and land @ 37 DBOP. Rig down and move out.	ally, give subsurface locate wide the Bond No. on file on results in a multiple corpe filed only after all requires. Install weight indica OOH w/ 2 3/8" tbg. R st retainer. Set retaine 2 BPM at 560 psig thriner w/ 179 psig in tbg. tbg and cement dn tbg 73'. Mix and pump 17 t.	tions and measured and the with BLM/BIA. Require a pletion or recompletion irements, including reclar and the w/4 1/2" squeeze rerand shear off. Pumpough perfs @ 3805'-38 t. Left 5 sx cmt to fall or sw/50 sx cement @ 1 1	de vertical depthed subsequent rin a new intervaluation, have been declared downhole petainer. Assection of the mixed top of retait top of retait /2 BPM @ 50	ns of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once on completed, and the operator has rump. Lay down. Drop standing mbly on 113 jts 2 3/8" tbg and circulate up csg w/3 bbls as and squeeze perfs w/37 sx aer. POOH w/ tbg. RIH and po 10 psig. POOH w/tbg. Fill hole.	s. g
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea Guardian Federal #1 SE/4 SE/4 Sec 5-T25N-F Rio Arriba Co., NM Plugging and Abandonn July 23 through July 27, valve. Load tbg to 1000 land @ 3461'. Load tbg displaced. Sting into rete cement and displace w/ 4 holes @ 2200'. RIH w/ RIH and perf 4 holes @ surface. POH w/ tbg. NI	irectionally or recomplete horizonta in the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be day for final inspection.) R2W ment Operations: , 2010: MIRU well service unit. psig - OK. NDWH. NUBOP. Pe and circulate 15 bbls water pasainer and establish inj rate of 2 3 bbls water. Sting out of retain (tbg and set @ 2250'. Pack off t 325. RIH w/ tbg and land @ 37 DBOP. Rig down and move out.	ally, give subsurface locate wide the Bond No. on file on results in a multiple corpe filed only after all requires. Install weight indica OOH w/ 2 3/8" tbg. R st retainer. Set retaine 2 BPM at 560 psig thriner w/ 179 psig in tbg. tbg and cement dn tbg 73'. Mix and pump 17 t.	ions and measured and the with BLM/BIA. Require mpletion or recompletion irements, including reclamstor. POOH w/ rods amount and shear off. Pumpough perfs @ 3805'-38. Left 5 sx cmt to fall or yw/50 sx cement @ 1 10 sx cement dn tbg @	de vertical depthed subsequent rin a new intervaluation, have been declared downhole petainer. Assection of the mixed top of retait top of retait /2 BPM @ 50	ns of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once on completed, and the operator has rump. Lay down. Drop standing mbly on 113 jts 2 3/8" tbg and circulate up csg w/3 bbls as and squeeze perfs w/37 sx aer. POOH w/ tbg. RIH and po 10 psig. POOH w/tbg. Fill hole.	s.
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea Guardian Federal #1 SE/4 SE/4 Sec 5-T25N-F Rio Arriba Co., NM Plugging and Abandonn July 23 through July 27, valve. Load tbg to 1000 land @ 3461'. Load tbg displaced. Sting into rete cement and displace w/ 4 holes @ 2200'. RIH w/ RIH and perf 4 holes @ surface. POH w/ tbg. NI	irectionally or recomplete horizonta in the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be day for final inspection.) R2W ment Operations: , 2010: MIRU well service unit. psig - OK. NDWH. NUBOP. Pe and circulate 15 bbls water pasainer and establish inj rate of 2 3 bbls water. Sting out of retain (tbg and set @ 2250'. Pack off t 325. RIH w/ tbg and land @ 37 DBOP. Rig down and move out.	ally, give subsurface locat wide the Bond No. on file on results in a multiple corpe filed only after all requires. Install weight indica OOH w/ 2 3/8" tbg. R st retainer. Set retaine 2 BPM at 560 psig threner w/ 179 psig in tbg. tbg and cement dn tbg 73'. Mix and pump 17 t.	tor. POOH w/ rods and the with BLM/BIA. Require mpletion or recompletion in terments, including reclamator. POOH w/ rods and IH w/ 4 1/2" squeeze rear and shear off. Pumpough perfs @ 3805'-38. Left 5 sx cmt to fall or g. w/50 sx cement @ 1 1 0 sx cement dn tbg @	d downhole petainer. Assert dan top of retait. Then min top of retait. BPM @ 50 3 BPM @ 800	ns of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once on completed, and the operator has rump. Lay down. Drop standing mbly on 113 jts 2 3/8" tbg and circulate up csg w/3 bbls as and squeeze perfs w/37 sx aer. POOH w/ tbg. RIH and po 10 psig. POOH w/tbg. Fill hole.	s. g
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea Guardian Federal #1 SE/4 SE/4 Sec 5-T25N-F Rio Arriba Co., NM Plugging and Abandonn July 23 through July 27, valve. Load tbg to 1000 land @ 3461'. Load tbg displaced. Sting into rete cement and displace w/ 4 holes @ 2200'. RIH w/ RIH and perf 4 holes @ surface. POH w/ tbg. NI	irectionally or recomplete horizonta in the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be day for final inspection.) R2W Interpret Operations: 1, 2010: MIRU well service unit. psig - OK. NDWH. NUBOP. Pound circulate 15 bbls water pasainer and establish inj rate of 2 3 bbls water. Sting out of retain (tbg and set @ 2250'. Pack off the 325. RIH w/tbg and land @ 37 DBOP. Rig down and move out. Interpret Operations: Inte	ally, give subsurface locat wide the Bond No. on file on results in a multiple corpe filed only after all requires. Install weight indica OOH w/ 2 3/8" tbg. R st retainer. Set retaine 2 BPM at 560 psig threner w/ 179 psig in tbg. tbg and cement dn tbg 73'. Mix and pump 17 t.	tor. POOH w/ rods and the with BLM/BIA. Require mpletion or recompletion in terments, including reclamator. POOH w/ rods and IH w/ 4 1/2" squeeze rear and shear off. Pumpough perfs @ 3805'-38. Left 5 sx cmt to fall or g. w/50 sx cement @ 1 1 0 sx cement dn tbg @	d downhole p etainer. Assert du top of retain top of retain top of september 2 BPM @ 50 3 BPM @ 800	ns of all pertinent markers and zone: reports shall be filed within 30 days al, a Form 3160-4 shall be filed once on completed, and the operator has rump. Lay down. Drop standing mbly on 113 jts 2 3/8" tbg and circulate up csg w/3 bbls as and squeeze perfs w/37 sx aer. POOH w/ tbg. RIH and po 10 psig. POOH w/tbg. Fill hole.	s. g

(Instructions on page 2)



OCT 0 4 2010



GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this

form and the number of copies to be submitted, particularly with regard to local area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13 - Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or

present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well and date well site conditioned for final inspection looking to approval of the abandonment.

NOTICE

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

This information is being collected to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT

Public reporting burden for this form is estimated to average 25 minutes per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer, (WO-630), Mail Stop 401 LS, 1849 C St., N.W., Washington D.C. 20240