## CEIVED

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCT 18 2010

	∠urea	rmington Field Office au of Land Management
	5.	Lease Number
(F a C XV/a1)		I-149-IND-8473
Type of Well GAS	6.	If Indian, All. or Tribe Name
		NAVAJO
	7.	Unit Agreement Name
Name of Operator		HUERFANITO UNIT
BURLINGTON		
RESCURCES OIL & GAS COMPANY LP		
· · · · · · · · · · · · · · · · · · ·	- 8.	Well Name & Number
Address & Phone No. of Operator		<b>HUERFANITO UNIT 93S</b>
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	API Well No.
	-	20.045.24590
Location of Well, Footage, Sec., T, R, M		30-045-34780
, · · · · · · · · · · · · · · · · ·	10.	Field and Pool
Surface: Unit K (NE/SW), 1495' FSL & 1510' FWL, Section 25, T27N, R9W, NMPM		BASIN FRUITLAND COA
	11.	County and State
		San Juan, NM
Casing Repair Water Shut off		OIL CONS. DIV.
Final Abandonment Altering Casing Conversion to Injection		DIST. 3
Altering Casing Conversion to injection  6. Describe Proposed or Completed Operations  6. Describe Proposed or Completed Operations  6. July 12/10 MIRU HP 283. NU BOPE. PT 7" csg to 600#/30min @ 20:00hrs on 10/12/10. Test - OK.  7/13/10 RIH w/ 6 1/4" bit. Tag & DO cmt @ 199'. Drilled to 2346' - TD reached 10/13/10. Circ. hole & R  7/13/10 Cacing set @ 2331'. RU to cmt. Pre-flushed w/ 10bbls FW, 10 bbls CW, 10 bbls FW. Pumped scave cmium Lite w/ 3% Caci, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Leadernium Lite w/ 3% Caci, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Tailment w/ 1% Caci, 0.25 pps celloflake, & 0,2% FL-52. Flushed pump & lines w/ 15bbls FW. Dropped play. Bump plug. Circ. 26bbls cmt to surface. Plug down @ 17:07hrs 10//14/10. WOC. ND BOPE. NU WF	enger w/ ad w/ 14; il w/ 45s;	Reuise 4jts, 4 1/2", 11#J-55, 9sx(27cf-5bbls) 3sx(305cf-54bbls) x(62cf-11bbls) Type III
6. Describe Proposed or Completed Operations  6/12/10 MIRU HP 283. NU BOPE. PT 7" csg to 600#/30min @ 20:00hrs on 10/12/10. Test - OK.  6/13/10 RIH w/ 6 1/4" bit. Tag & DO cmt @ 199'. Drilled to 2346' - TD reached 10/13/10. Circ. hole & R  7 C casing set @ 2331'. RU to cmt. Pre-flushed w/ 10bbls FW, 10 bbls CW, 10 bbls FW. Pumped scave cmium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Leadernium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Tailment w/ 1% CaCl, 0.25 pps celloflake, & 0,2% FL-52. Flushed pump & lines w/ 15bbls FW. Dropped play. Bump plug. Circ. 26bbls cmt to surface. Plug down @ 17:07hrs 10//14/10. WOC. ND BOPE. NU WF	enger w/ ad w/ 14; il w/ 45s;	Reuise 4jts, 4 1/2", 11#J-55, 9sx(27cf-5bbls) 3sx(305cf-54bbls) x(62cf-11bbls) Type III
6. Describe Proposed or Completed Operations  7/12/10 MIRU HP 283. NU BOPE. PT 7" csg to 600#/30min @ 20:00hrs on 10/12/10. Test - OK.  7/13/10 RIH w/ 6 1/4" bit. Tag & DO cmt @ 199'. Drilled to 2346' - TD reached 10/13/10. Circ. hole & RT&C casing set @ 2331'. RU to cmt. Pre-flushed w/ 10bbls FW, 10 bbls CW, 10 bbls FW. Pumped scave cmium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Leacmium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Taiment w/ 1% CaCl, 0.25 pps celloflake, & 0.2% FL-52. Flushed pump & lines w/ 15bbls FW. Dropped plv. Bump plug. Circ. 26bbls cmt to surface. Plug down @ 17:07hrs 10//14/10. WOC. ND BOPE. NU WF	enger w/ ad w/ 14; il w/ 45s;	Reuise 4jts, 4 1/2", 11#J-55, 9sx(27cf-5bbls) 3sx(305cf-54bbls) x(62cf-11bbls) Type III
6. Describe Proposed or Completed Operations  6/12/10 MIRU HP 283. NU BOPE. PT 7" csg to 600#/30min @ 20:00hrs on 10/12/10. Test - OK.  6/13/10 RIH w/ 6 1/4" bit. Tag & DO cmt @ 199'. Drilled to 2346' - TD reached 10/13/10. Circ. hole & R  7 C casing set @ 2331'. RU to cmt. Pre-flushed w/ 10bbls FW, 10 bbls CW, 10 bbls FW. Pumped scave cmium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Leadernium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Tailment w/ 1% CaCl, 0.25 pps celloflake, & 0,2% FL-52. Flushed pump & lines w/ 15bbls FW. Dropped play. Bump plug. Circ. 26bbls cmt to surface. Plug down @ 17:07hrs 10//14/10. WOC. ND BOPE. NU WF	enger w/ ad w/ 14; il w/ 45s; ug & dis H. RD RI	Revise 4jts, 4 1/2", 11#J-55, 9sx(27cf-5bbls) 3sx(305cf-54bbls) k(62cf-11bbls) Type III placed w/ 36bbls R @ 23:00hrs on 10/14/10
6. Describe Proposed or Completed Operations  7/12/10 MIRU HP 283. NU BOPE. PT 7" csg to 600#/30min @ 20:00hrs on 10/12/10. Test - OK.  7/13/10 RIH w/ 6 1/4" bit. Tag & DO cmt @ 199'. Drilled to 2346' - TD reached 10/13/10. Circ. hole & R T&C casing set @ 2331'. RU to cmt. Pre-flushed w/ 10bbls FW, 10 bbls CW, 10 bbls FW. Pumped scave cmium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Leacmium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Taiment w/ 1% CaCl, 0.25 pps celloflake, & 0.2% FL-52. Flushed pump & lines w/ 15bbls FW. Dropped play. Bump plug. Circ. 26bbls cmt to surface. Plug down @ 17:07hrs 10//14/10. WOC. ND BOPE. NU WF	enger w/ ad w/ 14; il w/ 45s; ug & dis, H. RD RI	Revise 4jts, 4 1/2", 11#J-55, 9sx(27cf-5bbls) 3sx(305cf-54bbls) k(62cf-11bbls) Type III placed w/ 36bbls R @ 23:00hrs on 10/14/10
6. Describe Proposed or Completed Operations  1/12/10 MIRU HP 283. NU BOPE. PT 7" csg to 600#/30min @ 20:00hrs on 10/12/10. Test - OK.  1/13/10 RIH w/ 6 1/4" bit. Tag & DO cmt @ 199'. Drilled to 2346' - TD reached 10/13/10. Circ. hole & R T&C casing set @ 2331'. RU to cmt. Pre-flushed w/ 10bbls FW, 10 bbls CW, 10 bbls FW. Pumped scave cmium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Lead cmium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 0.4% SMS & 8% bentonite. Tailment w/ 1% CaCl, 0.25 pps celloflake, & 0.2% FL-52. Flushed pump & lines w/ 15bbls FW. Dropped play. Bump plug. Circ. 26bbls cmt to surface. Plug down @ 17:07hrs 10//14/10. WOC. ND BOPE. NU WF.  T will be conducted by Completion Rig. Results & TOC will appear on next report.  1. I hereby certify that the foregoing is true and correct.  2. Marie E. Jaramillo  3. Title: Staff Regulation of Federal or State Office use)	enger w/ ad w/ 14; il w/ 45s; ug & dis, H. RD RI	4jts, 4 1/2", (11#) 1-55, 9sx(27cf-5bbls) 3sx(305cf-54bbls) x(62cf-11bbls) Type III placed w/ 36bbls R @ 23:00hrs on 10/14/10  Technician Date 10/18/10

OCT 2 5 2010
FARMINGTON FIELD OFFICE
BY TL SOLVETS

