State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Liner type: Thickness ____

<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
<u>District II</u>
1301 W. Grand Avenue, Artesia, NM 88210
<u>District III</u>
1000 Rio Brazos Road, Aztec, NM 87410
<u>District IV</u>
1220 S. St. Francis Dr., Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.
For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

7269		d-Loop System, Below-Grade ive Method Permit or Closure				
	Closure of a Modification	*				
Instructio	ons: Please submit one application (F	orm C-144) per individual pit, closed-loop sy	stem, below-grade tank or alternative request			
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.						
Operator:	DJ Simmons, Inc	OGRID#	005578			
-		Farmington, NM 87410				
		OCD Permit Number:	· ·			
		Township24N Range				
i			-107.658711 NAD: ☐1927 ☑ 1983			
	☐ Federal ☐ State ☐ Private ☒ Triba					
2.			RCVD NOV 12'10			
1	ion F or G of 19.15.17.11 NMAC					
	Orilling Workover	-	OIL COMS. DIV.			
Permanent Emergency Cavitation P&A						
Lined Unlined Liner type: Thicknessmil						
String-Reinfor	· ·	V. I				
Liner Seams:	welded Factory Other	Volume: Dimensi	ions in Feet:			
3.	Systems Subsection U of 10 15 17 11	NMAC				
☑ Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: ☐ P&A ☑ Drilling a new well ☐ Workover or Drilling (Applies to activities which require prior approval of a permit or notice of						
intent) ☐ Drying Pad ☐ Above Ground Steel Tanks ☐ Haul-off Bins ☐ Other						
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other						
Liner Seams: Welded Factory Other						
4. Below-grade	tank: Subsection I of 19.15.17.11 N	MAC				
Tank Construction material:						
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off						
i —	☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other					

mil HDPE PVC Other

5. Alternative Method:	
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration	on of approval.
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify	hospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)	
8. Signs: Subsection C of 19.15.17.11 NMAC ☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers ☐ Signed in compliance with 19.15.3.103 NMAC	
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	office for
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the approoffice or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of a Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to dry above-grade tanks associated with a closed-loop system.	priate district pproval.
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☐ NA
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 500 feet of a wetland.	│ │

- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site					
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No				
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No				
Within a 100-year floodplain FEMA map	☐ Yes ☐ No				
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC					
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 and 19.15.17.13 NMAC	.15.17.9 NMAC				
Previously Approved Design (attach copy of design) API Number: or Permit Number:					
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19. Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NM Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 1 and 19.15.17.13 NMAC	15.17.9 (AC				
Previously Approved Design (attach copy of design) API Number: 3004535019					
Previously Approved Operating and Maintenance Plan API Number: 3003922256 (Applies only to closed-loop system that use ab tanks or haul-off bins and propose to implement waste removal for closure)	ove ground steel				
tunks of fluid-off this and propose to implement waste removal for closure)					
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Contified Engineering Design Please, based upon the appropriate requirements of 19.15.17.11 NMAC	cuments are				
 □ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC □ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC □ Quality Control/Quality Assurance Construction and Installation Plan □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Nuisance or Hazardous Odors, including H₂S, Prevention Plan 					
 ☐ Emergency Response Plan ☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan ☐ Erosion Control Plan ☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC 					

Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.				
Type: ☑ Drilling ☐ Workover ☐ Emergency ☐ Cavitation ☐ P&A ☐ Permanent Pit ☐ Below-grade Tank ☒ Closed-loop ☐ Alternative	System			
Proposed Closure Method: Waste Excavation and Removal				
✓ Waste Removal (Closed-loop systems only)✓ On-site Closure Method (Only for temporary pits and closed-loop systems)				
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for c	onsideration)			
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be colorure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	attached to the			
16,				
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.1 Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if a facilities are required.				
Disposal Facility Name: <u>Basin Disposal</u> Disposal Facility Permit Number: <u>NM-01-005</u>				
Disposal Facility Name: Disposal Facility Permit Number:				
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that <i>will not</i> be used for future serviced in Yes (If yes, please provide the information below) ☑ No	vice and operations?			
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specifications based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	С			
17. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC				
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate distriction considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justi demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.	rict office or may be			
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA			
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA			
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No			
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No			

adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality					
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	☐ Yes ☐ No				
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No				
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No				
Within a 100-year floodplain FEMA map	☐ Yes ☐ No				
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC					
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.					
Name (Print): Steve Sacks Title: Regulatory and Permitting Specialist Date: /////2010					
e-mail address: ssacks@djsimmons.com Telephone: 505-326-3753 Ext 127	W. CO				
OCD Approval: ☐ Permit Application (including closure plan) ☐ Closure Plan (only) ☐ OCD Conditions (see attachment) OCD Representative Signature: ☐ Approval Date:	/10				
Title: OCD Permit Number:					
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:					
Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-le If different from approved plan, please explain.	oop systems only)				
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-o Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attatwo facilities were utilized.					

Attachment A Design, Operation, and Closure Plans

In accordance with 19.15.17 NMAC the following information describes the design, operation and closure requirements for a closed loop system on DJ Simmons, Inc locations, hereinafter known as DJ Simmons locations, in the San Juan Basin of New Mexico. This is DJ Simmons's standard procedure for all closed loop systems. A separate plan would be submitted and utilized for any closed loop system which does not conform to this plan.

Design, Construction, and Operation

- ➤ DJ Simmons shall follow all of the design and operation guidelines and stipulations outlined below and contained in their entirety within 19.15.17.9 NMAC Subsections A, B, and B (3).
- ➤ The above ground steel tank and haul off bin will be designed and constructed to contain liquids and solids and prevent contamination of fresh water and protect public health and environment. The capacity of the steel tank is approximately 180 barrels and the approximate capacity of the haul off bin is 120 barrels.
- The above ground steel tank will be set on the existing well pad. There will be no dirt work required for the work-over process.

Closure Requirements

- ➤ DJ Simmons shall abide by the closure requirements outlined below and contained in NMAC 19.15.17.13 D (1)
- ➤ DJ Simmons shall remove the waste by transferring the waste to a division approved facility, NMAC 19.15.17.13 D (1) (a).
- ➤ DJ Simmons shall substantially restore and re-vegetate the impacted area's surface NMAC 19.15.17.13 (1) (b) and in accordance with NMAC 19.15.17.13 I (1) (2) (3) and (5). An approved BLM/BIA seed mix and application rates will be used for reseeding.
- Notice of Closure will be given to the Aztec Division office between 72 hours and 7 days (one Week) of the closure via e-email, or verbally. The notification of closure will include the following:
 - o Operator's name (DJ Simmons)
 - o Well Name and API Number
 - o Location (USTR)
- > All closure activities will include proper documentation and be available for review per request and will be submitted to OCD within 60 days of closure or

removal of the above ground steel tank and haul off bin. The closure report will be filed on a C-144 form.