This form is not to be sused for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

			Lease	Name SAN	JUAN 28-7 UN	<u> </u>	Well No52
ocation of We	ili: Unit I	_etter H S	ec <u>27</u>	Twp028N	Rge	007W API	# 30-039-07315
	N	ame of Reservoir or Poo	1	Type of Prod		Method of Prod	Prod Medium
Upper Completion	PC		Gas	Gas			Tubing
Lower Completion	MV		Gas	Gas		al Lift	Tubing
			Pre-Flow S	hut-in Pressu	ire Data		
Upper	Hour, Da	te, Shut-In	Length o	Length of Time Shut-In		s. PSIG	Stabilized?(Yes or No)
Completion	8/1	9/2010	178 h	178 hours		144	Yes
Lower	Hour, Date, Shut-In		1	Length of Time Shot-In		s. PSIG	Stabilized?(Yes or No)
Completion	8/19/2010			105 hours		184	Yes
			Flo	w Test No. 1			
Commenced	at: 8/23	3/2010 9:25:00 AM		Zone Pro	oducing (Upper	or Lower): LC	WER
Time		Lapsed Time	PRESSURE Pr		Prod Zone		
(date/time	e)	Since*	Upper zone	Lowerzone	Temperature	Remarks	
8/24/2010 8:30:00 AM		23	144	184	 	Both zones shut in, opened MV.	
8/25/2010 9:54:31 AM		48	146	78		upper zone is shut it. MV is flowing.	
8/26/2010 10:39:05 AM		73 -	144	88		opened lower zor	ne. MV
roduction rate	e during t	est					
il:BPOD Based on:		Bbls. In	Bbls. In Hrs.		Grav.	GOR	
as		MCFPD; Test th	nru (Orifice or M	eter)			
			Mid-Yest C	hetin Besse	uca Data		
Upper Completion	Hour, Date, Shut-In			Mid-Test Shut-In Pressur Length of Time Shut-In		s. PSIG	Stabilized?(Yes or No)
Lower	1		Length of Time Shut-In		SI Press. PSIG		Stabilized?(Yes or No)

M_



Flow Test No. 2

Commenced a	t:	Zone Producing (Upper or Lower)					
Time	Lapsed Time	PRESSURE		Prod Zone			
(date/time) Since*	Upper zone	Lower zone	Temperature	Remarks		
			<u>-</u>	'	Marie - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		
			i 				
The same of the sa							
		<u> </u>					
	uction rate during testBPOD Based on:		Hrs.	Gra	vGOR		
as	MCFPD; Test t	nru (Orifice or M	eter)				
Remarks:							
hereby certify t	that the information herein o	contained is true	and complete	to the best of my	knowledge.		
hereby certify t				to the best of my	knowledge.		
Approved:	Oil Conservation Division		Operat	•	_		
New Mexico	9-10		Operat By:	or: COP			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven d is after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shatt-in. Such test shall be continued for soven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time basevals as follows: 2 hours tests; immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required appreciated the pressure some properties.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Picker Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).