RCW ALC 25'10

NEW MEXICO OIL CONSERVATION DIVISION Revised June 10, 2003 NORTHWEST NEW MEXICO PACKER LEAKAGE TEST Well 19N DEVON ENERGY Lease Name Operator 3003930216 7W API # 30-0 30N Rge Location Of Well: Unit Letter Name of Reservoir or Pool Type of Prod. Method of Prod. Prod. Medium (Oil or Gas) (Flow or Art. Lift) (Tbg. Or Csg.) FLOW CASING PICTURED CLIFFS GAS Upper Completion GAS ARTIFICIAL LIFT TUBING DAKOTA Lower Completion Pre-Flow Shut-In Pressure Data Length of Time Shut-In Stabilized? (Yes or No) Hour, Date,Shut-In SI Press. Psig Upper 1:00pm 8/6/2010 not capable of production YES Completion Hour, Date, Shut-In Length of Time Shut-In SI Press, Psig Stabilized? (Yes or No) Lower Completion 1:00pm 8/6/2010 289 hours Flow Test No. 1 Commenced at (hour, date)\* 2:00pm 8/18/2010 Zone Producing (Upper or Lower): lower Remarks Time Lasped Time Prod. Zone (Hour, Date) Since\* Upper Compl. Lower Compl. 2:00pm 8/18/2010 847 turned zone to production. 2:10pm 8/19/2010 11 produced 250 mef will not get below line pressure 24 110 1:55pm /8/20/2010 72 11 118 produced 228 mcf will not get below line pressure 2:17pm 8/21/2010 96 11 12Í produced 156 mef will not get below line pressure 2:07pm 8/22/2010 120 11 116 produced 133 mef will not get below line pressure Production Rate During Test Oil: BOPD based on Bbls. In Hrs. MCFPD; Test thru (Orifice of Meter): Gas: Mid-Test Shut-In Pressure Data

(Continue on reverse side)

SI Press. Psig

SI Press. Psig

Stabilized? (Yes or NO)

Stabilized? (Yes or NO)

K

Length of Time Shut-In

Length of Time Shut-In

Upper

Completion Lower

Completion

Hour, Date, Shut-In

Hour, Date, Shut-In

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Flow Test No. 2

Commenced a	t (hour, date)*		Zone Pro	ducing (Upper or I	ower):		]
Time	Lasped Time	Pressure		Prod. Zone	Remarks		
(Hour, Date)	Since*	Upper Compl.	Lower Compl.	Temp.	<del> </del>		-
							_
<u> </u>							-
Production R	ate During Test	<u></u>					
Oil:	BOPD base	ed on	Bbls. In	Hrs.	Grav	GOR	_
Gas:		MCFPD; Test thru	(Orifice or Meter):				-
. A /	7298						
- Velice	9-10-10						
I hereby certif	y that the information	herein contained is tr	ue and complete to	the best of my kno	wledge.		
Appoved New Mexico O	oil Conservation Divisio		20	<u>/</u> o <sub>p</sub>	erator	DEVON ENERGY	~
		7			í		
By _	Deputy (	Sil & Gas In	spector,	Title	Leas	se Operator John. Todd Od	
Title _		District #3		E-mail	Address	John. lodd Od	W.Com
				Date	8-3	24-2010	~

## Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).