

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

JAN 06 2011

Sundry Notices and Reports on Wells

Farmington Field Office
Bureau of Land Management1. Type of Well
GAS5. Lease Number
SF-078500-A6. If Indian, All. or
Tribe Name

2. Name of Operator

7. Unit Agreement Name
SAN JUAN 28-7 UNIT

ConocoPhillips

3. Address & Phone No. of Operator

8. Well Name & Number
SAN JUAN 28-7 UNIT 243P

PO Box 4289, Farmington, NM 87499 (505) 326-9700

9. API Well No.

4. Location of Well, Footage, Sec., T, R, M

30-039-30887

Surface: Unit N (SE/SW), 915' FSL & 1887' FWL, Section 31, T28N, R7W, NMPM
Bottomhole: Unit O (SW/SE), 915' FSL & 2400' FEL, Section 31, T28N, R7W, NMPM10. Field and Pool
BLANCO MV / BASIN DK11. County and State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other -- Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction

RCVD JAN 10 '11

☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing

OIL CONS. DIV.

☐ Casing Repair☐ Water Shut off

DIST. 3

☐ Altering Casing☐ Conversion to Injection

13. Describe Proposed or Completed Operations

12/17/10 MIRU AWS 673. NU BOPE. PT csg to 600#/30min @ 06:00hrs on 12/18/10. Test - OK.

PU & TIH w/ 8 3/4" bit. Tag & DO cmt to 351'. Drilled to 3366' - Inter TD reached 12/21/10. Circ. hole & RIH w/ 80jts, 2", 23# J-55 LT & C csg set @ 3359' w/ ST @ 2199'. 1st Stage - Pre-flushed w/ 10 bbls GW, 2 bbls FW. Pumped scavenger w/ 19sx(57cf-10bbls) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 86sx(183cf-33bbls) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Tail w/ 80sx(110cf-20bbls) Type III cement w/ 1% CaCl, .025 pps celloflake, & 0.2% FL-52. Dropped plug & displaced w/ 60bbls FW & 71bbls MW. Bumped plug. Plug down @ 22:24hrs 12/22/10. Open ST & Circ. 28bbls cmt to surface. WOC. 2nd Stage - Pre-flush w/ 10 bbls FW, 10bbls GW, 10bbls FW. Pumped scavenger w/ 19sx(57cf-10bbls) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 262sx(558cf-99bbls) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Displaced w/ 87bbls of FW. Bumped plug & close ST. Circ. 41bbls cmt to surface. Plug down @ 04:01hrs on 12/22/10. RD cmt. WOC.

12/23/10 Shut dwn for Holiday.

12/26/10 TIH w/ 6 1/4" bit. Drill out ST @ 2199'. PT 4 1/2" csg to 1500#/30min @ 19:00hrs on 12/26/10. Test - OK. Drilled w/ 6 1/4" bit reached TD @ 7326' on 12/28/10. Circ. hole & RIH w/ 170jts, 4 1/2", 11.6#, L-80 LT & C csg set @ 7321'. RU to cmt. Pre-flushed w/ 10bbls GW & 2bbls FW. Pumped scavenger 9sx(28cf-5bbls) Premium lite HS FM, 0.25pps celloflake, 0.3% CD-32, 6.25pps LCM-1, & 1% FL-52. Tail w/ 285sx(564cf-100bbls) Premium lite HS FM, 0.25 pps celloflake, 0.3% CD-32, 6.25pps LCM-1 & 1% FL-52. Dropped plug & displaced w/ 114bbls FW. Bumped plug. Plug down @ 16:20hrs on 12/30/10. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 22:30hrs on 12/30/10. PT will be conducted by Completion Rig. Results & TOC will appear on next report.

ACCEPTED FOR RECORD

JAN 07 2011

14. I hereby certify that the foregoing is true and correct.

Signed

Marie E. Jaramillo

Title

Staff Regulatory Technician

Date 01/04/11

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any statement or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within jurisdiction.