Form 3160-5 (August 2087)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side. 1. Type of Well Oil Well Gas Well Other					5. Lease Serial No. NMNM010063 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or NNMNM74063 8. Well Name and No. GENTLE 3								
							Name of Operator DUGAN PRODUCTION CC	JOHN C ALEXANDER under@duganproduction.com			9. API Well No. 30-045-20786-00-S1		
							3a. Address		3b. Phone No. (include area code) Ph: 505-325-1821		e)	10. Field and Pool, or Exploratory N PINON FRUITLAND SAND	
							FARMINGTON, NM 87499		111. 300-023-1021			THE INCIDENCE OF THE	
							4. Location of Well (Footage, Sec)			11. County or Parish, and State		
							Sec 8 T28N R11W SESE 0 36.67171 N Lat, 108.02040				SAN JUAN COUNTY, NM		
12. CHECK AP	PROPRIATE BOX(ES) TO	O INDICAT	E NATURE OF 1	NOTICE, RE	PORT, OR OTHER	R DATA							
TYPE OF SUBMISSION		TYPE OF ACTION											
NI-4:	☐ Acidize	☐ Deepen		☐ Producti	ction (Start/Resume) Water Shut-Off								
Notice of Intent		Fracture Treat		□ Reclama	_								
☐ Subsequent Report	Casing Repair	□ Ne	☐ New Construction		plete Other								
☐ Final Abandonment Notice ☐ Change Plans		Plug and Abandon		☐ Tempora	rily Abandon								
Convert to Injecti		Plug Back Wate		□ Water D	Disposal								
If the proposal is to deepen directic Attach the Bond under which the violeting has been completed. Final determined that the site is ready for Plan to plug well as follow: Set CIBP at 1630' (Pictured Spot Type V cement inside of Perforate 482' (Ojo Alamo 3). Pump cement to circulate to	work will be performed or provide red operations. If the operation re Abandonment Notices shall be fil r final inspection.) Cliffs 1580') Casing to fill to 1208' (Fruitla 82')	the Bond No. c sults in a multip ed only after all	on file with BLM/BIA ble completion or reco	A. Required subsompletion in a ne	sequent reports shall be ew interval, a Form 316	filed within 30 days 0-4 shall be filed once and the operator has							
Set dry hole monument	·			OIL CONS. DIV.									
•	Notify NMOCD 24 hrs			lik tilikul katu									
			prior to beginning operations										
١													
14. I hereby certify that the foregoing	is true and correct. Electronic Submission #1 For DUGAN PRODUC ommitted to AFMSS for proce	CTION CORPO	PRATION, sent to	the Farmingto	ว์ท								
Name (Printed/Typed) JOHN C				RESIDENT									
Signature (Electronic	Submission)		Date 12/30/20	010									
	THIS SPACE FO	R FEDERA	AL OR STATE	OFFICE US	E								
Approved By STEPHEN MASON		TitlePETROLE	JM ENGINEE	1 ENGINEER Date 01/0									

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Farmington

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT FARMINGTON DISTRICT OFFICE

1235 LA PLATA HIGHWAY FARMINGTON, NEW MEXICO 87401

Attachment to notice of Intention to Abandon:

Re: Permanent Abandonment

Well: 3 Gentle

CONDITIONS OF APPROVAL

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
- 2. Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907.
- 3. The following modifications to your plugging program are to be made:
- a) Place the Kirtland/Ojo Alamo plug from 561' to surface inside and if there is no cement outside the 5 ½" casing.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.