Form 3160-5 (August 2003)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0137 Expires July 31, 2010

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

SUNDRY NOTICES AND REPORTS ON WELLS				JIC CONT. 96		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or Tribe Name Jicarilla Apache	
					A/Agreement, Name and/or No.	
1. Type of Well Oil Well X Gas Well Other		FEB 03 2011		8. Well Name Jicarilla		
Name of Operator ENERGEN RESOURCES CORPORATION 3a. Address		Farmington Field Office Bureau of Land Management 3b. Phone No. (include area code)		9. API Well No. 30-039-21238		
2010 Afton Place, Farmington, NM 87 4. Location of Well (Footage, Sec., T., R., M., or Survey D 1190' FNL, 790' FWL, Sec. 11, T26N,	Description)				Pool, or Exploratory Area	
				11. County of Rio Arriba	a NM	
12. CHECK APPROPRIATE TYPE OF SUBMISSION	E BOX(ES) TO INI		PE OF ACTION	RT, OR OTHI	ER DATA	
X Notice of Intent Subsequent Report Final Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Fracture Treat New Construction Plug and Abandon Plug Back	Reclamation Recomple	te ly Abandon	Water Shut-Off Well Integrity X Other PC PayAdd and Downhole Commingle	
13. Describe Proposed or Completed Operation (clearly If the proposal is to deepen directionally or recomple Attach the Bond under which the work will be perfollowing completion of the involved operations. If testing has been completed. Final Abandonnent Number of the testing has been completed.	ete horizontally, give s formed or provide the I the operation results in otices shall be filed on	ubsurface locations and meas Bond No. on file with BLM/I	sured and true ve BIA. Required s	rtical depths of a	Ill pertinent markers and zones. Its shall be filed within 30 days	

determined that the final site is ready for final inspection.)

Energen Resources plans to add the PC to the Jicarilla 96 #5A as per the attached procedure.

This is to be completed and commingled per the approved order #R-13347.

Name (Printed/I	that the foregoing is true and correct Syped) Cabrera	Title District Engine	er		
Signature		Date 02/01/11			
	THIS SPACE FOR FED	RAL OR STATE OFFICE USE			
Approved by	Original Signed: Stephen Mason	Title	Date FEB 0 1 2011		
the applicant holds lega	if any, are attached. Approval of this notice does not warrant or cert. I or equitable title to those rights in the subject lease which would conduct operations thereon.	that Office			

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Energen Resources Corp. Pay Add Schedule – Jicarilla 96 5A API# 30-039-21238 DP#3129230B AFE# SJ11-104

Location: 1190' FNL, 790' FWL, Section 11, T 26 N, R 03 W, Rio Arriba Co., N.M.

Field: Blanco Mesaverde Elevation: 7056' TD: 6000' PBTD: 5940' KB: 14'

Cemented:

Consultant:

Casing Record:	<u>Csg. Size</u> 8-5/8" 4-1/2"	Wt. & Grade 20# K-55 10.5# K-55 DV TOOL	319' 6000'	et <u>Ceme</u> 250 s 1 st 76. 2 nd 96	ks S 5 sks S	OC Surface urface
Formation Tops:	<u>:</u> Ojo Alamo Kirtland Fruitland		250' 450'	Lewis Cliffhouse Menefee	37	750'
	Picture		630'	Point Lookout	5′	768'

Logging Record: IEL, Neutron, Caliper, Density, GR

Existing Perforations MV: 5390',96,98,5400',02,13,15,16,18,21,28,38,40,45,46,48,50,60,62,64,66, -5468' w/22 holes

MV: 5531',33,35,37,39,41,49,64,66,68,70,5625',27,29,31,35,37,39,43,45,47,49,57,70,72,- 5674' w/26

MV:5744',46,48,50,52,54,56,58,60,62,68,70,72,74,76,78,80,84,89,91,93,95,97,99,5802',04,06,08,10,12,14 ,16,18,20,22,26,28,30,32,34,36,38,-5840' w/43 holes

Recommended Completion Procedure:

- 1. MIRU WSU NUBOP. POOH production tubing.
- 2. TIH W/ RBP and set right below PC formation. Load the casing with clean 2% KCL W/ Biocide. Pressure Test Casing to desired specifications (80% yield press). Note: A packer may be required to isolate the wellhead from pressure. NU Frac Head/Valve assembly.
- 3. MIRU WL. TIH & perforate the PC formation per the selected interval.

Perforate Pictured Cliffs: 3690'-3734'

- 4. Pump the Breakdown schedule per the attached Halliburton procedure.
- 5. Fracture the PC per the attached Halliburton procedure. Note: The Max treating pressure will be 80% yield press. Maximum rate to be limited to 30 BPM (total rate) to ensure we stay within our target zone. Will frac w/ 20/40 sand.

- 6. TIH w/ tubing and POOH w/ RBP.
- 7. Cleanout to PBTD w/ air mist, TOH TIH w/ Prod. Tubing and land tubing.
- 8. NDBOP NUWH RDMO WSU. Turn the well over to production.