District I 1625 N. French Dr., Hobbs, NM 88240

District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico Energy Minerals and Natural Resources

> Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the

<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 8	37505	appropriate NMOCD District Office.	
0(11011	Pit, Closed-Loop System	, Below-Grade Tank, or	
UMUM P	roposed Alternative Method I	Permit or Closure Plan Application	
Type of action	on: Permit of a pit, closed-loop sys	tem, below-grade tank, or proposed alternative method	
	X Closure of a pit, closed-loop sy	stem, below-grade tank, or proposed alternative method	
	Modification to an existing per	mit	
		r an existing permitted or non-permitted pit, closed-loop s	system,
Instructions: Places submit	below-grade tank, or proposed	atternative method dual pit, closed-loop system, below-grade tank or alterna	rtina pagragt
		that pit, crosea-toop system, below-grade tank or atternations bility should operations result in pollution of surface water, ground water or the	=
		with any other applicable governmental authority's rules, regulations or ordinar	
Operator: ConocoPhillips Con	nnanv	OGRID#: 217817	
Address: P.O. Box 4289, Fari			
Facility or well name: MUDG			
API Number:	30-045-33271	OCD Permit Number:	
U/L or Qtr/Qtr: E(SW/NW)	Section: 30 Township: 26N	Range: 11W County: San Juan	
Center of Proposed Design: La	titude: 36.45988 °N	Longitude: 108.05141 °W NAD: 1	927 <b>X</b> 1983
Surface Owner: Feder	al State Private XT	ribal Trust or Indian Allotment	
Temporary: X Drilling Permanent Emergency X Lined Unlined X String-Reinforced Liner Seams: X Welded X	Liner type: Thickness 12 mil	X LLDPE HDPE PVC Other  Volume: 4400 bbl Dimensions L 65' x W 45'	x D 10'
Type of Operation: P&A	ubsection H of 19.15.17.11 NMAC  Drilling a new well Workover o notice of int e Ground Steel Tanks Haul-off Bins Liner type: Thickness mil  Factory Other	Other  LLDPE HDPE PVD Other	324252622
Below-grade tank: Subset Volume:  Tank Construction material:  Secondary containment with be Visible sidewalls and liner Liner Type: Thickness		er, 6-inch lift and automatic overflow shut-off	ONS. DIV. DIST. 3
5 Alternative Method: Submittal of an exception request	t is required. Exceptions must be submitted to	the Santa Fe Environmental Bureau office for consideration of a	

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institt  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify	ution or church	)
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)		
Signs: Subsection C of 19.15.17.11 NMAC  12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  X Signed in compliance with 19.15.3.103 NMAC		
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration (Fencing/BGT Liner)  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	deration of app:	roval.
Siting Criteria (regarding permitting) 19.15.17.10 NMAC  Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	□No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes	∐No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	NA	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applied to permanent pits)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes NA	No
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes	No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	No
Within a 100-year floodplain - FEMA map	Yes	No

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API or Permit
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9  NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design)  API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Climatological Factors Assessment
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
Emergency Response Plan
Oil Field Waste Stream Characterization
Monitoring and Inspection Plan
Erosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System  Alternative
Proposed Closure Method: Waste Excavation and Removal
Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place Burial On-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.
Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

Form C-144 Oil Conservation Division Page 3 of 5

16		
Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Ste Instructions: Please identify the facility or facilities for the disposal of liquids, drilling facilities are required.	el Tanks or Haul-off Bins Only:(19.15.17.13.D NMAC) fluids and drill cuttings. Use attachment if more than two	
	Disposal Facility Permit #:	
	Disposal Facility Permit #:	
Will any of the proposed closed-loop system operations and associated activity Yes (If yes, please provide the information No		
Required for impacted areas which will not be used for future service and operations:  Soil Backfill and Cover Design Specification - based upon the appropriate Re-vegetation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Plan - based upon the ap	riate requirements of Subsection H of 19.15.17.13 NP tion I of 19.15.17.13 NMAC	MAC
Siting Criteria (Regarding on-site closure methods only: 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recertain siting criteria may require administrative approval from the appropriate district office or office for consideration of approval. Justifications and/or demonstrations of equivalency are required.	commendations of acceptable source material are provided below. may be considered an exception which must be submitted to the Sa	
Ground water is less than 50 feet below the bottom of the buried waste.		Yes No
- NM Office of the State Engineer - iWATERS database search; USGS: Data obt	ained from nearby wells	∐N/A
Ground water is between 50 and 100 feet below the bottom of the buried was	<b>;</b>	Yes No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obta	ined from nearby wells	∐N/A
Ground water is more than 100 feet below the bottom of the buried waste.		Yes No
<ul> <li>NM Office of the State Engineer - iWATERS database search; USGS; Data obta</li> </ul>	ined from nearby wells	∐N/A
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other signific (measured from the ordinary high-water mark).	cant watercourse or lakebed, sinkhole, or playa lake	Yes No
- Topographic map; Visual inspection (certification) of the proposed site		
Within 300 feet from a permanent residence, school, hospital, institution, or church in - Visual inspection (certification) of the proposed site; Aerial photo; satellite image		Yes No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less that purposes, or within 1000 horizontal fee of any other fresh water well or spring, in exist - NM Office of the State Engineer - iWATERS database; Visual inspection (certification)	tence at the time of the initial application.	YesNo
Within incorporated municipal boundaries or within a defined municipal fresh water we pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obt		Yes No
Within 500 feet of a wetland		Yes No
<ul> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual insp</li> <li>Within the area overlying a subsurface mine.</li> </ul>	ection (certification) of the proposed site	Yes No
- Written confiramtion or verification or map from the NM EMNRD-Mining and N	4ineral Division	m., m.,
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & M Topographic map	ineral Resources; USGS; NM Geological Society;	YesNo
Within a 100-year floodplain FEMA map		Yes No
18 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each by a check mark in the box, that the documents are attached.	of the following items must bee attached to the clos	ure plan. Please indicate,
Siting Criteria Compliance Demonstrations - based upon the appropria	ate requirements of 19.15.17.10 NMAC	
Proof of Surface Owner Notice - based upon the appropriate requirem	ents of Subsection F of 19.15.17.13 NMAC	
Construction/Design Plan of Burial Trench (if applicable) based upon	the appropriate requirements of 19.15.17.11 NMAC	
Construction/Design Plan of Temporary Pit (for in place burial of a dr		of 19.15.17.11 NMAC
Protocols and Procedures - based upon the appropriate requirements o		
Confirmation Sampling Plan (if applicable) - based upon the appropria	•	AC
Waste Material Sampling Plan - based upon the appropriate requireme		
Disposal Facility Name and Permit Number (for liquids, drilling fluids Soil Cover Design - based upon the appropriate requirements of Subse	ection H of 19.15.17.13 NMAC	cannot be achieved)
Re-vegetation Plan - based upon the appropriate requirements of Subs		

Form C-144 Oil Conservation Division

Page 4 of 5

19 Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.  Name (Print):  Title:
Data
e-mail address: Telephone:
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature: Approval Date: Z/-7/11  Title: OCD Permit Number:
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.  X Closure Completion Date:  July 8, 2008
22 Closure Method:  Waste Excavation and Removal  The different from approved plan, please explain.  Alternative Closure Method  Waste Removal (Closed-loop systems only)
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:  Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.  Disposal Facility Name:  Disposal Facility Permit Number:  Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?  Yes (If yes, please demonstrate complilane to the items below)  Required for impacted areas which will not be used for future service and operations:  Site Reclamation (Photo Documentation)  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  X Proof of Closure Notice (surface owner and division) X Proof of Deed Notice (required for on-site closure) X Plot Plan (for on-site closures and temporary pits) X Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (if applicable) X Disposal Facility Name and Permit Number X Soil Backfilling and Cover Installation X Re-vegetation Application Rates and Seeding Technique X Site Reclamation (Photo Documentation) On-site Closure Location: Latitude: 36.4599444 °N Longitude: 108.051667 °W NAD 1927 X 1983
Operator Closure Certification:  I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print): Marie E. Jaramillo / Title: Staff Regulatory [Tech
Signature: Date: QUIO
e-mail address:

Form C-144

Oil Conservation Division

Page 5 of 5

# ConocoPhillips Company San Juan Basin Closure Report

Lease Name: MUDGE FEDERAL 1E

API No.: 30-045-33271

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure of the temporary pit referenced above. All proper documentation regarding closure activities is being included with the C-144. The temporary pit for this location was constructed and location drilled before June 16, 2008 (effective date for Rule 19.15.17). While closure of the temporary pit did fall within the rule some dates for submittals are after the rig release date.

- Details on Capping and Covering, where applicable. (See report)
- Plot Plan (Pit Diagram) (Included as an attachment)
- Inspection Reports (Included as an attachment)
- Sampling Results (Included as an attachment)
- C-105 (Included as an attachment)
- Copy of Deed Notice will be filed with County Clerk (Not required on Federal, State, or Tribal land as stated by FAQ dated October 30, 2008)

### **General Plan:**

1. All free standing liquids will be removed at the start of the pit closure process from the pit and disposed of in a division—approved facility or recycle, reuse or reclaim the liquids in a manner that the appropriate division district office approves.

All recovered liquids were disposed of at Basin Disposal (Permit #NM-01-005) and any sludge or soil required to be removed to facilitate closure was hauled to Envirotech Land Farm (Permit #NM-01-011) and JFJ Landfarm % IEI (Permit #NM-01-0010B).

2. The preferred method of closure for all temporary pits will be on-site burial, assuming that all the criteria listed in sub-section (B) of 19.15.17.13 are met.

The pit was closed using onsite burial.

3. The surface owner shall be notified of COPC's closing of the temporary pit as per the approved closure plan using certified mail, return receipt requested.

The closure process notification to the landowner was sent via email. (See Attached)(Well located on Federal Land, certified mail is not required for Federal Land per BLM/OCD MOU.)

4. Within 6 months of the Rig Off status occurring COPC will ensure that temporary pits are closed, re-contoured, and reseeded.

Provision 4 of the closure plan requirements were not met due to rig move off date as noted on C-105 which was prior to pit rule change. ConocoPhillips will ensure compliance with this rule in the future.

- 5. Notice of Closure will be given to the Aztec Division office between 72 hours and one week of closure via email, or verbally. The notification of closure will include the following:
  - i. Operator's name
  - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.

Notification is attached.

6. Liner of temporary pit shall be removed above "mud level" after stabilization. Removal of liner will consist of manually or mechanically cutting liner at mud level and removing all remaining liner. Care will be taken to remove "All" of the liner i.e., edges of liner entrenched or buried. All excessive liner will be disposed of at a licensed disposal facility.

Liner of temporary pit was removed above "mud level" after stabilization. Removal of the liner consisted of manually cutting liner at mud level and removing all remaining liner. Care was taken to remove "ALL" of the liner i.e., edges of liner entrenched or buried. All excessive liner was disposed of at a licensed disposal facility, (San Juan County Landfill).

7. Pit contents shall be mixed with non-waste containing, earthen material in order to achieve the solidification process. The solidification process will be accomplished using a combination of natural drying and mechanically mixing. Pit contents will be mixed with non-waste, earthen material to a consistency that is deemed a safe and stable. The mixing ratio shall not exceed 3 parts clean soil to 1 part pit contents.

ConocoPhillips mixed the Pit contents with non-waste containing, earthen material in order to achieve the solidification process. The solidification process was accomplished by using a combination of natural drying and mechanically mixing. Pit contents were mixed with non-waste, earthen material to a consistency that is deemed as safe and stable. The mixing ratio consisted of approximately 3 parts clean soil to 1 part pit contents.

8. A five point composite sample will be taken of the pit using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

A five point composite sample was taken of the pit using sampling tools and all samples tested per Subsection B of 19.15.17.1 3(B)(1)(b). (Sample results attached).

Tests Method	Limit (mg/Kg)	Results
EPA SW-846 8021B or 8260B	0.2	ND ug/kg
EPA SW-846 8021B or 8260B	50	ND ug/kG
EPA SW-846 418.1	2500	280mg/kg
EPA SW-846 8015M	500	27.3 mg/Kg
EPA 300.1	1000/500	877 mg/L
	EPA SW-846 8021B or 8260B EPA SW-846 8021B or 8260B EPA SW-846 418.1 EPA SW-846 8015M	EPA SW-846 8021B or 8260B       0.2         EPA SW-846 8021B or 8260B       50         EPA SW-846 418.1       2500         EPA SW-846 8015M       500

9. Upon completion of solidification and testing standards being passed, the pit area will be backfilled with compacted, non-waste containing, earthen material. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the background thickness of topsoil, whichever is greater. If standard testing fails BR will dig and haul all contents pursuant to 19.15.17.13.i.a. After doing such, confirmation sampling will be conducted to ensure a release has not occurred.

The pit material passed solidification and testing standards. The pit area was then backfilled with compacted, non-waste containing, earthen material. More than four feet of cover was achieved and the cover included one foot of suitable material to establish vegetation at the site.

10. During the stabilization process if the liner is ripped by equipment the Aztec OCD office will be notified within 48 hours and the liner will be repaired if possible. If the liner can not be repaired then all contents will be excavated and removed.

The integrity of the liner was not damaged in the pit closure process.

11. Dig and Haul Material will be transported to the Envirotech Land Farm located 16 miles south of Bloomfield on Angel Peak Road, CR 7175. Permit # NM010011

Dig and Haul was not required.

12. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final recontour shall have a uniform appearance with smooth surface, fitting the natural landscape.

The pit area was re-contoured to match fit, shape, line, form and texture of the surrounding area. Re-shaping included drainage control, to prevent ponding and erosion. Natural drainages were unimpeded and water bars and/or silt traps were placed in areas where needed to prevent erosion on a large scale. Final recontour has a uniform appearance with smooth surface, fitting the natural landscape.

13. Notification will be sent to OCD when the reclaimed area is seeded.

Provision 13 was accomplished through complying with BLM seeding requirements as allowed by the BLM/OCD MOU.

14. COPC shall seed the disturbed areas the first growing season after the operator closes the pit. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Provision 14 was accomplished through complying with State seeding requirements as allowed by the BLM/OCD MOU.

15. The temporary pit will be located with a steel marker, no less than four inches in diameter, cemented in a hole three feet deep in the center of the onsite burial upon the abandonment of all the wells on the pad. The marker will be flush with the ground to allow access of the active well pad and for safety concerns. The marker will include a threaded collar to be used for future abandonment. The top of the marker will contain a welded steel 12" square plate that indicates the onsite burial of the temporary pit. The plate will be easily removable and a four foot tall riser will be threaded into the top of the collar marker and welded around the base with the operator's information at the time of all wells on the pad are abandoned. The operator's information will include the following: Operator Name, Lease Name, Well Name and number, Unit Number, Section, Township, Range and an indicator that the marker is an onsite burial location.

Provision 15 was accomplished by installing a steel marker in the temporary pit, no less than four inches in diameter, cemented in a hole three feet deep in the center of the onsite burial. The marker is flush with the ground to allow access of the active well pad and for safety concerns. The top of the marker contains a welded steel 12" square plate that indicates the onsite burial of the temporary pit. The plate contains the following: Operator Name, Lease Name, Well Name and number, Unit Number, Section, Township, Range and an indicator that the marker is an onsite burial location.

The plate will be easily removable and a four foot tall riser will be threaded into the top of the collar marker and welded around the base with the following operator's information at the time of all wells on the pad are abandoned. The riser will be labeled: COP, BLM, MUDGE FEDERAL 1E, UL-E, Sec. 30, T 26N, R 11W, API # 30-045-33271

### Tafoya, Crystal

From:

Sent:

Tafoya, Crystal Saturday, October 04, 2008 9:27 AM 'larry\_pixley@nm.blm.gov'

To: Subject:

Surface Owner Notification

The temporary pits for the following wells will be closed on-site. Please let me know if you have any questions.

Mudge Federal 2 Mudge Federal 1E

Thank you,

Crystal L. Tafoya Regulatory Technician ConocoPhillips Company San Juan Business Unit Phone: (505) 326-9837

Email: Crystal.Tafoya@conocophillips.com

District I 1625 N. French Dr., Hobbs, NM 88240

State of New Mexico
Energy, Minerals & Natural Resources Department

Form C-102 Revised October 12, 2005 Instructions on back Submit to Appropriate District Office

District II 1301 W. Grand Avenue, Artesia, NM 88210

District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

Range

Lot Idn

Township

Section

Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

East/West line

District III 1000 Rio Brazos Rd., Aztec, NM 87410

UL or lot no.

OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

AMENDED REPORT

County

### WELL LOCATION AND ACREAGE DEDICATION PLAT


'AP	I Number			Code 529	'Pool Name BASIN FRUITLAND COAL				
Property 3158	ì				Property MUDGE FE			6	Well Number 1E
'OGRID 1				CO	*Operator Name *Elevation ONOCOPHILLIPS COMPANY 5118				
				1	<sup>0</sup> Surface I	Location			
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
E	30	26N	11W		2385   NORTH   770   WEST   5				SAN JUAN
P1	1,	11 E	Bottom	Hole L	ocation I	Different	From Surf	ace	


Feet from the

North/South line

Feet from the

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION







### EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConococPhillips	Project #:	96052-0026
Sample ID:	Mudge Fed #1E	Date Reported:	07-15-08
Laboratory Number:	46273	Date Sampled:	07-08-08
Chain of Custody No:	4630	Date Received:	07-08-08
Sample Matrix:	Soil	Date Extracted:	07-14-08
Preservative:		Date Analyzed:	07-15-08
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	27.3	0.1
Total Petroleum Hydrocarbons	27.3	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Drill Mud.

Analyst

Review Muchen



### EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConococPhillips	Project #:	96052-0026
Sample ID:	Mudge Fed #1E Background	Date Reported:	07-15-08
Laboratory Number:	46274	Date Sampled:	07-08-08
Chain of Custody No:	4630	Date Received:	07-08-08
Sample Matrix:	Soil	Date Extracted:	07-14-08
Preservative:		Date Analyzed:	07-15-08
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND ·	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Drill Mud.

Analyst

Christian Miceles
Review



### EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

### **Quality Assurance Report**

QA/QC		Project #:		N/A
07-15-08 QA/0	QC	Date Reported:		07-15-08
46256		Date Sampled:		N/A
Methylene Chlor	ide	Date Received:		N/A
N/A		Date Analyzed:		07-15-08
N/A	·	Analysis Reques	ted:	TPH
l Cal Date	LOSIBE	C-Cal DE	% Difference	Accept: Rang
a properties de la company	A LOCAL CONTRACTOR OF THE PARTY	1.0127E+003	0.04%	0 - 15%
05-07-07	1.0050E+003	1.0054E+003	0.04%	0 - 15%
al del control de la control d	AND THE STREET, THE PROPERTY OF THE STREET, THE STREET	www.shaneportwop.com/www.communicalanese	######################################	
	Concentration		Detection Limit	
	ND		0.2	
	ND		0.1	
	ND		0.2	
Sample	Duplicate	% Difference.	Accept: Range	500 CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
ND	ND	0.0%	0 - 30%	
11.0	10.9	0.9%	0 - 30%	
Sample	Spike Added	Spike Result	% Recovery	Accept: Rang
ND	250	243	97.2%	75 - 125%
112				
	07-15-08 QA/0 46256 Methylene Chlor N/A N/A I-Gal Date 05-07-07 05-07-07	07-15-08 QA/QC 46256 Methylene Chloride N/A N/A  I-Cal Date I-Cal RF: 05-07-07 1.0123E+003 05-07-07 1.0050E+003  Concentration ND ND ND ND ND 11.0 10.9  Sample Spike Added	07-15-08 QA/QC         Date Reported:           46256         Date Sampled:           Methylene Chloride         Date Received:           N/A         Date Analyzed:           N/A         Analysis Reques:           I-Cal Date         I-Cal RF         G-Cal RF           05-07-07         1.0123E+003         1.0127E+003           05-07-07         1.0050E+003         1.0054E+003           Concentration           ND         ND           ND         ND           ND         ND           11.0         10.9         0.9%   Sample Spike Added: Spike Results	07-15-08 QA/QC         Date Reported:           46256         Date Sampled:           Methylene Chloride         Date Received:           N/A         Date Analyzed:           N/A         Analysis Requested:           I-Cal Date I-Cal RF: G-Cal RF: % Difference           05-07-07 1.0123E+003 1.0127E+003 0.04%           05-07-07 1.0050E+003 1.0054E+003 0.04%           ND 0.2           ND 0.1           ND 0.1           ND 0.2           Sample Duplicate % Difference Accept Range           ND 0.0% 0-30%           11.0 10.9 0.9% 0-30%           Sample Spike Added Spike Result % Recovery

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 46256 - 46257, 46273 - 46278, and 46377 - 46378.

Analyst

Review



# EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Mudge Fed #1E	Date Reported:	07-16-08
Laboratory Number:	46273	Date Sampled:	07-08-08
Chain of Custody:	4630	Date Received:	07-08-08
Sample Matrix:	Soil	Date Analyzed:	07-15-08
Preservative:		Date Extracted:	07-14-08
Condition:	Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	ND	0.9	
Toluene	ND	1.0	
Ethylbenzene	ND	1.0	
	ND	1.2	
p,m-Xylene o-Xylene	ND	0.9	
Total BTEX	ND		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Drill Mud.

Analyst

Moster Waster
Review



# EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Mudge Fed #1E Background	Date Reported:	07-16-08
Laboratory Number:	46274	Date Sampled:	07-08-08
Chain of Custody:	4630	Date Received:	07-08-08
Sample Matrix:	Soil	Date Analyzed:	07-15-08
Preservative:		Date Extracted:	07-14-08
Condition:	Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	0.9
Toluene	ND	1.0
Ethylbenzene	ND	1.0
p,m-Xylene	ND	1.2
o-Xylene	ND	0.9
Total BTEX	ND	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	97.0 %
	1,4-difluorobenzene	97.0 %
	Bromochlorobenzene	97.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Drill Mud.

Analyst

Christine m Waster



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Project #:	N/A
Sample ID:	07-15-BT QA/QC	Date Reported:	07-16-08
Laboratory Number:	46254	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Preservative:	N/A	Date Analyzed:	07-15-08
Condition:	N/A	Analysis:	BTEX

Calibration and Detection Limits (ug/L)	I-CaliRF:	C-Cal RF Accept Rang	%Diff. je 0 - 15%	Blank Conc	Defect. Limit
Benzene	1.4558E+007	1.4587E+007	0.2%	ND	0.1
Toluene	9.9191E+006	9.9390E+006	0.2%	ND	0.1
Ethylbenzene	7.4164E+006	7.4312E+006	0.2%	ND	0.1
p,m-Xylene	1.8962E+007	1.9000E+007	0.2%	ND	0.1
o-Xylene	7.2244E+006	7.2389E+006	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample Du	plicate	%Diff.	Accept Range	Detect. Eimit
Benzene	1.0	1.1	10.0%	0 - 30%	0.9
Toluene	2.2	2.0	9.1%	0 - 30%	1.0
Ethylbenzene	1.6	1.7	6.3%	0 - 30%	1.0
p,m-Xylene	1.9	1.8	5.3%	0 - 30%	1.2
o-Xylene	1.3	1.2	7.7%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample Amo	ount Spiked - Spik	ed Sample	% Recovery	Accept Range
Benzene	1.0	50.0	50.4	98.8%	39 - 150
Toluene	2.2	50.0	51.6	98.9%	46 - 148
Ethylbenzene	1.6	50.0	51.0	98.8%	32 - 160
p,m-Xylene	1.9	100	101	99.4%	46 - 148
o-Xylene	1.3	50.0	50.7	98.8%	46 - 148

ND - Parameter not detected at the stated detection limit.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 46254 - 46257 and 46273 - 46278.

Analyst

(histum Waller Review

# ENVIROTECH LABS

### PRAVOTION SOLUTIONS FOR A BETTER TOMORROW

### **CATION / ANION ANALYSIS**

Cliente	Consessition	Don't at the	00050 0000
Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Mudge Fed #1E	Date Reported:	07-15-08
Laboratory Number:	46273	Date Sampled:	07-08-08
Chain of Custody:	4630	Date Received:	07-08-08
Sample Matrix:	Soil Extract	Date Extracted:	07-09-08
Preservative:		Date Analyzed:	07-10-08
Condition:	Intact		

Parameter	Analytical Result	Units		
рН	9.54	s.u.		A
Conductivity @ 25° C	3,070	umhos/cm		
Total Dissolved Solids @ 180C	1,930	mg/L		
Total Dissolved Solids (Calc)	2,101	mg/L		
SAR	32.6	ratio		
Total Alkalinity as CaCO3	62.0	mg/L		
Total Hardness as CaCO3	77.0	mg/L		
Bicarbonate as HCO3	62.0	mg/L	1.02	meq/L
Carbonate as CO3	<0.1	mg/L	0.00	meq/L
Hydroxide as OH	<0.1	mg/L	0.00	meq/L
Nitrate Nitrogen	< 0.01	mg/L	0.00	meq/L
Nitrite Nitrogen	0.004	mg/L	0.00	meg/L
Chloride	877	mg/L	24.74	meg/L
Fluoride	0.171	mg/L	0.01	meg/L
Phosphate	1.000	mg/L	0.03	meg/L
Sulfate	368	mg/L	7.66	meq/L
Iron	0.011	mg/L	0.00	meq/L
Calcium	30.60	mg/L	1.53	meq/L
Magnesium	0.131	mg/L	0.01	meq/L
Potassium	129.0	mg/L	3.30	meq/L
Sodium	657	mg/L	28.58	meq/L
Cations			33.42	meq/L
Anions			33.46	meq/L
Cation/Anion Difference			0.12%	

Reference: U.S.E.P.A., 600/4-79-020, "Methods for Chemical Analysis of Water and Wastes", 1983.

Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Drill Mud.

Analyst

Musteren Weeters Review

# ENVIROTECH LABS

### **CATION / ANION ANALYSIS**

Client:	ConocoPhillips	Project #:	96052-0026
	•		
Sample ID:	Mudge Fed #1E Background	Date Reported:	07-15-08
Laboratory Number:	46274	Date Sampled:	07-08-08
Chain of Custody:	4630	Date Received:	07-08-08
Sample Matrix:	Soil Extract	Date Extracted:	07-09-08
Preservative:		Date Analyzed:	07-10-08
Condition:	Intact		

	Analytical			
Parameter	Result	Units		
рН	7.37	s.u.		
Conductivity @ 25° C	134	umhos/cm		
Total Dissolved Solids @ 180C	62.0	mg/L		
Total Dissolved Solids (Calc)	63.1	mg/L		
SAR	0.6	ratio		
Total Alkalinity as CaCO3	38.0	mg/L		
Total Hardness as CaCO3	24.6	mg/L		
Bicarbonate as HCO3	38.0	mg/L	0.62	meq/L
Carbonate as CO3	<0.1	mg/L	0.00	meq/L
Hydroxide as OH	<0.1	mg/L	0.00	meq/L
Nitrate Nitrogen	2.12	mg/L	0.03	meq/L
Nitrite Nitrogen	0.172	mg/L	0.00	meq/L
Chloride	15.5	mg/L	0.44	meq/L
Fluoride	1.26	mg/L	0.07	meq/L
Phosphate	0.483	mg/L	0.02	meq/L
Sulfate	2.58	mg/L	0.05	meq/L
Iron	8.66	mg/L	0.31	meq/L
Calcium	3.38	mg/L	0.17	meq/L
Magnesium	3.94	mg/L	0.32	meq/L
Potassium	3.5	mg/L	0.09	meq/L
Sodium	7.13	mg/L	0.31	meq/L
Cations			1.20	meq/L
Anions			1.23	meq/L
Cation/Anion Difference			2.49%	

Reference: U.S.E.P.A., 600/4-79-020, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Drill Mud.

Analyst

(Review ( ) cetter



### TRACE METAL ANALYSIS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Mudge Fed #1E	Date Reported:	07-11-08
Laboratory Number:	46273	Date Sampled:	07-08-08
Chain of Custody:	4630	Date Received:	07-08-08
Sample Matrix:	Soil	Date Analyzed:	07-09-08
Preservative:		Date Digested:	07-09-08
Condition:	Intact	Analysis Needed:	Total Metals

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	TCLP Regulatory Level (mg/Kg)
Arsenic	0.131	0.001	5.0
Barium	8.56	0.001	100
Cadmium	0.007	0.001	1.0
Chromium	Chromium 0.383		5.0
Lead 0.234		0.001	5.0
Mercury	ND	0.001	0.2
Selenium	0.098	0.001	1.0
Silver	ND	0.001	5.0

ND - Parameter not detected at the stated detection limit.

References:

Method 3050B, Acid Digestion of Sediments, Sludges and Soils.

SW-846, USEPA, December 1996.

Method 6010B, Analysis of Metals by Inductively Coupled Plasma Atomic Emmision

Spectroscopy, SW-846, USEPA, December 1996.

Note:

Regulatory Limits based on 40 CFR part 261 subpart C

section 261.24, August 24, 1998.

Comments:

Drill Mud.

Analyst

Portour my L

Review



### TRACE METAL ANALYSIS

Client:	ConocoPhillips	Project #:	96052-0026
Sample ID:	Mudge Fed #1E Background	Date Reported:	07-11-08
Laboratory Number:	46274	Date Sampled:	07-08-08
Chain of Custody:	4630	Date Received:	07-08-08
Sample Matrix:	Soil	Date Analyzed:	07-09-08
Preservative:		Date Digested:	07-09-08
Condition:	Intact	Analysis Needed:	Total Metals

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	TCLP Regulatory Level (mg/Kg)
Arsenic	0.090	0.001	5.0
Barium	9.82	0.001	100
Cadmium	0.003	0.001	1.0
Chromium	0.208	0.001	5.0
Lead	0.204	0.001	5.0
Mercury	ND	0.001	0.2
Selenium	0.038	0.001	1.0
Silver	ND	0.001	5.0

ND - Parameter not detected at the stated detection limit.

References:

Method 3050B, Acid Digestion of Sediments, Sludges and Soils.

SW-846, USEPA, December 1996.

Method 6010B, Analysis of Metals by Inductively Coupled Plasma Atomic Emmision

Spectroscopy, SW-846, USEPA, December 1996.

Note:

Regulatory Limits based on 40 CFR part 261 subpart C

section 261.24, August 24, 1998.

Comments:

Drill Mud.

Analyst

Review Called Control of the Control



# TRACE METAL ANALYSIS Quality Control / Quality Assurance Report

Client:	QA/QC	Project #:	QA/QC
Sample ID:	07-09 TM QA/AC	Date Reported:	07-11-08
Laboratory Number:	46273	Date Sampled:	N/A
Sample Matrix:	Soil	Date Received:	N/A
Analysis Requested:	Total RCRA Metals	Date Analyzed:	07-09-08
Condition:	N/A	Date Digested:	07-09-08

Blank & Duplicate Conc. (mg/Kg)	Instrument Blank (mg/Kg)	Method Blank	Detection Limit	CONTRACTOR STATE OF THE LAND	Duplicate	) % Diff.	Acceptance Range
Arsenic	ND	ND	0.001	0.131	0.129	0.8%	0% - 30%
Barium	ND	ND	0.001	8.56	8.84	3.2%	0% - 30%
Cadmium	ND	ND	0.001	0.007	0.007	0.0%	0% - 30%
Chromium	ND	ND	0.001	0.383	0.409	6.8%	0% - 30%
Lead	ND	ND	0.001	0.234	0.243	3.7%	0% - 30%
Mercury	ND	ND	0.001	ND	ND	0.0%	0% - 30%
Selenium	ND	ND	0.001	0.098	0.090	7.8%	0% - 30%
Silver	ND	ND	0.001	ND	ND	0.0%	0% - 30%

Spike Conc (mg/Kg)	Spike Added	Sample	e Spiked Sample		Acceptance Range
Arsenic	0.250	0.131	0.332	87.3%	80% - 120%
Barium	0.500	8.56	9.21	102%	80% - 120%
Cadmium	0.250	0.007	0.231	89.9%	80% - 120%
Chromium	0.500	0.383	0.750	84.9%	80% - 120%
Lead	0.500	0.234	0.76	103%	80% - 120%
Mercury	0.100	ND	0.097	97.3%	80% - 120%
Selenium	0.100	0.098	0.204	103%	80% - 120%
Silver	0.100	ND	0.093	92.9%	80% - 120%

ND - Parameter not detected at the stated detection limit.

References:

Method 3050B, Acid Digestion of Sediments, Sludges and Soils.

SW-846, USEPA, December 1996.

Method 6010B, Analysis of Metals by Inductively Coupled Plasma Atomic Emmision

Spectorscopy, SW-846, USEPA, December 1996.

Comments:

QA/1QC for Samples 46273 - 46278.

Analyst

Mustum Waster



### EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

ConocoPhillips

Project #:

96052-1659

Sample No.:

- 1

Date Reported: Date Sampled:

3/1/2010

Sample ID:

5 pt Composite

2/26/2010

Sample Matrix:

Soil

Date Analyzed:

2/26/2010

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

280

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Mudge Federal #1E

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review

Toni McKnight

Orintad

Printed

Printed

James McDaniel



# CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal. Date:

26-Feb-10

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
TPH	100		
	186	185	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Analyst Analyst	3/1/20/0 Date
Toni McKnight Print Name	
Réview	3 /2 / (O Date
James McDaniel	

**Print Name** 

Submit To Appropr Two Copies District I	riate Distri	ct Office		Em		State of Ne											orm C-105 July 17, 2008
1625 N. French Dr. District II	, Hobbs, N	M 88240		En	agy, i	Minerals and	u iva	ıurarı	Ke	sources	ŀ	1. WELL A		NO.			July 17, 2008
1301 W. Grand Ave	•		210			l Conservat					-	30-045-332 2. Type of Le					
1000 Rio Brazos Ro District IV	,		505			20 South St Santa Fe, N				r.	-	3. State Oil &		FE FE		FED/IND	IAN
1220 S. St. Francis												I-149-IND-	-797	1			
4. Reason for fili		LETIO	N OR	RECC	MPL	ETION RE	POF	RTAN	ND	LOG	+	5. Lease Name					
☐ COMPLETI	Ü	PORT (Fil	ll in boxes	#1 throu	gh #31	for State and Fee	e wells	s only)				MUDGE F	EDI				
C-144 CLOS #33; attach this ar	SURE All	ГТАСНМ	IENT (Fi	ll in boxe	s#1thr	ough #9, #15 Da	nte Rig	Releas			ı,	1E	er.				
	VELL_[	□ WORK	OVER [	DEEPI	ENING	□PLUGBAC	<b>Κ</b> 🔲	DIFFER	REN	IT RESERVO	OIR	OTHER					
8. Name of Opera		ıpanv									- 1	9. OGRID 217817					
10. Address of Op PO Box 4298, Fa	perator		99									11. Pool name	or W	ildcat			
	Unit Ltr	,		Towns	hin	Panga	Lot			Feet from the		N/S Line	Foot	from th	a Lea	W Line	County
12.Location Surface:	Olit Eti	500		TOWNS	шр	Range	1 201		+	Teet Holli th		N/3 Line	rect	. HOIII UI	le 127	W Line	County
BH:											1						
13. Date Spudded	1 14. C	Date T.D. I	Reached	15. I 12/1		Released			16.	Date Comple	ted	(Ready to Prod	luce)			vations (DI R, etc.)	and RKB,
18. Total Measure	ed Depth	of Well		19. I	lug Bac	k Measured Dep	oth	2	20.	Was Direction	onal	Survey Made?	•	21. Ty	ype Ele	ectric and O	ther Logs Run
22. Producing Int	erval(s),	of this cor	mpletion -	Top, Bot	tom, Na	ame								1			
23.					CAS	ING REC	OR				ng				,		
CASING SI	ZE	WEI	GHT LB.	FT.		DEPTH SET			HO.	LE SIZE	_	CEMENTIN	G RE	CORD		AMOUNT	PULLED
SIZE	ТОР		ВО	ттом	LIN	ER RECORD SACKS CEM	ENT	SCRE	EEN		25. SIZ			NG RE			ER SET
		-															
26. Perforation	record (i	interval, si	ze, and nu	mber)		<u> </u>		27 A	ACI	D SHOT F	R/	ACTURE, CE	MEN	IT SOI	JEEZ!	E. ETC.	
	,	,	ĺ							NTERVAL		AMOUNT A					
												<u> </u>					
28.  Date First Produc	tion		Produc	tion Met	hod (Fl	owing, gas lift, p				TION		Well Status	(Pro	d or Sh	ıt in)		
Date Hist House	don		Troduc	tion wice	nou (x re	wing, gas iyi, p	итріп	g - 512e	ини	і іуре ритр)		Well Status	(170	a. Or Sni	<i>ii-iii)</i>		
Date of Test	Hour	s Tested	Ch	oke Size		Prod'n For Test Period		Oil - I	Bbl	1	Gas	- MCF	w 	ater - Bl	ol.	Gas - 0	Oil Ratio
Flow Tubing Press.	Casir	ng Pressur		lculated a	24-	Oil - Bbl.		G	ias -	MCF		Water - Bbl.		Oil G	ravity -	- API - (Coi	T.)
29. Disposition of	f Gas (So	old, used fo	or fuel, ver	ited, etc.,		l	<del></del>						30.	Test Wit	nessed	Ву	
31. List Attachme																	
32. If a temporary	•		4	-			-		t.								
33. If an on-site b	ourial was		1	-					ים ו	71027 1710	102						
I hereby certij	fy that i	the infor	mation:	showh c	n boti	ongitude 108.05 h sides of this	forn	n is tru	ie a	and comple	ete	to the best o	f my	knowl	edge i	and belie	f
Signature (	$\int \!\! \int \!\! W$	NA	Ma	v X	/ Nar	nted ne Marie E.	Jara	millo	Т	Title: Staff	f R	egulatory To	ech	Da	te: 6/	18/2010	
E-mail Addre	ss mar	ie.¢.jara:	millo@d	onocoj	hillip	s.com											
		\/															

# ConocoPhillips Pit Closure Form:

Date: 7/8/08
Well Name: Madge fed # 1 E
Footages: 2385 FNL Unit Letter: E
Section: 30, 1-24-N, R-11 -W, County: San Juan State: N. M.
Pit Closure Date: 1/8/08  Contractor Closing Ptt: A 2 7 2 -
Contractor Closing Pfr: A 212
Enc Snith 1/8/08
Construction inspector Name Date ConocoPhillips
Signature

Revised 10/22/07

### Jaramillo, Marie E

From:

Swenson, Kathy A

Sent:

Tuesday, July 01, 2008 2:32 PM

To: Cc:

'Brandon.Powell@state.nm.us'; 'Erinn Shirley'; 'Mark Kelly'; 'Robert Switzer'; 'Sherrie Landon' 'Faver Norman'; 'Aztec Excavation'; Blair, Maxwell O; Blakley, Maclovia; Clark, Joan E; Farrell, Juanita R; Finkler, Jane; Maxwell, Mary A (SOS Staffing Services, Inc.); McWilliams, Peggy L;

Seabolt, Elmo F; 'gmeador.aec@earthlink.net'

Subject:

Clean Up Notice: Mudge Federal 1E

Importance:

High

Attachments:

Mudge Federal 1E.PDF

Aztec Excavation will move a tractor to the Mudge Federal 1E on Monday, July 7, 2008 to start the reclamation process. Please contact Eric Smith (608-1387) if you have any questions or need additional information.

Network #: 10147913 (CoP - HZ) Navajo Allotted + BLM/ Tribal Minerals

API: 30-045-33271

PTRRC: Please notify James Miles-BIA



1E.PDF (16 KB)

Thank you!

Kathy Swenson

ConocoPhillips - SJBU

**Construction Technician-Project Development Team** 

Farmington, NM 87401

505.324.6127(office) 505.599.4062(fax)


Kathy.A.Swenson@conocophillips.com


# ConocoPhillips

Reclamation Form:			
Date: <u>5115/08</u>	<del></del>		
Well Name: Mudg	≥ fed. #1 €		
Footages: 2385 FNL	MYOFWL	Unit Letter:	E
Section: <u>30</u> , T- <u>26</u> -	-N, R- <u>//</u> W, County: <u>S</u> a	พ <u>ไหลม</u> State:	N.M.
Reclamation Contractor:	Azdze		
Reclamation Date:	7/12/08		
Road Completion Date:	7/14/08		
Seeding Date:	7/15/08		
Construction Inspector:	Eric Smith	Date: 1	15/08
Inspector Signature:	5.25		•









# WELL PAD SAFETY AND ENVIRONMENTAL CHECK LIST

WELL NAME:	WELL NAME: Mudge Fed 1E			API#:	
		SAFETY	LOCATION	PICTURES	
DATE	INSPECTOR	CHECK	CHECK	TAKEN	COMMENTS
11/29/2007	Eric Smith	×	×	×	
12/20/2007	Eric Smith	×	×	×	
1/2/2008	Eric Smith	×	×	×	
1/14/2008	Eric Smith	×	×	×	
1/22/2008	Eric Smith	×	×	×	
1/31/2008	Eric Smith	×	×	×	
2/21/2008	Eric Smith	×	×	×	Called contractor to fix fence.
3/12/2008	Eric Smith	X	×	×	
4/11/2008	Johnny R McDonald	×	×	×	
4/29/2008	Jared Chavez	×	×	×	Pit & location in good condition
5/16/2008	Jared Chavez	×	×	×	Pit & location in good condition
6/3/2008	Jared Chavez	X	×	×	Pit & location in good condition
8/6/2008	Scott Smith	X	×	×	Pit & location in good condition
6/12/2008	Scott Smith	X	×	×	Small tear in SW corner. Called contractor to repair.
6/19/2008	Scott Smith	×	×	×	Liner needs repaired. OCD & Contractors notified.
6/26/2008	Scott Smith	X	×	×	Pit & location in good condition
7/3/2008	Scott Smith	X	×	×	Pit & location in good condition
		74.50			
Part of the second seco					