

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FEB 23 2011

## Sundry Notices and Reports on Wells

1. Type of Well  
GAS

2. Name of Operator  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Surface: Unit M (SWSW), 715' FSL & 1220' FWL, Section 25, T31N, R12W, NMPM

BHL: Unit L (NWSW), 1880' FSL & 1025' FWL, Section 25, T31N, R12W, NMPM

Lease Number  
SF-077652

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

8. Well Name & Number  
East 9N

9. API Well No.

30-045-35182

10. Field and Pool  
Blanco MV / Basin DK

11. County and State  
San Juan, NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ X

Other -

Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

## 13. Describe Proposed or Completed Operations

02/05/2011 MIRU AWS 920. NU BOPE. PT csg to 600#/30min @ 11:00hrs on 2/6/11. Test - OK. RIH w/ 8 3/4" bit. Tag cmt @ 200' & D/O cmt to 238'.

02/09/2011 Drilled ahead w/ 8 3/4" bit to 4595' - Inter TD reached 2/09/2011. Circ hole & RIH w/ 108jts, 7", 23#, J-55 LT&C set @ 4580' w/ ST @ 1842'. 2/11/11 RU to cmt. 1<sup>st</sup> Stage - Pre-flush w/ 10bbbs GW, 2bbbs FW. Pumped scavenger 19sx (56cf-10bbbs) Premium Lite w/ 3% CaCl, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite & .4% SMS. Lead w/ 272sx (579cf-103bbbs) Premium Lite w/ 3% CaCl, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite & .4% SMS. Tail w/ 106sx (146cf-26bbbs) Type III cmt w/ 1% CaCl, .25pps celloflake & .2% FL-52. Drop plug & displaced w/ 120bbbs FW. Bump plug. Plug down. Open ST & Circ 60bbbs cmt to surface. WOC.

2<sup>nd</sup> Stage - Pre-flush w/ 10bbbs FW, 10bbbs MW, 10bbbs FW. Pumped scavenger 19sx (56cf-10bbbs) Premium Lite w/ 3% CaCl, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite & .4% SMS. Lead w/ 209sx (445cf-79bbbs) Premium Lite w/ 3% CaCl, .25pps celloflake, 5pps LCM-1, .4% FL-52, 8% bentonite & .4% SMS. Drop plug & displaced w/ 73bbbs FW. Bump plug & close ST. Circ 20bbbs cmt to surface. RD cmt. Plug down @ 16:30hrs on 2/11/11. WOC. 2/12/11 RIH w/ 6 1/4" bit. Drill out ST @ 1842'. PT 7" csg to 1500#/30min @ 06:30hrs on 2/12/11. Test - OK. Drilled ahead w/ 6 1/4" bit to 7240' (TD) TD reached 2/13/11. Circ hole & RIH w/ 168jts, 4 1/2", 11.6#, L-80 LT&C set @ 7238'. 2/14/11 RU to cmt. Pre-flush w/ 10bbbs CW, 2bbbs FW. Pumped scavenger 9sx (28cf-5bbbs) Premium Lite HS FM, .25pps celloflake, .3% CD-32, 6.25pps LCM-1 & 1% FL-52. Tail w/ 188sx (372cf-66bbbs) Premium Lite HS FM, .25pps celloflake, .3% CD-32, 6.25pps LCM-1 & 1% FL-52. Flush lines w/ 15bbbs FW. Drop plug & displaced w/ 113bbbs FW. Bump plug. Plug down @ 13.30hrs on 2/14/11. RD cmt. WOC. ND BOPE. NU WH. RD RR @ 19:30hrs on 2/14/11.

PT will be conducted by Completion Rig. Results & TOC will appear on next report.

## 14. I hereby certify that the foregoing is true and correct.

Signed Dollie L. Busse

Dollie L. Busse

Title Staff Regulatory Technician

Date 2-18-11

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

MMOCD

FARMINGTON FIELD OFFICE