Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5. Lease Serial No. NMSF080379A

6.	If Indian, A	llottee or	Tribe	Name

	,	N. Carlos				
SUBMIT IN TRIF	PLICATE - Other instruc	tions on réverse sidé c	200.	7. If Unit or CA/Agreen NMNM78416E	nent, Name and/or No.	
Type of Well ☐ Oil Well ☐ Gas Well ☐ Oth				8. Well Name and No. SAN JUAN 29-6 UNIT 245A		
Name of Operator CONOCOPHILLIPS COMPANY Contact: Contact:		PATSY CLUGSTON	Mail: plclugs@ppco.com (a) (a) (a)		9. API Well No. 30-039-27508-00-X1	
3a. Address 5525 HIGHWAY 64 FARMINGTON, NM 87401	3b. Phone No. (include area coordinated	No. (findfude area code)		10. Field and Pool, or Exploratory BASIN FRUITLAND COAL		
4. Location of Well (Footage, Sec., T.	, R., M., or Survey Description	n)		11. County or Parish, as	nd State	
Sec 8 T29N R6W NWNW 740	FNL 995FWL			RIO ARRIBA COUNTY, NM		
12. CHECK APPR	COPRIATE BOX(ES) TO	O INDICATE NATURE OF	F NOTICE, RI	EPORT, OR OTHER	DATA	
TYPE OF SUBMISSION		TYPE	OF ACTION			
☐ Notice of Intent	□ Acidize	Deepen	□ Product	ion (Start/Resume)		
-	☐ Alter Casing	☐ Fracture Treat	☐ Reclam	ation	■ Well Integrity	
Subsequent Report	□ Casing Repair	■ New Construction	□ Recomp	olete	Other Drilling Operations	
Final Abandonment Notice	☐ Change Plans	Plug and Abandon	☐ Tempor	arily Abandon	Drilling Operations	
	Convert to Injection	□ Plug Back	□ Water I	Disposal		
determined that the site is ready for fit 7" CASING REPORT 2/3/04 RIH w/8-3/4" bit & tagge Circ. hole. RIH w/7", 20#, J-5t of 30 bbls FW w/dye in lst 10 l cement w/3% extender, 0.25#, bbl slurry) 50/50 Class G POZ Antifoam. Dropped plug and c 0707 hrs 2/8/04. Circ. 36 bbls ND BOP & PU stack. Set slips hrs 2/8/04. Will show casing F	ed cement @ 188'. Drille 5 ST&C casing and set @ 5 bls. Pumped Lead - 45 /sx cellephane, & 0.2% a w/2% Gel, 5#/sx Gilsoni displaced plug w/20 bbls good cement to surface s and cut off casing. Ins	3449'. RU Schlumberger. 5 sx (1187.6 cf - 211.5 bbl s Intifoam. Tail - Pumped 100 te, 2% CaCl2, 0.25#/sx Cell FW & 118 bbls mud. Bump . RD Schlumberger. Chand	. Pumped a p slurry) Class G) sx (127 cf - 2 lo-phane, & 29 ped plug w/12 ged rams to 4	reflush /2.5 /6 50 psi @ -1/2".		
14. I hereby certify that the foregoing is	Electronic Submission in For CONOCOPI	#27865 verified by the BLM W HILLIPS COMPANY, sent to to ssing by ADRIENNE GARCIA	he Farmington	_		
Name (Printed/Typed) PATSY CL		• •		PRESENTATIVE		
Signature (Electronic S			/2004			
	THIS SPACE FO	OR FEDERAL OR STATI		SE		
Approved By ACCEPT	ED		INE GARCIA LEUM ENGINI	EER	Date 02/17/2004	
Conditions of approval, if any, are attache ertify that the applicant holds legal or equivalent would entitle the applicant to condu-		ngton				
Title 18 U.S.C. Section 1001 and Title 43	U.S.C. Section 1212, make it:	a crime for any person knowingly:	and willfully to m	ake to any department or	agency of the United	

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.