UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED

MAR 11 2011

AMENDED

Sundry Notices and Reports on Wells	Farmington Field Office Bureau of Land Management
	5. Lease Number SF-079383
1. Type of Well GAS	
2. Name of Operator BURLINGTON RESCURCES OIL & GAS COMPANY LP	6. If Indian, All. or Tribe Name 7. Unit Agreement Name SAN JUAN 30-6 UNIT 8. Well Name & Number
3. Address & Phone No. of Operator	8. Well Name & Number SAN JUAN 30-6 UNIT 95 9. API Well No.
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9. API Well No.
A Location of Well Feature See T. D. M.	30-039-30922
4. Location of Well, Footage, Sec., T, R, M Surface: Unit M (SW/SW), 875' FSL & 790' FWL, Section Bottomhole: Unit L (NW/SW), 2000' FSL & 710' FWL,	
Bottommore. Unit L (N W/S W), 2000 FSL & 710 FWL,	11. County and State Rio Arriba, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATUR Type of Submission Type of Action	E OF NOTICE, REPORT, OTHER DATA
Notice of Intent Abandonment Recompletion	Change of Plans X Other – Casing Report New Construction
X Subsequent Report Plugging	Non-Routine Fracturing
Final Abandonment Casing Repair Altering Casing	Water Shut off Conversion to Injection
13. Describe Proposed or Completed Operations	
set @ 4246' w/ ST @ 3605'. 1st Stage - Pre-flushed w/ 10bbls GW, 2bbls FW. P celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 28sx 52, 8% bentonite, & 0.4% SMS. Tail w/ 76sx(105cf-19bbls) Type III cmt w/ 1% Bumped plug. Plug down @ 20:33hrs 02/04/11. Open ST & Circ. 8bbls cmt to scavenger w/ 19sx(57cf-10bbls) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 169bbls) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FLBumped plug & close ST. Plug down @ 22:54hrs on 02/04/11. Circ. 40bbls cmt 02/05/11 TIH w/ 6 1/4" bit. Drill out ST @ 3605'. PT csg to 1500#/30min @04:38503' on 02/08/11. Circ. hole & RIH w/ 198jts, (34jts BT&C & 164jts LT&C) 4 Pumped scavenger 9sx(28cf-5bbls) Premium lite HS FM, 0.25pps celloflake, 0.	(60cf-11bbls) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-CaCl, .025 pps celloflake, & 0.2% FL-52. Dropped plug & displaced w/ 166bbls FW. urface. WOC. 2nd Stage - Pre-flush w/ 10 bbls FW, 10bbls GW, 10bbls FW. Pumped 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Lead w/ 447sx(452cf-52, 8% bentonite, & 0.4% SMS. Dropped plug & Displaced w/ 142bbls of FW.
PT will be conducted by Completion Rig. Results & TOC will appear on next rep	port.
14. I hereby certify that the foregoing is true and correct. Signed Marie E. J	aramillo Title <u>Staff Regulatory Technician</u> Date <u>02/12/11</u>
(This space for Federal or State Office use)	
APPROVED BY Title CONDITION OF APPROVAL, if any:	Date ACCEPTED FOR RECORD
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any departm the United States any false, fictitious or fraudulent statements or representations as to any matter within its j	ent or agency of urisdiction.
	IMOCD MAR 1 5 2011