

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT L" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Tesoro Petroleum Corporation	5. State Oil & Gas Lease No.
3. Address of Operator 8520 Crownhill Boulevard, San Antonio, Texas 78209	7. Unit Agreement Name
4. Location of Well UNIT LETTER F, 1650 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 7 TOWNSHIP 17N RANGE 8W NMPM.	8. Farm or Lease Name Santa Fe R.R.
	9. Well No. 9
	10. Field and Pool, or Wildcat South Hospah-Upper Sand
15. Elevation (Show whether DF, RT, GR, etc.) 6972' KB; 6968' GL	12. County McKinley

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/> (Plug back)	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 6-19-70: Set Halliburton E-Z, C.I. retainer at 1610'. Staged squeezed Lower Hospah Sand with 90 sacks common cement to 2000#. Left 1' cement on retainer. P.B.T.D. 1609' KB.
- 6-20-70: Swabbed hole. Ran Gamma Ray Neutron and Collar Log. Perforated Upper Hospah Sand 1571-79' with 32 holes, 4/foot. Ran 2-cup packers and pumped 1/2 barrel 15% HCl acid into each foot of perforations w/800#.
- 6-21-70: Ran completion tubing and swabbed load oil.
- 7-7-70: Ran rods and pump. Put on production.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>[Signature]</i>	TITLE Petroleum Engineer	DATE July 28, 1970
APPROVED BY <i>[Signature]</i>	TITLE SUPERVISOR DIST. #3	DATE AUG 3 1970
CONDITIONS OF APPROVAL, IF ANY:		