

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 052931

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hanson

9. WELL NO.

17

10. FIELD AND POOL, OR WILDCAT

South Hospah-Upper Sand

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 6, T17N, R8W, NMPM

12. COUNTY OR PARISH

McKinley

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Tesoro Petroleum Corporation

3. ADDRESS OF OPERATOR

8520 Crownhill Boulevard, San Antonio, Texas 78209

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

Unit Letter K 1940' from West Line and 2090' from South Line

14. PERMIT NO.

?

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6887' GL

6899' RKB

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING.  
(Other) Commence drilling & casing settings

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 10:00 AM 4-16-70. Drilled 12-1/4" hole to 75' RKB. Set 2 joints 8-5/8" 24# H-40 ST&C surface casing at 74' RKB with 50 sacks common cement plus 2% CaCl. Cement circulated to surface.

Drilled 7-7/8" hole to 1514' RKB and ran Schlumberger IES Log.

Ran 48 joints 5-1/2" 14# J-55 ST&C casing with Larkin float shoe and Larkin coupling insert float in top of bottom joint, 4 short bow latch-on centralizers, and 100' rotating scratchers. Set at 1513' RKB with 100 sacks regular cement. Plug down at 12:10 AM 4-18-70.

Preparing to drill in with power swivel for open hole completion.



RECEIVED

APR 22 1970

GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED R. H. BenmanTITLE Petroleum EngineerDATE April 21, 1970

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side