

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-031-20232

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Blackeye (SFP)

8. Well No.

1.

9. Pool name or Wildcat
Blackeye Dakota

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒

GAS WELL ☐

OTHER

2. Name of Operator

Black Oil Inc.

3. Address of Operator

P. O. Box 537, Farmington, New Mexico 87401

4. Well Location

Unit Letter M : 990 Feet From The South Line and 990 Feet From The West Line

Section 29

Township 20N

Range 9W

NMPM

McKinley

County

10. Elevation (Show whether DP, RKB, RT, GR, etc.)

6557 KB

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

DIST. 3

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

07/30/92 Rigged up. Unseated pump and POH with 147 3/4" rods and tubing pump.

07/31/92 POH with 120 jts 2-3/8" tubing, 3761' RIH with open ended tubing and subs to 3782'. Plugged #1 fm 3782' to 3265' with 40 sxs Class B cement, POH with tubing.

08/03/92 Pressure tested csg to 500#, OK. RIH and tagged cement at 3304'. Perforated at 1600'. RIH with tbg to 1610'. Plugged #2 fm 1610' to 1213' with 30 sxs cement, POH to 1128' and squeezed 20 sxs cement outside casing. WOC. RIH and tag cement at 1470'. POH with tbg and perf at 150'. Cir out bradenhead. Plugged #3 fm 150 to surf with 40 sxs cement; cir good cmt to surface. WOC. ND BOP and cut off wellhead. Installed P & A marker with 10 sxs cement. Plugging operations in the field were by Charles Gholson of the NM Oil Conservation Division.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE President

DATE 8/11/92

TYPE OR PRINT NAME

Bruce A. Black

TELEPHONE NO. 325-7855

(This space for State Use)

DEPUTY OIL & GAS INSPECTOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

AUG 6 1993