NO. OF COPIES RECEIVED 3			Form C-103/
DISTRIBUTION			Supersedes Old C-102 and C-103
SANTA FE (NEW MEXICO OIL C	ONSERVATION COMMISSION	Effective 1-1-65
FILE /			
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE			State Fee XX
	- 		5. State Oil & Gas Lease No.
OPERATOR //			5, state on a sas pease no.
			mmmmm
SUN COO NOT USE THIS FORM FOR	NDRY NOTICES AND REPORTS	ON WELLS	
USE REPL	ICATION FOR PERMIT - " (FORM C-101) FOR	SUCH PROPOSALS.)	
I. OIL GAS T			7. Unit Agreement Name
OIL GAS WELL WELL	OTHER-		
2. Name of Operator			8. Farm or Lease Name
William G. Gill			Santa Fe
1. Attress of Operator			9, Well No.
430 Wilson Building	g, Corpus Christi, TX 7	8401	1
4. Location of Well			10. Field and Pool, or Wildcat
Λ	330 N	330	Marcelina/Dakota
UNIT LETTER	330 FEET FROM THE N	LINE AND FEET FROM	mmmmmm
E	22	16N 10U	
THELINE, 5	ection 23 township	IDIN RANGE IUW NMPM	
		7	
	15, Elevation (Show who	ether DF, RT, GR, etc.)	12. County
	7155 GL		McKinley ()
16. Che	ck Appropriate Box To Indica	te Nature of Notice, Report or Ot	
	FINTENTION TO:		
NOTICE	FINIENTION TO.	SUBSEQUEN	T REPORT OF:
ليا			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT A
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	
		OTHER	
OTHER.		OTHER	
17. Pescribe Proposed or Complete	ed Operations (Glearly state all pertinen	OTHER t details, and give pertinent dates, including	estimated date of starting any proposed
	ed Operations (Clearly state all pertinen		estimated date of starting any proposed
17. Pescribe Proposed or Complete	ed Operations (Clearly state all pertinen		estimated date of starting any proposed
17. Pescribe Proposed of Complete work) SEE RULE 1103.			estimated date of starting any proposed
17. Pescribe Froposed or Complete scork) SEE RULE 1103. Spudded 7/13/77 - 9) 5/8" Hole	t details, and give pertinent dates, including	
12. Poscribe Proposed or Complete work) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of) 5/8" Hole 7 5/8" 26.4#, J-55 Surfa		
17. Poscribe Proposed or Complete work) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl) 5/8" Hole 7 5/8" 26.4#, J-55 Surfa oride	t details, and give pertinent dates, including	
17. Pescribe Proposed or Complete work) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T.	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa Joride D.	t details, and give pertinent dates, including	
17. Poscribe Proposed or Complete work) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa Joride D.	t details, and give pertinent dates, including	
17. Pescribe Proposed or Complete work) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T.	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa Joride D.	t details, and give pertinent dates, including	
17. Pascribe Proposed or Complete leark) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attack	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa Joride D.	t details, and give pertinent dates, including	
17. Pescribe Proposed or Complete work) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T.	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa Joride D.	t details, and give pertinent dates, including	
17. Pascribe Proposed or Complete Rock) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attack	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa Joride D. Ched	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000'	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa Joride D. Shed to 1,824' w/ 35 sks	t details, and give pertinent dates, including	
17. Pescribe Proposed or Complete (cork) SEE RULE 1103. Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chil Drilled to 2,028 T. Logged - copy attack 7/20/77 Plugged From 2,000' From 1,170'	0 5/8" Hole 7 5/8" 26.4#, J-55 Surfa loride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chil Drilled to 2,028 T. Logged - copy attack 7/20/77 Plugged From 2,000' From 1,170' From 585' t	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa oride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chil Drilled to 2,028 T. Logged - copy attack 7/20/77 Plugged From 2,000' From 1,170' From 585' t	0 5/8" Hole 7 5/8" 26.4#, J-55 Surfa loride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chil Drilled to 2,028 T. Logged - copy attack 7/20/77 Plugged From 2,000' From 1,170' From 585' t	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa oride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 185' t	0 5/8" Hole 7 5/8" 26.4#, J-55 Surfa oride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 185' t	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa oride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 185' t	0 5/8" Hole 7 5/8" 26.4#, J-55 Surfa oride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 185' t	0 5/8" Hole 7 5/8" 26.4#, J-55 Surfa oride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks	t details, and give pertinent dates, including	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 185' t From 145' t	9 5/8" Hole 7 5/8" 26.4#, J-55 Surfa Oride D. Thed to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks to 45' w/ 20 sks	details, and give pertinent dates, including ace Casing, cemented to sur	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 185' t From 145' t	0 5/8" Hole 7 5/8" 26.4#, J-55 Surfa oride D. ched to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks	details, and give pertinent dates, including ace Casing, cemented to sur	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 185' t From 145' t	o 5/8" Hole of 5/8" 26.4#, J-55 Surfatoride of to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks to 45' w/ 20 sks ected per NM regulations	details, and give pertinent dates, including ace Casing, cemented to sur	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 585' t From 145' t	o 5/8" Hole of 5/8" 26.4#, J-55 Surfatoride of to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks to 45' w/ 20 sks ected per NM regulations	details, and give pertinent dates, including ace Casing, cemented to sur	rface with 66 sks common
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 185' t From 145' t	o 5/8" Hole of 5/8" 26.4#, J-55 Surfatoride oride to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks to 45' w/ 20 sks ected per NM regulations	details, and give pertinent dates, including ace Casing, cemented to sur	
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 585' t From 145' t	o 5/8" Hole of 5/8" 26.4#, J-55 Surfatoride of to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks to 45' w/ 20 sks ected per NM regulations	details, and give pertinent dates, including ace Casing, cemented to sur	Pface with 66 sks common
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 585' t From 145' t	o 5/8" Hole of 5/8" 26.4#, J-55 Surfatoride oride to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks to 45' w/ 20 sks ected per NM regulations	details, and give pertinent dates, including ace Casing, cemented to sur	Pface with 66 sks common
Spudded 7/13/77 - 9 7/14/77 Set 90' of with 2% Calcium Chl Drilled to 2,028 T. Logged - copy attac 7/20/77 Plugged From 2,000' From 1,170' From 585' t From 145' t	o 5/8" Hole of 5/8" 26.4#, J-55 Surfatoride oride to 1,824' w/ 35 sks to 1,030' w/ 28 sks to 480' w/ 21 sks to 45' w/ 20 sks ected per NM regulations	details, and give pertinent dates, including ace Casing, cemented to sur	rface with 66 sks common