

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
Joel B. Burr, Jr.

3. ADDRESS OF OPERATOR NM 87401
300 W. Arrington, Suite 300, Farmington,

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
330' FNL and 2310' FWL
AT SURFACE:
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM 15646

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
N/A8. FARM OR LEASE NAME
Robinson - Coleman9. WELL NO.
210. FIELD OR WILDCAT NAME
Franciscian Lake Mesa Verde11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
13-20N-6W12. COUNTY OR PARISH
McKinley13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6758 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill 7 7/8" hole to total depth 2826'. Ran IES and FDC logs. Set 50 sacks class "B" cement plug from 2651 - 2826'. Set 5 1/2" 15.5# K-55 casing at 2487'. Float at 2458'. Cement with 100 sacks 65-35 poz + 6% gel followed by 225 sacks class "B" + 0.75% CFR2. Plug down 10:30 p.m. 7-3-78. Wait on cement.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jack D. Cook

TITLE

Agent

DATE

September 26, 1978

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: