

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
Oil

2. Name of Operator
NERDLIHC

3. Address & Phone No. of Operator
C/O NMOCD, 1000 Rio Brazos Road, Aztec, NM 87410

4. Location of Well, Footage, Sec., T, R, M
Sec 18, T-16-N, R-9-W, NMPM, McKinley County
Unit O, 330' FSL and 2310' FEL

API # (assigned by OCD)
30-031-20578

5. Lease Number
Fee

6. State Oil & Gas Lease #
Fee

7. Lease Name/Unit Name
Bullseye

8. Well No.
#10

9. Pool Name or Wildcat

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

This well was plugged under NMOCD Contract #00-521-25-205 per attached work report.

SIGNATURE

William F. Clark
William F. Clark, President, A-Plus Well

January 8, 2001

(This space for State use)

Approved by

ORIGINAL SIGNED BY E. VILLANUEVA

Title

Date

DEPUTY OIL & GAS INSPECTOR, DIST. #8

JAN - 8 2001

Daily Report

A - PLUS WELL SERVICE

16906

P.O. BOX 1979 • FARMINGTON, NM 87499
505-325-2627 • FAX (505) 325-1211Rig No #1 Date Multiple
Well No Ballouge #10 Location 0-18-16-9 Company Newkirk

FROM	TO	DESCRIPTION OF OPERATION
Sept 2000		- MO RU, Pull and LD 60 jts 2 7/8" 16g. (1860')
Oct 31, 2000		Wireline Bruce Martin Run 5 1/2" 6' Ring to Set 5 1/2" Plug Well CIBP @ 1740'
Wed 11-15-00		R-D CUDG & P-T #104. T/H with coiled TBG & TAG CIBP @ 1,746'. Circulate The Hole Clean with 17 BBLs WATER. Test CSG TO 500'. Hold 5 min OK. Plug #1 mix & Pump 18 SKS ^{15.6"} CEMENT, From 1,746' TO TAC @ 1,591'. POOH with TBG TO 1,014'. Load The Hole with 2 BBLs WATER. Plug #2 mix & Pump 27 SKS ^{15.6"} CEMENT, From 1,014' TO TAC @ 782'. POOH TO 250'. Circulate The Hole. POOH. R-D EQUIP. MAL. BRUCE MARTIN W/ALMACO ON LOC.
Mon 11-20-00		T/H with wireline & TAG TAC @ 773'. POOH. HENRY VILLANUEVA W/ALMACO ON LOC.
Mon 12-4-00		Dig out & cut Well Head off. 9 5/8" CSG cement @ surf. T/H with coiled TBG TO 190'. Load The Hole with 1 BBL WATER. Plug #3 mix & Pump 40 SKS ^{15.6"} CEMENT, From 190' with good cement Returns out The 5 1/2" CSG. POOH with coiled TBG. Set marker & top off 5 1/2" CSG with cement left in coiled TBG. BRUCE MARTIN W/ALMACO WAS ON LOC.
Dec 2000		No Equipment

Fuel & Motor Oil _____ Water Hauled _____
 Rental Equipment _____ Cement Retainers _____
 Cementing P-#1- 18 SKS ^{15.6"} P-#2- 27 SKS ^{15.6"} P-#3- 40 SKS + marker - 85 SKS (bid - 90 SKS)
 Wireline 5 1/2" 6' R, 5 1/2" CIBP P-#1 Well

CREW	NAME	UNIT #	MILEAGE	HOURS
Supervisor	Bell Clark	45		
Operator	Bob Stuart	131		
Helper	Sam Stuart	161		
Helper				
Helper				