

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

<p>1. Type of Well Oil</p> <p>2. Name of Operator Robert L. Bayless</p> <p>3. Address & Phone No. of Operator PO Box 168, Farmington, NM 87499 (505)327-2659</p> <p>4. Location of Well, Footage, Sec., T, R, M Unit A, 330' FNL and 330' FEL Section 29, T-16-N, R-6-W, NMPM, McKinley County</p>	<p style="text-align: right;">API # (assigned by OCD) 30-031-20606</p> <p>Lease Number Fee State Oil&Gas Lease #</p> <p>Lease Name/Unit Name Santa Fe Pacific RR</p> <p>Well No. #25</p> <p>Pool Name or Wildcat Miguel Creek Gallup</p> <p>Elevation: 6430' GL</p>
--	---

RECEIVED

AUG 10 1999

OIL CON. DIV.

DIST. 3

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

Robert L Bayless plugged and abandoned this well on July 15, 1999.

7-15-99 MORU. Load tubing with 1 bbl water and pressure test to 500#, OK. Unseat pump. LD 27 5/8" rods and 18' of 5/8" sub with pump. ND wellhead and NU flange with BOP, test. TOH and tally 23 joints 2-3/8" tubing with 8' mule shoe, total 706'. TIH and tag bottom at 750'. Circulate clean with 8 bbls water. Plug #1 with 15 sxs Class B cement from 750' to 547'. SI and WOC.

7-16-99 TIH with tubing; tag cement at 605'. Attempt to PT casing, leak 1-1/2 bpm at 400#. LD tubing. RU wireline truck. Perforate 2 squeeze holes at 100'. Establish circulation around 4-1/2" casing with 2 bbls water. Plug #2 with 40 sxs Class B cement with 2% CalCl2 from 100' to surface, circulate good cement around 4-1/2" casing. Shut in well and WOC. PU 1 joint tubing and tag cement 9' from surface, LD tubing. ND BOP. Dig out and cut off 4-1/2" casing. Mix 15 sxs Class B cement, fill 4-1/2" casing and install P&A marker. RD, MOL
H. Villaneuva, NMOCD, was on location.

SIGNATURE <u>Tom McCarthy</u>	Engineer	August 4, 1999
-------------------------------	----------	----------------

(This space is reserved for use by the Villaneuva)
Approved by _____

Title DEPUTY OIL & GAS INSPECTOR, DIST. 3

Date _____

AUG 10 1999