

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. IG-2229
7. Lease Name or Unit Agreement Name State
8. Well No. 11
9. Pool name or Wildcat Chaco Wash MV
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6115' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER <u>H₂O Injection</u>
2. Name of Operator <u>Brana Corporation</u>
3. Address of Operator <u>320 Gold Ave. S.W., Suite 1223, ABQ., N.M. 87102</u>
4. Well Location Unit Letter <u>A</u> : <u>330</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>28</u> Township <u>20N</u> Range <u>9W</u> NMPM <u>McKinley</u> County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work to begin the week of October 14, 1991.

Casing: 4 1/2", 10.5 lb/ft set at 540' GR.

Cemented with 80 Sks class "B". Circulated cement.

FBTD: 350' GR.

Perforations: 304'-338', 2 SPF.

Proposed Plugging Procedure: Release packer set at 290' GR. TOOHw/tubing and packer. Lay down packer. TIH w/tubing. Set a 100' cement plug from 338' to 238' using 8 Sks(9.44CF) class "B" cement. Set a 50' cement plug at surface with 4 Sks(4.72CF) class "B" cement. Install an appropriate dry hole marker.

RECEIVED

OCT 7 1991.

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Frank A. Welker TITLE Agent for Brana DATE 10-4-91
TYPE OR PRINT NAME Frank A. Welker TELEPHONE NO. 291-9502

(This space for State Use)

Original Signed by CHARLES GHOLSON

DEPUTY OIL & GAS INSPECTOR, DIST. #3

OCT 07 1991

APPROVED BY

DATE

CONDITIONS OF APPROVAL, IF ANY:

TOP Plug 100' minimum

WELL # State #11 Injection Well

A Sec. 28 T. 20 N., R. 9 W McKinley County
330' From N line, 660' From East line

Casing: $4\frac{1}{2}" @ 540'$ GR.

Perfs.: $304'-338'$

T.D. 566 GR.

