

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other ☐

2. NAME OF OPERATOR

Bird Oil Corp. c/o Bayless Drilling

3. ADDRESS OF OPERATOR

P.O. Box 2669, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2310' FSL & 1650' FWL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) T.D., set & cement csg. ☐

SUBSEQUENT REPORT ☐

RECEIVED
APR 11 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
APR 14 1983

CL. CON. DIV.
DST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-10-83 T.D. well @ 2200' @ 10:30 a.m. 4-9-83. Lay down drill pipe and collars. Ran 51 jts. of 4½" 10.5#/ft. J-55 casing as follows:

DESCRIPTION

KB to landing point
50 jts. 4½" 10.5#/ft. J-55 casing
1 insert float collar
1 jt. 4½" 10.5#/ft. J-55 casing
1 4½" cement filled guide shoe

LENGTH

10.01
2145.62
0.0
43.73
.65

2200.00

DEPTH

0-10
10-2156
2156
2156-2199
2199-2200

(continued on reverse)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Eileen Hare TITLE Agent DATE April 11, 1983

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

APR 12 1983

FARMINGTON DISTRICT

NMOCC

BY gta

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

(cont.)

Rigged up Halliburton. Cemented longstring with 551 ft³ (225 sx) Class B with 2% econolite tailed by 219 ft³ (150 sx) 50-50 pozmix containing 4% gel and 2% CaCl₂. Good circulation throughout job. Circulated cement to the surface. Bumped plug to 1000 psi. Plug down at 10:15 p.m. 4-9-83. Wait on completion.