5. LEASE

## UNITED STATES

SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for promosals to drill or to deepen or plug back to a different receiver, the form 3.31-C for vice the promosals to drill or to deepen or plug back to a different receiver, the form 3.31-C for vice the promosals to drill or to deepen or plug back to a different receiver, the form 3.31-C for vice the promosals to drill or to deepen or plug back to a different receiver, the form 3.31-C for vice the promosals to drill or to deepen or plug back to a different receiver, the form 3.31-C for vice the promosals to drill or to deepen or plug back to a different receiver. The promosals to drill or to deepen or plug back to a different receiver. The promosals to drill or to deepen or plug back to a different receiver. The promosals to different receivers the promosals to different receivers the promosals. The promosals to different receivers the promosals to different receivers the promosals. The promosals to different receivers the promosals to different receivers the promosals. The promosals the drill promosals the promosals to different receivers the promosals. The promosals the promosals the drill promosals the promosals to different receivers the promosals. The promosals the promosals the promosals the promosals the promosals the promosals the promosals. The promosals the		NM 17184	
SUNDING NOTICES AND REPORTS ON CONTROL OF STATE OF STAT	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIE	BE NAME
Bird Federal  9. WELL NO.  1. NAME OF OPERATOR Bird Oil Corp. c/o Bayless Drilling  3. ADDRESS OF OPERATOR P.O. Box 2669, Farmington, NM 87499  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990' FSL & 330' FSL (SWSW) AT TOP PROD. INTERVAL: Same AT TOP PROD. INTERVAL: Same AT TOTAL DEFTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT OFF FRACTURE TREAT SHOOT OR ACIDIZE PULL OR ALTER CASING WILLTIPLE COMPLETE CHANGE ZONES ABANDON'* (other) Spud, set SUTFace Csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations at measured and true vertical depths for all markers and zones pertinent to this work.)*  11. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations at measured and true vertical depths for all markers and zones pertinent to this work.)*  11. SPECIAL STATES AND	(Do not use this form for proposals to drill or to deepen or plug back to a different		
9. WELL NO. 12-13  12-13  13. ADDRESS OF OPERATOR P.O. BOX 2669, Farmington, NM 87499 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990' FSL & 330' FSL (SWSW) AT TOTAL DEPTH: Same AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND W. 17 MOTE: Report results of multiple completion or 20 pull. OR ALTER CASING MULTIPLE COMPLETE COMPLETE COMPLETE CHANGE ZONES ABANDON* (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent distaincluding estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations at measured and true vertical depths for all markers and zones pertinent to this work.)*  18. Subsurface Safety Valve: Manu. and Type Subsurface Safety Valve: Manu. and Subsurface	reservoir. Use Form 9-331-C for Such proposals.)	·i	
2. NAME OF OPERATOR Bird Oil Corp. c/o Bayless Drilling 3. ADDRESS OF OPERATOR P.O. Box 2669, Farmington, NM 87499 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 990 FSL & 330 FSL (SWSW) AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same OF OPERATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) OF REPORT, OR OTHER DATA  REQUEST FOR APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: OF REACTURE TREAT OF SUBSEQUENT REPORT OF: OF REPORT OF THE MEXICAL OF SUBSEQUENT REPORT OF: OF REPORT OF THE MEXICAL OF SUBSEQUENT REPORT OF: OF REPORT OF THE MEXICAL OF SUBSEQUENT REPORT OF: OF REPORT OF THE MEXICAL OF SUBSEQUENT REPORT OF THE MEXICAL OF THE ME	1. oil gy gas		
Bird Oil Corp. c/o Bayless Drilling  3. ADDRESS OF OPERATOR P.O. BOX 2669, Parmington, NM 87499  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990' FSL & 330' FSL (SWSW) AT SURFACE: Same AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON' Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data measured and true vertical depths for all markers and zones pertinent to this work.)*  18. Subsurface Safety Valve: Manu, and Type  Subsurface Safety Valve: Manu, and Type  Set @ 18  18. Thereby certify that the foregoing is true and correct	well well other	-	
3. ADDRESS OF OPERATOR P.O. BOX 2669, Farmington, NM 87499 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 990' FSL & 330' FSL (SWSW) AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING ONLY Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drifted, give subsurface locations as measured and true vertical depths for all markers and zones pertinent to this work.)*  18-33 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft <sup>3</sup> (65 sx) Class B with 2% CaCl <sub>2</sub> . Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type  Set @ 18  Subsurface Safety Valve: Manu. and Type  Set @ 18  Wildcat-Mesaverdo 11. SEC. T. R., M. OR BLK. AND SURVEY OF AREA.  Sec. 12, T19N, R5W 12. COUNTY OR PARISH 13. STATE MCKINJEY OR PARISH 13. STATE MC			- · · ·
P.O. Box 2669, Farmington, NM 87499  4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below) AT SURFACE: 990' FSL & 330' FSL (SWSW) AT TOP PROD, INTERVAL: Same AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 15. ELEVATIONS (SHOW DF, KDB, AND W)  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 16. CHACK APPROVAL TO: SUBSEQUENT REPORT OF: 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details, and give pertinent details, and give pertinent details, and give pertinent details and pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations as measured and true vertical depths for all markers and zones pertinent to this work.)  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft 3 (65 sx)  Class B with 2% CaCl. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.	Bird Oil Corp. c/o Bayless Drilling	10. FIELD OR WILDCAT NAME	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  AT SURFACE: 990' FSL & 330' FSL (SWSW) AT SURFACE: 990' FSL & 330' FSL (SWSW) AT SURFACE: Same AT TOP PROD. INTERVAL: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUTOFF			
below.) AT SURFACE: 990' PSL & 330' PSL (SWSW) AT SURFACE: 990' PSL & 330' PSL (SWSW) AT TOTAL DEPTH: Same  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KDB, AND W.  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KDB, AND W.  REPAIR WELL  PULL OR ALTER CASING  MULTIPLE COMPLETE  CHANGE ZONES  ASANDON*  (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft³ (65 sx)  Class B with 2% Cacl <sub>2</sub> . Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type  Set @			SURVEY OR
AT SURFACE: 990 FSD & 330 FSD (SWSW) AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KDB, AND W)  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT OF:  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations at measured and true vertical depths for all markers and zones pertinent to this work.)*  18. Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 121" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft 3 (65 sx)  Class B with 2% Cacl 2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.	below.)	Sec. 12, T19N, R5W	
AT TOTAL DEPTH: same  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  15. ELEVATIONS (SHOW DF, KDB, AND W)  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF  FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  DULL OR ALTER CASING  MULTIPLE COMPLETE  COLLOGICA  MULTIPLE CASING  MULTIPLE COMPLETE  COLLOGICA  MULTIPLE CASING  MULTIPLE CASING  MULTIPLE COMPLETE  COLLOGICA  MULTIPLE CASING  MUL	AT SOM ACE.		ATE
14. API NO.  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  15. ELEVATIONS (SHOW DF, KD8, AND WINDICATE NATURE OF NOTICE, REPORT OF)  16. CHECK APPROPOSAL TO: SUBSEQUENT REPORT OF:  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations at measured and true vertical depths for all markers and zones pertinent to this work.)*  18. Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 121" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft <sup>3</sup> (65 sx) Class B with 2% CaCl <sub>2</sub> . Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.		McKinley New	Mexico
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF	AI IOTAL DEPTH: same		
REQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF  FRACTURE TREAT  SHOOT OR ACIDIZE  SHOOT OR ACIDIZE  PULL OR ALTER CASING  MULTIPLE COMPLETE  CHANGE ZONES  ABANDON*  (other)  Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations an measured and true vertical depths for all markers and zones pertinent to this work.*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft 3 (65 sx)  Class B with 2% CaCl 2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.	16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
CHANGE ZONES  ABANDON* (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft (65 sx) Class B with 2% CaCl2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type  Set @	REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KD	B, AND WD)
CHANGE ZONES  ABANDON* (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft³ (65 sx) Class B with 2% CaCl2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type	DECUISOT FOR APPROVAL TO CURSTOUENT DEPORT OF ME		
CHANGE ZONES  ABANDON* (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft (65 sx) Class B with 2% CaCl2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type  Set @	REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF		
CHANGE ZONES  ABANDON* (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft (65 sx) Class B with 2% CaCl2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type  Set @	TEST WATER SHUT-OFF	<u>,                                     </u>	
CHANGE ZONES  ABANDON* (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft 3 (65 sx) Class B with 2% CaCl2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type	SHOOT OR ACIDIZE	.ω.β <b>3</b> - <b>.</b>	
CHANGE ZONES  ABANDON* (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-33 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft³ (65 sx) Class B with 2% CaCl2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type	REPAIR WELL	(NOTE: Report results of multiple com	nletion or zone
CHANGE ZONES  ABANDON* (other) Spud, set surface csg.  17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft³ (65 sx) Class B with 2% CaCl2. Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type	PULL OR ALTER CASING	change on Form 9-330.)	pietion or zone
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations at measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft <sup>3</sup> (65 sx) Class B with 2% CaCl <sub>2</sub> . Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type Set @ False. I hereby certify that the foregoing is true and correct	MULTIPLE COMPLETE	CALSUM	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations at measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft <sup>3</sup> (65 sx) Class B with 2% CaCl <sub>2</sub> . Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type Set @ False. I hereby certify that the foregoing is true and correct	CHANGE ZONES   GOVICIO	Col.	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent date including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations at measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft <sup>3</sup> (65 sx) Class B with 2% CaCl <sub>2</sub> . Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type Set @ False. I hereby certify that the foregoing is true and correct	ABANDON* Chyd sot symfaco csg	, d 1	
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations are measured and true vertical depths for all markers and zones pertinent to this work.)*  1-83 Spud well @ 4:45 p.m. 4-10-83. Drilled 96' of 12½" surface hole. Ran 96' of 8-5/8" surface casing. Cemented surface with 76.7 ft <sup>3</sup> (65 sx) Class B with 2% CaCl <sub>2</sub> . Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type	(other) Spaa, See Sufface Cosy.		
96' of 8-5/8" surface casing. Cemented surface with 76.7 ft <sup>3</sup> (65 sx) Class B with 2% CaCl <sub>2</sub> . Good circulation throughout job. Plug down @ 10:00 p.m. 4-10-83.  Subsurface Safety Valve: Manu. and Type Set @ Ft. I hereby certify that the foregoing is true and correct	including estimated date of starting any proposed work. If well is d	irectionally drilled, give subsurface le	tinent dates, ocations and
Subsurface Safety Valve: Manu. and Type Set @ F	96' of 8-5/8" surface casing. Cemented sur Class B with 2% CaCl <sub>2</sub> . Good circulation to	rface with 76.7 ft <sup>3</sup> (65	sx)
Subsurface Safety Valve: Manu. and Type Set @ F	10:00 p.m. 4-10-63.	-	1 1 22
18. I hereby certify that the foregoing is true and correct		in the second se	
18. I hereby certify that the foregoing is true and correct			41
18. I hereby certify that the foregoing is true and correct		•	8,28
18. I hereby certify that the foregoing is true and correct			•
18. I hereby certify that the foregoing is true and correct			4
18. I hereby certify that the foregoing is true and correct			
18. I hereby certify that the foregoing is true and correct		-	
The same of the sa	Subsurface Safety Valve: Manu. and Type	Set @	Ft.
SIGNED TITLE Agent DATE April 11, 1983	18. I hereby certify that the foregoing is true and correct		
\ \tag{\tag{\tag{\tag{\tag{\tag{\tag{		DATE April 11, 19	83
(This space for Federal or State office use)	SIGNED TITLE Agent		

\*See Instructions on Reverse Side