FARMINGIUN RESUURCE AREA

5mm

BY.....

UNITED STATES

DEPARTMENT OF THE INTERIOR	5. LEASE NM - 052931
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Navajo
SUNDRY NOTICES AND REPORTS OF	
(Do not use this form for proposals to drill or to deepen or plug be reservoir. Use Form 9–331–C for such proposals.)	pack to a different
1. oil - gas	8. FARM OR LEASE NAME Hanson
well XX well other	9. WELL NO.
2. NAME OF OPERATOR	42
Tesoro Petroleum Corporation	10. FIELD OR WILDCAT NAME SA NA
3. ADDRESS OF OPERATOR	South Hospah, Lower Hospah
8700 Tesoro Drive, San Antonio, TX	78286 11. SEC., T., R., M., OR BLK. AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY, below.) 	· •
AT SURFACE: 1770' FSL & 1280' FWL	Sec. 6 - T17N - R8W
AT TOP PROD. INTERVAL: same	12. COUNTY OR PARISH 13. STATE McKinley New Mexico
AT TOTAL DEPTH: same	McKinley New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURI	E OF NOTICE,
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT R	। 6886' ਵਾ
REQUEST FOR APPROVAL TO: SUBSEQUENT R TEST WATER SHUT-OFF	EPORT OF:
FRACTURE TREAT	in the state of th
SHOOT OR ACIDIZE	RECEIVED
REPAIR WELL	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE	00T 171983 change on Form 9-330.
CHANGE ZONES	
ABANDON*	RAMINES FOR RESOURCE AREA
	DIST. 3
 DESCRIBE PROPOSED OR COMPLETED OPERATION including estimated date of starting any proposed w measured and true vertical depths for all markers and 	IS (Clearly state all pertinent details, and give pertinent dates, ork. If well is directionally drilled, give subsurface locations and d zones pertinent to this work.)*
	lled 12½" hole to 93'. Set 82' of 8 5/8"
24#/ft J-55 csg and cement w/75	5 sks Class "B" w/3% CaCl to surface.
2) Drilled / //8" hole to TD, 1575	5' (10-8-83).
3) Ran Induction Electrical log 15	563-831
4) Ran 1583' of 5½' 15.5#/ft J-55	csg to 1574'. Set at 1574' and cemented
w/ 150 sks 50-50 rozhits w/ 2/6 ger	Valculated top 500 (10-8-83)
5) Prepare well and location to pe	ertorate Lower Hospah.
No.	
Subsurface Safety Valve: Manu. and Type None	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
Gav	rino Perez, Jr.
The state of	Production Mgmate 10-10-83
(This space for Fe	ederal or State office use)
APPROVED BY TITLE	ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:	007 0 0 1000
NM	OCC OCT 26 1983

*See Instructions on Reverse Side